

### **Technical datasheet**

# Alloy X-750 / W-Nr. 2.4669

A precipitation hardenable nickel-chromium alloy with excellent resistance to high temperature oxidation and combined with good high temperature mechanical properties.

### **Available products**

Product form	Size	Size range to
Sheet/plate	1.2 mm thickness	
Bar	15.0 mm diameter	60.0 mm diameter

### **Chemical composition (%)**

Ni	Cr	Fe	Ti	Al	Mn	Nb	Co	C
70.0 min	14.0-17.0	5.0-9.0	2.25-2.75	0.40-1.00	1.0 max	0.7-1.2	1.0 max	0.08 max

### **Major specifications**

ASTM B637	UNS N07750
AMS 5670, 5671, 5667, 5542, 5598	

### **Physical properties**

Density	8.28 g/cm <sup>3</sup>
Melting range	1393-1427°C

# Mechanical properties – typical room temperature properties

Yield strength	975 MPa
Tensile strength	1325 MPa
Elongation	23 %

# **Key attributes**

Alloy X-750 is similar to alloy 600 but is made age hardenable through additions of Al and Ti. It has excellent resistance to oxidation at temperatures up to 980°C combined with good high temperature mechanical properties. It retains high tensile strength up to 600°C and high creep and rupture strength to 800°C. The alloy exhibits good resistance to oxidisation in combustion gas environment at temperatures to 870°C. Alloy X-750 also has excellent mechanical properties in cryogenic environments. Due to this combination of properties Alloy X-750 has a wide range of applications from gas turbines for both aeroengines and industrial turbines to rocket component and nuclear reactors.

Alloy X-750 is readily machined, formed and welded by conventional processes and techniques. Please contact us for further details on forming, fabrication and welding consumables.

# **Applications**

Gas turbine components (both aero and industrial turbines)

Cryogenic applications

High temperature fasteners

**Springs** 

Nuclear reactor components

Pressure vessels

Rocket engines

All information is subject to change without notice. The properties correspond to the material in the heading. They may vary for other specifications. Please contact us for more details.

BIBUS METALS | info@bibusmetals.com | www.bibusmetals.com