



PLHE

This is progress:
In this planetary gearbox, precision and cost effectiveness meet

The **PLHE** is our ideal combination of economy and precision gearboxes. The preloaded tapered roller bearings of this planetary gearbox guarantee high rigidity even under maximum load. The high-performance seal provides increased protection against dust and water spray.

Cyclic torque **15 - 260 Nm**



Radial force **3200 - 6000 N**



Axial force **4400 - 8000 N**



Torsional backlash **7 - 12 arcmin**




Protection class **IP65**



Frame sizes

- 60
- 80
- 120



Economy Line



Equidirectional rotation



Square type output flange




Preloaded tapered roller bearings



Planet carrier in disc design



Option: Rack and pinion
Planetary gearbox (Details on page 158)




Coaxial gearbox



Spur gear



Preloaded tapered roller bearings



Extra long centering collar



Option: Splined output shaft (DIN 5480)



Option: Painted surface
– RAL 9005 Jet black

Detailed explanations of the technical features starting on page 201.

Code	Gearbox characteristics		PLHE060	PLHE080	PLHE120	p ⁽¹⁾	
	Service life ⁽²⁾	L _h	h	20,000		1 2	
	Efficiency ⁽³⁾	η	%	97			
				96			
	Min. operating temperature	T _{min}	°C	-25 (-13)			
	Max. operating temperature	T _{max}	(°F)	90 (194)			
	Protection class		IP65				
S	Standard lubrication		Grease (lifetime lubrication)				
F	Food grade lubrication		Grease (lifetime lubrication)				
	Installation position		Any				
S	Standard backlash	φ	arcmin	< 10	< 7	< 7	1
				< 12	< 9	< 9	2
	Torsional stiffness ⁽³⁾	C _{2t}	Nm / arcmin (lb _f .in/ arcmin)	2.6 - 4.4 (23 - 39)	7.3 - 11.6 (65 - 103)	18.5 - 26.0 (164 - 230)	1
				2.5 - 4.6 (22 - 41)	7.3 - 12.3 (65 - 109)	16.7 - 27.5 (148 - 243)	2
	Gearbox weight ⁽³⁾	m	kg (lb _m)	1.5 - 1.6 (3.4 - 3.5)	3.0 - 3.1 (6.6 - 6.7)	6.8 - 7.1 (15.1 - 15.7)	1
				1.7 - 1.8 (3.8 - 3.9)	3.5 - 3.6 (7.6 - 7.9)	8.5 - 9.0 (18.7 - 19.8)	2
S	Standard surface		Housing: Steel – heat-treated and post-oxidized (black)				
B	Painted surface ⁽⁴⁾		RAL 9005 Jet black				
	Running noise ⁽³⁾	L _{pA}	dB(A)	58	60	65	

Output shaft loads		PLHE060	PLHE080	PLHE120	p ⁽¹⁾	
Maximum radial force	F _{r max}	N	3200 (719)	5500 (1236)	6000 (1349)	1 2
Maximum axial force	F _{a max}	(lb _f)	3400 (764)	4500 (1012)	6500 (1461)	
Maximum tilting moment	M _{K max}	Nm (lb _f .in)	191 (1690)	383 (3393)	488 (4317)	

Input characteristics		PLHE060	PLHE080	PLHE120	p ⁽¹⁾	
Clamping system diameter input (Code)	D26	mm	11 (C)	19 (E) ⁽⁵⁾	24 (F) ⁽⁵⁾	1 2
			14 (D) ⁽⁵⁾	24 (F)	35 (G)	
			19 (E)	-	-	
Mass moment of inertia input ⁽³⁾⁽⁵⁾	J ₁	kgcm ² (lb _f .in.s ² 10 ⁻⁴)	0.090 - 0.198 (0.797 - 1.752)	0.370 - 0.775 (3.275 - 6.859)	1.390 - 2.486 (12.303 - 22.003)	1
			0.085 - 0.155 (0.752 - 1.372)	0.357 - 0.641 (3.160 - 5.673)	1.378 - 2.326 (12.196 - 20.587)	2
Average idle torque ⁽³⁾⁽⁵⁾	T ₀	Nm (lb _f .in)	0.15 - 0.50 (1 - 4)	0.30 - 0.90 (3 - 8)	0.65 - 1.75 (6 - 15)	1
			0.10 - 0.20 (1 - 2)	0.15 - 0.40 (1 - 4)	0.45 - 0.95 (4 - 8)	2
Max. bending moment based on the gearbox input flange	M _{b1}		8 (71)	16 (142)	40 (354)	

(1) Number of stages
 (2) Application specific configuration with NCP – www.neugart.com
 (3) The ratio-dependent values can be retrieved in Tec Data Finder – www.neugart.com
 (4) More information on page 183
 (5) Reference clamping system diameter

Output torques			PLHE060	PLHE080	PLHE120	i ⁽¹⁾	p ⁽²⁾
Cyclic torque ⁽³⁾⁽⁴⁾	T _{2z}	Nm (lb _r .in)	28 (248)	85 (752)	115 (1018)	3	1
			38 (336)	115 (1018)	155 (1372)	4	
			40 (354)	110 (974)	195 (1726)	5	
			25 (221)	65 (575)	135 (1195)	7	
			18 (159)	50 (443)	120 (1062)	8	
			15 (133)	38 (336)	95 (841)	10	
			44 (389)	130 (1151)	210 (1859)	9	2
			44 (389)	120 (1062)	260 (2301)	12	
			44 (389)	110 (974)	230 (2036)	15	
			44 (389)	120 (1062)	260 (2301)	16	
			44 (389)	120 (1062)	260 (2301)	20	
			40 (354)	110 (974)	230 (2036)	25	
			44 (389)	120 (1062)	260 (2301)	32	
			40 (354)	110 (974)	230 (2036)	40	
			18 (159)	50 (443)	120 (1062)	64	
			15 (133)	38 (336)	95 (841)	100	
Maximum torque ⁽³⁾⁽⁴⁾	T _{2max}	Nm (lb _r .in)	44 (389)	105 (929)	184 (1629)	3	1
			60 (531)	140 (1239)	245 (2168)	4	
			61 (540)	175 (1549)	310 (2744)	5	
			40 (354)	104 (920)	215 (1903)	7	
			28 (248)	80 (708)	192 (1699)	8	
			24 (212)	60 (531)	152 (1345)	10	
			70 (620)	182 (1611)	335 (2965)	9	2
			65 (575)	192 (1699)	415 (3673)	12	
			70 (620)	176 (1558)	365 (3231)	15	
			65 (575)	192 (1699)	415 (3673)	16	
			65 (575)	192 (1699)	415 (3673)	20	
			61 (540)	176 (1558)	365 (3231)	25	
			65 (575)	192 (1699)	415 (3673)	32	
			61 (540)	176 (1558)	365 (3231)	40	
			28 (248)	80 (708)	192 (1699)	64	
			24 (212)	60 (531)	152 (1345)	100	

PLHE


⁽¹⁾ Ratios (i=n₁/n₂)
⁽²⁾ Number of stages
⁽³⁾ Application specific configuration with NCP – www.neugart.com
⁽⁴⁾ Based on reference clamping system diameter

Output torques			PLHE060	PLHE080	PLHE120	$i^{(1)}$	$p^{(2)}$
Continuous torque ⁽³⁾	T_{2D}	Nm (lb _r .in)	23 (204)	43 (381)	97 (859)	3	1
			25 (221)	95 (841)	131 (1159)	4	
			25 (221)	93 (823)	165 (1460)	5	
			19.5 (173)	55 (487)	114 (1009)	7	
			15 (133)	42 (372)	102 (903)	8	
			12.5 (111)	32 (283)	80 (708)	10	
			30 (266)	88 (779)	178 (1575)	9	2
			32 (283)	102 (903)	220 (1947)	12	
			35 (310)	93 (823)	195 (1726)	15	
			35 (310)	102 (903)	220 (1947)	16	
			37 (327)	102 (903)	220 (1947)	20	
			34 (301)	93 (823)	195 (1726)	25	
			37 (327)	102 (903)	220 (1947)	32	
			34 (301)	93 (823)	195 (1726)	40	
			15 (133)	42 (372)	102 (903)	64	
			12.5 (111)	32 (283)	80 (708)	100	

Input speeds			PLHE060	PLHE080	PLHE120	$i^{(1)}$	$p^{(2)}$				
Continuous input speed ⁽³⁾⁽⁴⁾	n_{1D}	rpm	2250	2550	1350	3	1				
			3400	2300	1600	4					
			3950	2800	1800	5					
			4500	3800	2500	7					
			4500	4000	3150	8					
			4500	4000	3500	10					
			4500	3850	1750	9	2				
			4500	4000	2000	12					
			4500	4000	2550	15					
			4500	4000	2300	16					
			4500	4000	2850	20					
			4500	4000	3500	25					
			4500	4000	3500	32					
			4500	4000	3500	40					
			4500	4000	3500	64					
			4500	4000	3500	100					
			Max. mechanical input speed ⁽³⁾	n_{1max}	rpm	13000		7000	6500		

Output torques			PLHE060	PLHE080	PLHE120	$i^{(1)}$	$p^{(2)}$
Emergency stop torque ⁽⁴⁾⁽⁵⁾	T_{2Stop}	Nm (lb _r .in)	60 (531)	150 (1328)	375 (3319)	3	1
			80 (708)	200 (1770)	500 (4425)	4	
			80 (708)	220 (1947)	500 (4425)	5	
			80 (708)	178 (1575)	340 (3009)	7	
			80 (708)	190 (1682)	380 (3363)	8	
			75 (664)	200 (1770)	480 (4248)	10	
			88 (779)	260 (2301)	500 (4425)	9	2
			88 (779)	240 (2124)	520 (4602)	12	
			88 (779)	220 (1947)	500 (4425)	15	
			88 (779)	240 (2124)	520 (4602)	16	
			88 (779)	240 (2124)	520 (4602)	20	
			80 (708)	220 (1947)	500 (4425)	25	
			88 (779)	240 (2124)	520 (4602)	32	
			80 (708)	220 (1947)	500 (4425)	40	
			80 (708)	190 (1682)	380 (3363)	64	
			75 (664)	200 (1770)	480 (4248)	100	

(1) Ratios ($i=n_1/n_2$)
 (2) Number of stages
 (3) Application specific configuration with NCP – www.neugart.com
 (4) Based on reference clamping system diameter
 (5) Permitted 1000 times



Drawing corresponds to a PLHE060 / 1-stage / smooth output shaft / 11 mm clamping system / motor adaptation – one part / B5 flange type motor

⁽¹⁾ The dimensions vary with the motor/gearbox flange. The input flange dimensions can be retrieved for each specific motor in Tec Data Finder at www.neugart.com

Geometry ⁽²⁾			PLHE060	PLHE080	PLHE120	p ⁽³⁾	Code
Pitch circle diameter output	D1		68 (2.677) - 75 (2.953)	85 (3.346)	120 (4.724)		
Mounting bore output	D2	4x	5.5 (0.217)	6.5 (0.256)	9.0 (0.354)		
Shaft diameter output	D3	k6	16 (0.630)	22 (0.866)	32 (1.260)		
Shaft collar output	D4		35 (1.378)	40 (1.575)	45 (1.772)		
Centering diameter output	D5	g7	60 (2.362)	70 (2.756)	90 (3.543)		
Housing diameter	D6		60 (2.362)	80 (3.150)	115 (4.528)		
Diagonal dimension output	D7		92 (3.622)	100 (3.937)	140 (5.512)		
Flange cross section output	Q1	■	70 (2.756)	80 (3.150)	110 (4.331)		
Min. total length	L1		127 (5.000)	159 (6.260)	199.5 (7.854)	1	
			139.5 (5.492)	177 (6.969)	227 (8.937)	2	
Housing length	L2		55 (2.165)	69.5 (2.736)	64 (2.520)	1	
			67.5 (2.657)	87 (3.425)	91.5 (3.602)	2	
Shaft length output	L3		48 (1.890)	56 (2.205)	88 (3.465)		
Centering depth output	L7		19 (0.748)	17.5 (0.689)	28 (1.102)		
Flange thickness output	L8		7 (0.276)	8 (0.315)	10 (0.394)		
Motor shaft diameter j6/k6	D20		More information on page 191/192				
Clamping system diameter input	D26		More information on page 42				
Output shaft with feather key (DIN 6885-1)			A 5x5x25	A 6x6x28	A 10x8x50		
Feather key width (DIN 6885-1)	B1		5 (0.197)	6 (0.236)	10 (0.394)		A
Shaft height including feather key (DIN 6885-1)	H1		18 (0.709)	24.5 (0.965)	35 (1.378)		
Shaft length from shoulder	L4		28 (1.102)	36 (1.417)	58 (2.283)		
Feather key length	L5		25 (0.984)	28 (1.102)	50 (1.969)		
Distance from shaft end	L6		2 (0.079)	4 (0.157)	4 (0.157)		
Center hole (DIN 332, type DR)	C		M5x12.5	M8x19	M12x28		
Smooth output shaft							
Shaft length from shoulder	L4		28 (1.102)	36 (1.417)	58 (2.283)		B
Spined output shaft (DIN 5480)			W16x0,8x18x6m	W22x1,25x16x6m	W32x1,25x24x6m		
Width of gearing	L _v		15 (0.591)	15 (0.591)	15 (0.591)		C
Shaft length output	L3		46 (1.811)	46 (1.811)	56 (2.205)		
Shaft length from shoulder	L4		26 (1.024)	26 (1.024)	26 (1.024)		
Center hole (DIN 332, type DR)	C		M5x12.5	M8x19	M12x28		

⁽²⁾ Dimensions in mm

⁽³⁾ Number of stages