



Agitator drive eco-Seal^{V2}



All dimension in mm.

Drive sizes	eco-Seal ^{V2} zone separation flange aluminium Art. Nr.	eco-Seal Pro ^{V2} zone separation flange stainless steel Art. Nr.	Medium air consumption	A	B
eco-Seal 450 ^{V2} with threaded hub M12	5083	5069	25 l/min	23	Ø25
eco-Seal 900 ^{V2} with threaded hub M12	5085	5070	50 l/min	23	Ø25
eco-Seal 1800 ^{V2} with threaded hub M16	5086	5071	100 l/min	24	Ø28
eco-Seal 3600 ^{V2} with threaded hub M16	5088	5072	200 l/min	24	Ø28
eco-Seal 450 with eco-Quick ^{V2} (quick-change system for agitator shafts)	6010	6014	25 l/min	51	Ø39
eco-Seal 900 with eco-Quick ^{V2} (quick-change system for agitator shafts)	6011	6015	50 l/min	51	Ø39
eco-Seal 1800 with eco-Quick ^{V2} (quick-change system for agitator shafts)	6012	6016	100 l/min	53	Ø44
eco-Seal 3600 with eco-Quick ^{V2} (quick-change system for agitator shafts)	6013	6017	200 l/min	53	Ø44

WE GENERATE MOVEMENT IN SPECIAL ENVIRONMENTS.



Variants	C	D	E	F	G	H	Wrench size drive hub	Torque	Rotation speed	Radial load Fr	Axial load Fa
eco-Seal 450 V2	146.5	75	91.5	10	6	105	SW21	4 Nm	0-300 rpm	400 N	100 N
with transmission 1:2	188.5	75	91.5	10	6	105	SW21	2 Nm	0-600 rpm	400 N	100 N
with transmission 3:1	188.5	75	91.5	10	6	105	SW21	12 Nm	0-100 rpm	400 N	100 N
with transmission 9:1	214.5	75	91.5	10	6	105	SW21	36 Nm	0-33 rpm	400 N	100 N
eco-Seal 900 V2	161	75	91.5	10	6	105	SW21	8 Nm	0-300 rpm	400 N	100 N
with transmission 1:2	203	75	91.5	10	6	105	SW21	4 Nm	0-600 rpm	400 N	100 N
with transmission 3:1	203	75	91.5	10	6	105	SW21	24 Nm	0-100 rpm	400 N	100 N
with transmission 9:1	229	75	91.5	10	6	105	SW21	72 Nm	0-33 rpm	400 N	100 N
eco-Seal 1800 V2	169	75	93.5	12	8	169	SW24	16 Nm	0-300 rpm	800 N	200 N
with transmission 1:2	219	75	93.5	12	8	169	SW24	8 Nm	0-600 rpm	800 N	200 N
with transmission 3:1	219	75	93.5	12	8	169	SW24	48 Nm	0-100 rpm	800 N	200 N
with transmission 9:1	250.5	75	93.5	12	8	169	SW24	144 Nm	0-33 rpm	800 N	200 N
eco-Seal 3600 V2	191	75	93.5	12	8	169	SW24	32 Nm	0-300 rpm	800 N	200 N
with transmission 1:2	241	75	93.5	12	8	169	SW24	16 Nm	0-600 rpm	800 N	200 N
with transmission 3:1	241	75	93.5	12	8	169	SW24	96 Nm	0-100 rpm	800 N	200 N
with transmission 9:1	272.5	75	93.5	12	8	169	SW24	288 Nm	0-33 rpm	800 N	200 N

WE GENERATE MOVEMENT IN SPECIAL ENVIRONMENTS.