

G25 Specifications

Port Dimensions (40.1 GPM Max.)

Intake & discharge connection:

Aluminum (ADC-12)	1" Female NPT
Air inlet (incl. ball valve):	3/8" Female NPT
Air exhaust (incl. silencer):	3/4" Female NPT

Maximum Liquid Temperature*

Diaphragm Material	Temperature
Buna N	180°F (82°C)
Hytrel® (TPE)	248°F (120°C)
Santoprene® (TPO)	212°F (100°C)
PTFE	212°F (100°C)

* The maximum liquid temperature for metal pumps is determined by the elastomer (diaphragm material).

Air Supply Pressure (All Models)

20 – 100 PSI (1.4 – 7 kgf/cm²)

Discharge Volume Per Cycle

Rubber diaphragm: 0.158 gallons

PTFE diaphragm: 0.118 gallons

Maximum Cycles Per Minute

Rubber diaphragm: 253

PTFE diaphragm: 297

Maximum Size Solid

1/8" (3 mm)


Air Motor

Aluminum air motor standard on metal pumps.

Valve Type

Ball

Notes: Santoprene® fitted pumps include EPDM wetted o-rings.




Aluminum (NPT)

Dimensions: 10.04"L x 8.27"W x 12.44"H

Net Wt.: 20.3 lbs. (9.2 kg)

Shipping Wt.: 25 lbs.

Model Number Nomenclature



G25 Series Models

G25AH	G25AS
G25AN	G25AT




Yamada America, Inc. 955 E. Algonquin Rd., Arlington Heights, IL 60005
USA Toll-Free: 800-990-7867 | Phone: 847-631-9200 | Fax: 847-631-9273
Email: sales@yamadapump.com | Web: yamadapump.com

© 2025 Yamada America, Inc.


G25A Performance Curve - Rubber

Rubber Diaphragm Performance Curve



G25A Performance Curve - PTFE

PTFE Diaphragm Performance Curve




Yamada America, Inc. 955 E. Algonquin Rd., Arlington Heights, IL 60005
USA Toll-Free: 800-990-7867 | Phone: 847-631-9200 | Fax: 847-631-9273
Email: sales@yamadapump.com | Web: yamadapump.com

© 2025 Yamada America, Inc.



BIBUS s.r.o.
+420 547 125 300
www.bibus.cz

G25 Aluminum



Yamada America, Inc. 955 E. Algonquin Rd., Arlington Heights, IL 60005
USA Toll-Free: 800-990-7867 | Phone: 847-631-9200 | Fax: 847-631-9273
Email: sales@yamadapump.com | Web: yamadapump.com

© 2025 Yamada America, Inc.



BIBUS s.r.o.
+420 547 125 300
www.bibus.cz

AutoCAD® is a registered trademark of Autodesk, Inc.

Hytrel® is a registered trademark of E.I. du Pont de Nemours and Company.

Kynar® is a registered trademark of Arkema.

Nordel™ is a trademark of DuPont Dow Elastomers.

Ryton® is a registered trademark of Chevron Phillips Chemical Company.

Santoprene® is a registered trademark of Advanced Elastomer Systems.

Viton® is a registered trademark of DuPont Performance Elastomers.

Swagelok™ & VCR™ are trademarks of the Swagelok Companies.

Flaretek® is a registered trademark of Entegris.

Garlock ONE-UP® is a registered trademark of W.L. Gore & Associates.

Yamada® is a registered trademark of Yamada America, Inc.

SolidPRO Designed to Pump Fluids Containing Solids® is a registered trademark of Yamada America, Inc.

Xtreme Duty Pro XDP® is a registered trademark of Yamada America, Inc.

The Proof's in the Pump® is a registered trademark of Yamada America, Inc.

The Proof is in the Pump® is a registered trademark of Yamada America, Inc.

Engineered to Perform. Designed to Outlast.® is a registered trademark of Yamada America, Inc.

Due to Yamada's continued commitment to product improvement, specifications may change without notice.



Yamada America, Inc. 955 E. Algonquin Rd., Arlington Heights, IL 60005
USA Toll-Free: 800-990-7867 | Phone: 847-631-9200 | Fax: 847-631-9273
Email: sales@yamadapump.com | Web: yamadapump.com

© 2025 Yamada America, Inc.