



www.samway.com
sales@samway.com

| Main Specification | SAMWAY P20D |
|----------------------|-----------------|
| Max Hydraulic Hose | 1 1/2" 4SP |
| Crimping Range mm | 4-65 |
| Die Type | P20 |
| Master Die Length mm | 80 |
| Max Opening mm | +26 |
| Motor KW | 3 |
| Crimping Force KN | 1700 |
| Crimpings Per Hour | 1800 |
| Control | Digital Control |
| Foot pedal | Included |
| Die Rack | Included |
| Quick Change Tool | Included |
| Backstop Device | Optional |
| Control by Pressure | Optional |
| Noise Level dBA | 65 |
| Protection Class | IP56 |
| L*W*H mm | 680*600*1400 |
| Weight KG | 270 |

P20D

| Benefit: |
|------------------------------------|
| Digital Precision Control |
| Quick Change Tool and Die rack |
| Energy Saving and Safety Operation |
| TUV CE Approved |

Standard Die Sets Included:

| | | | | | | | | | | | | | |
|---------|-----|-----|----|----|----|----|----|----|----|----|----|-----|-----|
| Die No. | 10* | 12* | 14 | 16 | 19 | 22 | 26 | 30 | 34 | 39 | 45 | 51* | 57* |
| Length | 55 | 55 | 55 | 55 | 55 | 55 | 75 | 75 | 90 | 90 | 90 | 90 | 90 |

* Optional Die Sets Upon Request