

easyE-i
the intelligent actuator
with slim design

Bansbach
easylift

EEL-S3/S4 Charger



Introduction

The Bansbach EEL- S3/S4 series is a range of battery-based actuator controllers developed especially for mobile applications. It is supplied with a NiMH battery. The NiMH chargers can be supplied with medical approval (EN60601-1).

Technical data and model designation

Charging voltage:	24VDC
Operating temperature:	5°C to 40°C
Relative humidity:	20% to 70%
Atmospheric pressure:	1atm
Max. operating attitude:	2000m
Battery technology:	NiMH

Model designation and label:

EEL-CHNI-US/EU: NiMH charger with external power supply

To secure long lifetime of NiMH batteries,
we strongly recommend to recharge the batteries at least every 3 months.

Preparation

Before the system may be used, the battery must be charged using the accompanying charger.
It takes 5-8 hours to fully charge a battery.



EEL-CHNI-US/EU

NiMH charger with external power supply

The flyer is subject to technical alterations and printing

Bansbach easylift GmbH

Barbarossastraße 8
D-73547 Lorch

Tel. +49 (0) 7172/9107-0
Fax +49 (0) 7172/9107-44

info@bansbach.de
www.bansbach.de

Bansbach
easylift

02/2023