



Elastomer Jaw Couplings

RINGFEDER® ECE 6518


Type with Freely Combinable Cast Iron Hubs and Elastomer Spiders of Various Hardnesses




Hub Designs



Hub Design 1



Hub Design 1a



Hub Design 1b

Size	Hub Design	d _{1kmin} -d _{1kmax}	d _{2kmin} -d _{2kmax}	D	C ₁	C ₂	D ₁	H ₃	I	L	L ₃
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
38	1	12 - 40	12 - 40	80	45	45	66	24	22,5	114	37
38	1a	12 - 48	12 - 48	80	45	45	78	24	22,5	114	37
38	1b	12 - 48	12 - 48	80	70	70	78	24	35	164	62
42	1	14 - 45	14 - 45	95	50	50	75	26	25	126	40
42	1a	14 - 55	14 - 55	95	50	50	94	26	25	126	40
42	1b	14 - 55	14 - 55	95	75	75	94	26	37,5	176	65
48	1	15 - 52	15 - 52	105	56	56	85	28	28	140	45
48	1a	15 - 62	15 - 62	105	56	56	104	28	28	140	45
48	1b	15 - 62	15 - 62	105	80	80	104	28	40	188	69
55	1	20 - 60	20 - 60	120	65	65	98	30	32,5	160	52
55	1a	20 - 74	20 - 74	120	65	65	118	30	32,5	160	52
55	1b	20 - 74	20 - 74	120	90	90	118	30	45	210	77

To continue see next page

Elastomer Jaw Couplings RINGFEDER® ECE 6518

Size	Hub Design	d _{1kmin} -d _{1kmax}	d _{2kmin} -d _{2kmax}	D	C ₁	C ₂	D ₁	H ₃	I	L	L ₃
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
65	1	22 - 70	22 - 70	135	75	75	115	35	37,5	185	61
65	1a	22 - 80	22 - 80	135	75	75	133	35	37,5	185	61
65	1b	22 - 80	22 - 80	135	100	100	133	35	50	235	86
75	1	30 - 80	30 - 80	160	85	85	135	40	42,5	210	69
75	1a	30 - 95	30 - 95	160	85	85	158	40	42,5	210	69
75	1b	30 - 95	30 - 95	160	85	85	158	40	55	260	84
90	1	40 - 97	40 - 97	200	100	100	160	45	50	245	81
90	1a	40 - 110	40 - 110	200	100	100	198	45	50	245	81
90	1b	40 - 110	40 - 110	200	125	125	198	45	62,5	295	106

Size	Hub Design	T _{KN} ¹⁾	d _{bz}	D _G	T _A	G _w
		Nm	mm	mm	Nm	kg
38	1	190	38	5	2	2,00
38	1a	190	38	5	2	2,40
38	1b	190	38	5	2	3,6
42	1	265	46	5	2	3,20
42	1a	265	46	5	2	3,8
42	1b	265	46	5	2	5,50
48	1	310	51	5	2	4,96
48	1a	310	51	5	2	5,45
48	1b	310	51	5	2	7,51
55	1	410	60	5	2	6,6
55	1a	410	60	5	2	7,50
55	1b	410	60	5	2	10,20
65	1	940	68	5	2	10,10
65	1a	940	68	5	2	11,50
65	1b	940	68	5	2	15,00
75	1	1920	80	6	6	16,00
75	1a	1920	80	6	6	18,20
75	1b	1920	80	6	6	21,20
90	1	3550	100	10	17	27,50
90	1a	3550	100	10	17	36,30
90	1b	3550	100	10	17	44,80

1) T_{KN} is specified for corresponding standard elastomer spider.

Coupling sizes 38-55: Yellow elastomer spider (92 SH A). Coupling sizes 65-90: Red elastomer spider (98 SH A).

To continue see next page

Elastomer Jaw Couplings RINGFEDER® ECE 6518

Technical Data of Elastomer Spiders

Size	Hardness	n_{max}	T_{KN}	T_{KW}	T_{Kmax}	ψ	C_{Tdyn} at $1 \cdot T_{KN}$	C_{Tdyn} at $0,5 \cdot T_{KN}$	C_{Tdyn} at $0,25 \cdot T_{KN}$	d_{bZ}	ΔK_a at $n = 1500$ 1/min	ΔK_r at $n = 1500$ 1/min	ΔK_w at $n = 1500$ 1/min	ϕ at T_{Kmax}
		1/min	Nm	Nm	Nm		10^3 Nm/rad	10^3 Nm/rad	10^3 Nm/rad	mm	mm	mm	degrees	degrees
38	64 SH D	8300	405	105	810	0,75	38,14	22,41	15,54	38	-0,7 +1,8	0,21	0,9	3,6
38	92 SH A	8300	190	49	380	0,8	9,8	6,42	4,59	38	-0,7 +1,8	0,28	1	5
38	98 SH A	8300	325	85	650	0,8	30,89	22,41	15,54	38	-0,7 +1,8	0,28	1	5
42	64 SH D	7000	560	146	1120	0,75	60,4	45,5	29,8	46	-1 +2	0,23	0,9	3,6
42	92 SH A	7000	265	69	530	0,8	15,4	10,4	7,4	46	-1 +2	0,32	1	5
42	98 SH A	7000	450	117	900	0,8	45,5	33,2	23,0	46	-1 +2	0,32	1	5
48	64 SH D	6350	655	170	1310	0,75	71,0	53,5	35,0	51	-1 +2,1	0,25	1	3,6
48	92 SH A	6350	310	81	620	0,8	17,8	12,0	8,6	51	-1 +2,1	0,36	1,1	5
48	98 SH A	6350	525	137	1050	0,8	52,3	38,1	26,4	51	-1 +2,1	0,36	1,1	5
55	64 SH D	5550	825	215	1650	0,75	92,3	69,5	45,5	60	-1 +2,2	0,27	1	3,6
55	92 SH A	5550	410	107	820	0,8	24,5	16,5	11,8	60	-1 +2,2	0,38	1,1	5
55	98 SH A	5550	685	178	1370	0,8	70,6	51,4	35,6	60	-1 +2,2	0,38	1,1	5
65	64 SH D	4950	1175	306	2350	0,75	141,1	102,5	59,8	68	-1 +2,6	0,3	1,1	3,6
65	92 SH A	4950	590	160	1220	0,8	40,4	27,8	19,8	68	-1 +2,6	0,42	1,2	5
65	98 SH A	4950	940	244	1880	0,8	100,7	73,7	51,0	68	-1 +2,6	0,42	1,2	5
75	64 SH D	4150	2400	624	4800	0,75	294,4	213,8	124,8	80	-1,5 +3	0,34	1,1	3,6
75	92 SH A	4150	1220	326	2500	0,8	84,6	58,1	41,4	80	-1,5 +3	0,48	1,2	5
75	98 SH A	4150	1920	499	3840	0,8	209,6	153,5	106,3	80	-1,5 +3	0,48	1,2	5
90	64 SH D	3300	4500	1128	9000	0,75	550,5	338,4	183,3	100	-1,5 +3,4	0,36	1,1	3,6
90	92 SH A	3300	2350	610	4700	0,8	158,7	109,1	77,7	100	-1,5 +3,4	0,5	1,2	5
90	98 SH A	3300	3550	880	7100	0,8	413,4	273,0	134,2	100	-1,5 +3,4	0,5	1,2	5

 T_{KN} = Nominal torque of coupling given in Nm

Continuous torque which can be transmitted throughout the entire speed range, taking into consideration operational factors such as ambient temperatures and torsional stiffness.

 T_{Kmax} = Maximum torque of coupling given in Nm

Torque which can be transmitted as dynamic load $\geq 10^5$ times or 5×10^4 as alternating load, respectively, during the entire operating life of the coupling, taking into account the operating factors.

 T_{KW} = Alternating torque of coupling given in Nm

Amplitude of the permissible continuous torque fluctuation with max. $f = 10$ Hz and a basic load up to T_{KN} .

To continue see next page

Elastomer Jaw Couplings RINGFEDER® ECE 6518

Explanations

$d_{1k,2kmin}$ = Min. bore diameter with keyway acc. to DIN 6885-1	D_G = Thread	ΔK_a at $n = 1500$ 1/min = Max. permissible axial misalignment at $n = 1500$ 1/min
$d_{1k,2kmax}$ = Max. bore diameter with keyway acc. to DIN 6885-1	T_A = Max. tightening torque of the clamping screws	ΔK_r at $n = 1500$ 1/min = Max. permissible radial misalignment at $n = 1500$ 1/min
D = Max. outer diameter	G_w = Weight	ΔK_w at $n = 1500$ 1/min = Max. permissible angular misalignment at $n = 1500$ 1/min
C_1 = Guided length in hub bore d_1	n_{max} = Max. rotational speed	ϕ at T_{Kmax} = Torsional angle at T_{Kmax}
C_2 = Guided length in hub bore d_2	T_{KW} = Transmissible torque for changing direction of rotation	
D_1 = Outer diameter hub	T_{Kmax} = Max. transmissible torque	
H_3 = Length of damping component	ψ = Relative damping	
I = Distance between center screw hole and hub end	C_{Tdyn} at $1 \cdot T_{KN}$ = Dynamic torsional stiffness at $1 \cdot T_{KN}$	
L = Total length	C_{Tdyn} at $0,5 \cdot T_{KN}$ = Dynamic torsional stiffness at $0,5 \cdot T_{KN}$	
L_3 = Section length	C_{Tdyn} at $0,25 \cdot T_{KN}$ = Dynamic torsional stiffness at $0,25 \cdot T_{KN}$	
T_{KN} = Transmissible torque at given T_A		
d_{bz} = Inner diameter elastomer spider		

Technical Information

- All dimensions are in millimeters, unless otherwise specified.
- Hubs made of cast iron, elastomer spiders made of polyurethane.
- Shaft tolerance to be within fit tolerance: g6, h7.
- For coupling sizes 38-55, as standard with yellow elastomer spider (92 SH A).
For coupling sizes 65-90, as standard with red elastomer spider (98 SH A).
- Different hub designs can be combined. Hubs optionally available without bore.
- Available are: Complete couplings, single hubs, single elastomer spiders.
- The values given for max. permissible axial, angular and radial shaft misalignment may not occur simultaneously.

Ordering example

Series	Type	Size	Design Hub 1	Bore diameter d_{1k}	Design Hub 2	Bore diameter d_{2k}	Elastomer Spider Hardness
ECE	6518	65	1	35	1	38	98 SH A

Further information on
RINGFEDER® ECE 6518
 on www.ringfeder.com

Disclaimer of liability

All technical details and notes are non-binding and cannot be used as a basis for legal claims. The user is obligated to determine whether the represented products meet his requirements. We reserve the right to carry out modifications at any time in the interests of technical progress.