

AIR BRAKE FITTINGS SERIES 9000

Brake safely
with our fittings



SOLUTIONS FOR THE TRANSPORTATION SECTOR

Being one of our three strategic business sectors, Camozzi Automation offers the Transportation industries a wide range of products. These products are ready for use in the harshest conditions, are reliable and efficient, in order to keep you moving.

In close cooperation with our customers and partners, we develop and produce standard products and customised solutions, always focussing on three main targets: **high performance, smart design and excellent quality**.

Developing products that can operate under extreme temperatures, in dirty or corrosive environments and tolerant of high mechanical loads and vibrations is **the mission** that drives our experienced and motivated engineers. A remarkable level of design and production know-how, combined with an enterprising spirit and a commitment to listen to customers, is for us the **key to success** in the **Transportation** sector.

Our **worldwide customer base** consists of leading OEMs, Tier 1 System Suppliers, Component Manufacturers, Body Builders and well-known players in the Aftermarket and Repair business. We always follow one leading principle: **"The customer first – always"**.

Camozzi Automation's long history in the **Transportation** sector has brought us into the supply chain of many different vehicle classes, including **Road, Off-Road** and **Rail** operations.

We are active in all the major application fields, including **Chassis, Cabin & Body, Mobile Automation** and **Powertrain**.



Our offering starts from fittings for multiple fluids like air, fuel, water, oil or grease and extends over a wide range of control valves for gases & fluids, to pneumatic and electric actuators, filters, regulators and other complementary products. This comprehensive range makes us **the right partner for your project.**

Connection or Actuation, On/Off or Proportional, Analogue or CAN-BUS, IATF 16949 or IRIS, **we talk your language.**

TRUCK & TRAILER



BUS & COACH



OFF HIGHWAY



PASSENGER CAR & LIGHT DUTY CV



RAILWAY



General index

Straight connectors

	Page
 Mod. 9512 Straight fittings	13
 Mod. D6512 Straight fittings	13
 Mod. 9510 Straight fittings	14
 Mod. 9463 Straight fittings with female thread	14
 Mod. 9590 Bulkhead connectors	14
 Mod. 9590 Bulkhead connectors Mod. 9590 with 24° cone	15
 Mod. 9592 Bulkhead connectors	15

Shaped non-swivel connectors

	Page
 Mod. 9502 Elbow fittings	16
 Mod. 9500 Elbow fittings	16
 Mod. 9412 Branch Tee fittings	17
 Mod. 9410 Branch Tee fittings	17
 Mod. 9422 Run Tee fittings	18
 Mod. 9420 Run Tee fittings	18
 Mod. 9102 135° Elbow fittings	18
 Mod. 9555 Plug-In Elbow connector	19
 Mod. 9450 Y fittings	19
 Mod. 9402 Elbow fittings	19

Shaped swivel connectors

	Page
 Mod. D2912 Swivel studs	20
 Mod. D2993 Bulkhead swivel studs	20
 Mod. 9919 Bulkhead swivel connectors	20
 Mod. 9707 Anti-rotation ring	21
 Mod. 9520 Swivel Elbow fittings	21
 Mod. 9430 Swivel Branch Tee fittings	21
 Mod. 9440 Swivel Run Tee fittings	22
 Mod. D2220 Swivel Elbow adaptors	22
 Mod. D2260 Swivel Branch Tee adaptors	22
 Mod. D2270 Swivel Run Tee adaptors	23
 Mod. D2210 Swivel 135° adaptors	23

Inline connectors

	Page
 Mod. 9580 Straight connectors	24
 Mod. 9592 Bulkhead connectors	24
 Mod. 9851 Barb connectors	25
 Mod. 9540 Tee connectors	25
 Mod. 9560 Y connectors	25

Adaptors & Valves

	Page
 Mod. D2502 and D2512 Bulkhead adaptors	26
 Mod. D2592 Bulkhead adaptors	26
 Mod. D2593 Bulkhead reducer	26
 Mod. D2543 Union	27
 Mod. D2532 Reducer	27
 Mod. D2602 Hose adaptors	27
 Mod. D2022 Elbow adaptors	28
 Mod. D2062 Branch Tee adaptors	28
 Mod. D2072 Run Tee adaptors	28
 Mod. D2003 Branch Tee adaptors	29
 Mod. D2003-S01 Branch Tee adaptors	29
 Mod. D2032 Cross adaptors	29
 Mod. D2077 Bilateral Tee adaptors	30
 Mod. D3043 Multiport adaptors	30

Adaptors & Valves

	Page
 Mod. D2612 Plug (inner hex)	30
 Mod. D2612 Plug (outer hex)	30
 Mod. VPC2 Test point valve	31
 Mod. VPC2 Bulkhead with test point & tube connection	31
 Mod. VDC2 Drain valve	31
 Mod. V604 Tyre inflator valve	32
 Mod. D1593 Bulkhead Nut	32
 Mod. D1593 Thread Nut	32

Accessories

	Page
 Mod. TRN Tubes	33
 Mod. DRK Tube disconnecting	33
 Mod. PNZ and PNPZ Tube cutter tool	33

Assortment boxes / Repair Kits

	Page
 TRUCK-DCASE/6000 Repair kit with Series 6000 fittings	34
 TRUCK-DCASE/9000 Repair kit with Series 9000 fittings	34
 TRUCK-DCASE/9000+6000 Repair kit with Series 9000 and Series 6000 fittings	34

Series 9000 Air Brake Fittings

SERIES 9000



Series 9000 fittings have been designed to connect tubing according to DIN 74324 or ISO 7628 in the pneumatic brake systems of commercial vehicles. They offer excellent reliability and ease of assembly. The range includes a very compact release tool for disconnecting tubes from the fittings.

The tube interface is shielded by a rubber cap for protecting the internal parts against dirt and water ingress. The integrity level of the interface concept, even during disassembling, is outstanding.

The Series 9000 offers a smart portfolio of different types of connectors. Depending on the demands of our customers, we are also ready to provide customized solutions.

Series 9000 fittings are TÜV certified and produced according to IATF 16949:2016 standards.

Main technical features

Thread type	Metric acc. ISO965 / Conical NPTF acc. ANSI B1.20.3
Media	Compressed air (other fluids, please contact our technicians)
Operating pressure	Up to 16 bar (review also tube specifications)
Operating temperature	-50°C up to 100°C (peak) (review also tube specifications)
Tubes	Designed for use with Polyamide or Hytrel® tubing, compliant with standards DIN 73378, DIN 74324 or ISO 7628



Certifications

Camozzi's primary goals include quality and safety, the protection of the environment and compatibility of our activities with the territories in which they are performed.




Scan the QR CODE to learn about the certifications obtained by Camozzi Automation S.p.A.

Assembly and removal of the tube



To guarantee a correct, safe and tight connection, it is necessary to cut the tube correctly. The cutting angle should not exceed 5° (Picture A), and we recommend using a suitable tube cutting tool. (Refer to PNZ in this catalogue). The outer surface of the tube should be smooth and free from any kind of damage or dirt (Picture B). When inserting the tube, make sure to push it into the fitting, down to the tube stop (Picture C). The correct insertion length is specified for every tube size/fitting and can be found in the table to the right (Assembly length L). We recommend marking the insertion length on the tube with a pen or tape before assembling, to visually ensure proper insertion.

Tube	Outer diameter (mm)	Inner diameter (mm)	Assembly length L (mm)
4x1	4	2	18,5
6x1	6	4	17,5
8x1	8	6	19,5
10x1	10	8	21
10x1,25	10	7,5	21
10x1,5	10	7	21
12x1,5	12	9	21,5
15x1,5	15	12	25
16x2	16	12	27,5
18x2	18	14	27,5



To remove the tube from the fitting, use the Series 9000 DRK release tool. Hook it onto the tube and press the protection cap down to release the tube so that you can pull it out of the fitting.

Attention: Do not try to remove from the fitting when the system is still pressurised. Make sure you have released all the air pressure before you remove the tube.

Tube assembly and disassembly must be carried out by a technician who is trained and has detailed knowledge of the air brake system and the Series 9000 fittings.


Please ensure mounting torques for straight connectors, straight studs and the fixation nuts of shaped connectors meet the values shown in the table on the right.

Thread	Torque force (Nm)
M10x1	11 - 15
M12x1,5	15 - 22
M14x1,5	19 - 23
M16x1,5	24 - 33
M18x1,5	27 - 33
M22x1,5	36 - 44


Make sure that the torque forces of the bulkhead nuts comply with the values.

Thread	Torque force ±10% (Nm)
M16x1,5	35
M18x1,5	35
M20x1,5	50
M22x1,5	50
M24x1,5	50
M28x1,5	70


Straight connectors



Shaped swivel connectors



Shaped non-swivel connectors



COMPONENT	MATERIAL
1 = Body	Brass
2 = Support Tube	Composite
3 = Tube O-Ring	NBR
4 = Collet	Brass
5 = Dirt Seal	NBR
6 = Thread O-Ring	NBR
7 = Locking Nut	Brass
8 = Swivel Body	Brass
9 = Swivel O-Ring	NBR
10 = Seeger Ring	Stainless Steel
11 = Protection Cap	Biodegradable Composite

Assembly of shaped Non-Swivel Connectors

To ensure a tight and secure connection between the fitting and the threaded port of the component in the pneumatic system, please install following this procedure:

1. Screw the nut upwards until you reach the mechanical stop (do not tighten the nut against the stop with a tool, simply position the nut by hand, as shown in the picture).



2. Screw the fitting into the threaded port until the O-ring seal touches the surface of the port. This can be done by hand or using a tool. We recommend you do this by hand to maintain feel and identify once the correct position is reached. (Picture A)



3. Bring the fitting into the final, desired position rotating it by a maximum of 180° clockwise or anti-clockwise.



4. Fix the position you have defined for your fitting with one hand and tighten the connection by screwing the nut downwards until you have reached the recommended torque (see table on the previous page).



5. The assembly is now complete.



Assembly of Swivel Connectors

For Swivel Connectors, please install manually according to the following instructions. **Attention:** Swivel connectors must not be used in applications with relative movement (e.g. connections between truck & trailer or between axle and chassis).

1. Mount the stud onto the port (please refer to the maximum torque forces on the previous pages). We recommend removing the cap just before you mount the female part to the stud in order to prevent dirt on or damage to the O-rings.



2. Position the female part on the stud. If you want to use an anti-rotation lock, attach this to the female part before you connect to the stud.



3. Now press down the upper part completely. The assembly is now complete.

Note: This connection cannot be disassembled again.



4. The swivel connector is now completed and ready for the tube to be inserted. The connector can be rotated to the necessary position (360° swivelling). If you have added a rotation lock and the connector is still swivelling, this is because you have not yet engaged the lock.



5. To engage the rotation lock, bring the upper part to a position that lets you press it down to interlock with the hexagon of the stud. Then press the locking ring down. The connector is now fixed in position.

Attention: The lock is a positioning support for line routing. It is not meant to withstand excessive bending forces



Assembly of barb connectors

For the assembly of our inline barb connectors, we recommend using a suitable tool set.

1. Choose the appropriate tool insert for the fitting and plug it into the tool.
2. Choose the right clamping fixture for your tube size. Position and clamp the tube.
3. Slide the fitting, with the S9000 tube interface end on to the insert. The barb end directs towards the clamped tube (Picture 1).



4. Slowly close the tool until the barb end of the fitting touches the tube.
5. Make sure barb and tube bore are well centred before pressing the barb end into the tube (Picture 2).




6. Press the fitting into the tube until the tube end reaches the tube stop of the fitting (Picture 3).

Note: For detailed information, please refer to the operating manual for the tool set you are using, which will provide manufacturer-approved instructions and guidance. Make sure you are using a tube compatible with barb fitting technology, and do not use any other processes (e.g. lubricants or temperature treatment) to reduce the pressing force needed during the fitting assembly.



Application examples



Example 1:
Mod. 9592
Bulkhead connector for mounting
of a gladhand on a bracket



Example 2:
Mod. 9555
Plug-in elbow connector
on backside of a test point panel




Example 3:
Mod. 9919
Bulkhead swivel connector
with t-adaptor, testpoint
and straight connector



Example 4:
Mod. D2593
Bulkhead reducer with straight connector
for external drain valve position

Straight connectors


Raccordi dritti con filetto maschio Mod. 9512



CHARACTERISTICS									
Mod.	A	D	F	G	H	L	SW	Weight (g)	Pack. (pcs)
9512 6-M10X1	6x1	M10X1	13,8	15	7	27,5	14	17,5	10
9512 6-M12X1,5R	6x1	M12X1,5	13,8	15	10	27,5	14	17,5	10
9512 6-M14X1,5R	6x1	M14X1,5	13,8	15	10	26,5	14	19,5	10
9512 6-M16X1,5R	6x1	M16X1,5	13,8	17	10	19,5	14	17,5	10
9512 6-M22X1,5R	6x1	M22X1,5	14,5	23	10	21	17	41,5	10
9512 8-M10X1	8x1	M10X1	16,5	18,5	7	30	17	26,5	10
9512 8-M12X1,5R	8x1	M12X1,5	16,5	18,5	10	32	17	28,5	10
9512 8-M14X1,5R	8x1	M14X1,5	16,5	18,5	10	29	17	26	10
9512 8-M16X1,5R	8x1	M16X1,5	16,5	18,5	10	28,5	17	29,5	10
9512 8-M22X1,5R	8x1	M22X1,5	16,5	23	10	21	19	39,5	10
9512 10/7-M12X1,5R	10x1,5	M12X1,5	17,8	19,5	10	33,5	18	26,5	10
9512 10/7-M16X1,5R	10x1,5	M16X1,5	17,8	19,5	10	29,5	18	29	10
9512 10/7-M22X1,5R	10x1,5	M22X1,5	18,5	23	10	22,5	19	37	10
9512 10/7,5-M12X1,5R	10x1,25	M12X1,5	17,8	19,5	10	33,5	18	26,5	10
9512 10/7,5-M16X1,5R	10x1,25	M16X1,5	17,8	19,5	10	29,5	18	29	10
9512 10/7,5-M22X1,5R	10x1,25	M22X1,5	18,5	23	10	22,5	19	37	10
9512 10-M12X1,5R	10x1	M12X1,5	17,8	19,5	10	33,5	18	26,5	10
9512 10-M16X1,5R	10x1	M16X1,5	17,8	19,5	10	29,5	18	29	10
9512 10-M22X1,5R	10x1	M22X1,5	18,5	23	10	22,5	19	37	10
9512 12-M12X1,5R	12x1,5	M12X1,5	19,8	21,5	10	35,5	20	34	10
9512 12-M14X1,5R	12x1,5	M14X1,5	19,8	21,5	10	35	20	35,5	10
9512 12-M16X1,5R	12x1,5	M16X1,5	19,8	21,5	10	34	20	37	10
9512 12-M22X1,5R	12x1,5	M22X1,5	20,5	24	10	23	22	37	10
9512 15-M16X1,5R	15x1,5	M16X1,5	23,8	26,5	10	39	24	53,5	10
9512 15-M22X1,5R	15x1,5	M22X1,5	23,8	26,5	10	32	24	50,5	10
9512 16/12-M16X1,5R	16x2	M16X1,5	25	30	10	42,5	27	75	10
9512 16/12-M22X1,5R	16x2	M22X1,5	25	30	10	35	27	68,5	10
9512 18-M22X1,5R	18x2	M22X1,5	26,8	30	10	40	27	68	10


Straight fittings Mod. D6512

Supplied without any insert



CHARACTERISTICS									
Mod.	A	D	F	G	H	L	SW	Weight (g)	Pack. (pcs)
D6512 4-M10X1	4x1	M10X1	11,7	13,2	7	24,5	12	9	10


Straight fittings Mod. 9510



CHARACTERISTICS

Mod.	A	D	F	G	H	L	SW	Weight (g)	Pack. (pcs)
9510 6-02	6x1	1/8 NPTF	13,8	15	8	24,5	14	16	10
9510 05-02	8x1	1/8 NPTF	16,5	18,5	8	30	17	27	10


Straight fittings with female thread Mod. 9463



CHARACTERISTICS

Mod.	A	D	F	G	h	L	SW	Weight (g)	Pack. (pcs)
9463 6-M12X1,5	6x1	M12X1,5	13,8	17	11	34	15	34	10
9463 6-M16X1,5	6x1	M16X1,5	15,3	21	10,5	34	19	51	10
9463 8-M10X1	8x1	M10X1	16,5	18,5	9	33	17	46	10
9463 8-M12X1,5	8x1	M12X1,5	16,5	18,5	10,5	35,5	17	51	10
9463 8-M16X1,5	8x1	M16X1,5	16,5	21	10,5	35,5	17	51	10

Bulkhead connectors Mod. 9590




CHARACTERISTICS

Mod.	A	D	F	G	H	h	L	N	T	Y	Z	SW	SW1	Weight (g)	Pack. (pcs)
9590 8-M18X1,5	8x1	M18X1,5	-	25,5	50	10	55,5	10,8	15,7	53	4	22	22	99,5	10
9590 12-M18X1,5	12x1,5	M18X1,5	20,5	25,5	34	4	53	11	16	60	5	22	22	83	10

Bulkhead connectors with 24° cone Mod. 9590




Supplied without nut;
Combine with D1593



CHARACTERISTICS											
Mod.	A	B	D	F	G	H	h	L	SW	Weight (g)	Pack. (pcs)
9590 6-M14x1,5	6x1	8	M14X1,5	14,5	20	21	2,5	36	17	36	10
9590 8-M14x1,5	8x1	8	M14X1,5	16,5	20	21	2,5	43,5	17	46	10
9590 8-M16x1,5	8x1	10	M16X1,5	16,5	22	21	2,5	37	19	44	10
9590 12-M18x1,5-S06	12x1,5	12	M18X1,5	20,5	25,5	21	2,5	40	22	56	10


Bulkhead connectors Mod. 9592



CHARACTERISTICS													
Mod.	A	D	D1	C	G	G1	L	H	h	SW	SW1	Weight (g)	Pack. (pcs)
9592 8-M20X1,5-M16X1,5R	8x1	M16X1,5	M20X1,5	5	25,5	28	41	10	2,5	22	24	83	10
9592 10/7-M22X1,5-M22X1,5R	10x1,5	M22X1,5	M22X1,5	8	31	31	44	10	2,5	27	28	120	10
9592 12-M24X1,5-M16X1,5R	12x1,5	M16X1,5	M24X1,5	6	32,5	31	41	10	2,5	28	27	95	10


Shaped non-swivel connectors

Elbow fittings Mod. 9502




CHARACTERISTICS												
Mod.	A	D	C	E	F	G	H	M	SW	SW1	Weight (g)	Pack. (pcs)
9502 6-M10X1R	6x1	M10X1	6	22	14,5	16	7	22,5	9	14	25	10
9502 6-M12X1,5R	6x1	M12X1,5	8,2	25	14,5	19	9	22,5	9	17	34	10
9502 6-M16X1,5R	6x1	M16X1,5	8,2	26	14,5	24	9	23	11	22	46,5	10
9502 6-M22X1,5R	6x1	M22X1,5	8,2	29	14,5	30	9	23	11	27	60	10
9502 8-M10X1R	8x1	M10X1	6	23	16,5	16	7	25	11	14	30,5	10
9502 8-M12X1,5R	8x1	M12X1,5	8,2	26	16,5	19	9	25	11	17	39,5	10
9502 8-M14X1,5R	8x1	M14X1,5	8,2	26	16,5	21	9	25	11	19	40	10
9502 8-M16X1,5R	8x1	M16X1,5	8,2	26	16,5	24	9	25	11	22	45,5	10
9502 8-M22X1,5R	8x1	M22X1,5	8,2	29	16,5	30	9	25	11	27	60	10
9502 8-1/8R	8x1	G1/8	6	23	16,5	16	7	25	11	14	30,5	10
9502 10/7-M12X1,5R	10x1,5	M12X1,5	8,2	27	18,5	19	9	27	13	17	48	10
9502 10/7-M16X1,5R	10x1,5	M16X1,5	8,2	27,5	18,5	24	9	27	13	22	55,5	10
9502 10/7-M22X1,5R	10x1,5	M22X1,5	8,2	29	18,5	30	9	27	13	27	69,3	10
9502 10/7,5-M12X1,5R	10x1,25	M12X1,5	8,2	27	18,5	19	9	27	13	17	48	10
9502 10/7,5-M16X1,5R	10x1,25	M16X1,5	8,2	27,5	18,5	24	9	27	13	22	55,5	10
9502 10/7,5-M22X1,5R	10x1,25	M22X1,5	8,2	29	18,5	30	9	27	13	27	69,3	10
9502 10-M12X1,5R	10x1	M12X1,5	8,2	27	18,5	19	9	27	13	17	47	10
9502 10-M16X1,5R	10x1	M16X1,5	8,2	27,5	18,5	24	9	27	13	22	54	10
9502 10-M22X1,5R	10x1	M22X1,5	8,2	29	18,5	30	9	27	13	27	68	10
9502 12-M12X1,5R	12x1,5	M12X1,5	8,2	28,5	20,5	19	9	28,5	15	17	55,5	10
9502 12-M16X1,5R	12x1,5	M16X1,5	8,2	28,5	20,5	24	9	28,5	15	22	59,5	10
9502 12-M22X1,5R	12x1,5	M22X1,5	8,2	30	20,5	30	9	28,5	15	27	72,5	10
9502 15-M16X1,5R	15x1,5	M16X1,5	8,2	31,5	24,5	24	9	34	18	22	91	10
9502 15-M22X1,5R	15x1,5	M22X1,5	8,2	34	24,5	30	9	34	18	27	103	10
9502 16/12-M16X1,5R	16x2	M16X1,5	8,2	33	25	24	9	35,5	21	22	114	10
9502 16/12-M22X1,5R	16x2	M22X1,5	8,2	33	25	30	9	35,5	21	27	117,5	10
9502 18-M22X1,5R	18x2	M22X1,5	8,2	33	27,5	30	9	35,5	21	27	115	10

Elbow fittings Mod. 9500




CHARACTERISTICS									
Mod.	A	D	E	F	H (min)	M	SW	Weight (g)	Pack. (pcs)
9500 6-02	6x1	1/8 NPTF	17,5	14,5	8,5	21,5	9	18	10
9500 05-02	8x1	1/8 NPTF	17	16,5	7	25	11	23	10
9500 12-06	12x1,5	3/8 NPTF	24,5	20,5	10,5	28,5	15	46	10

Branch Tee fittings Mod. 9412



CHARACTERISTICS													
Mod.	A	D	C	E	F	G	H	L	M	SW	SW1	Weight (g)	Pack. (pcs)
9412 6-M10X1R	6x1	M10X1	6	23	14,5	16	7	45	22,5	9	14	38	10
9412 6-M12X1,5R	6x1	M12X1,5	8,2	27,5	14,5	19	9	46	23	11	17	57	10
9412 6-M16X1,5R	6x1	M16X1,5	8,2	28	14,5	24	9	46	23	11	22	64,5	10
9412 6-M22X1,5R	6x1	M22X1,5	8,2	32	14,5	30	9	49	24,5	15	27	87	10
9412 8-M12X1,5R	8x1	M12X1,5	8,2	27,5	16,5	19	9	50	25	11	17	59,5	10
9412 8-M16X1,5R	8x1	M16X1,5	8,2	28	17	24	9	50	25	11	22	67	10
9412 8-M22X1,5R	8x1	M22X1,5	8,2	32	16,5	30	9	53	26,5	15	27	95,5	10
9412 10/7-M12X1,5R	10x1,5	M12X1,5	8,2	29	18,5	19	9	55	27,5	15	17	86	10
9412 10/7-M16X1,5R	10x1,5	M16X1,5	8,2	29	18,5	24	9	55	27,5	15	22	91	10
9412 10/7-M22X1,5R	10x1,5	M22X1,5	8,2	32	18,5	30	9	55	27,5	15	27	103	10
9412 10-M12X1,5R	10x1	M12X1,5	8,2	29	18,5	19	9	55	27,5	15	17	83	10
9412 10-M16X1,5R	10x1	M16X1,5	8,2	29	18,5	24	9	55	27,5	15	22	88	10
9412 10-M22X1,5R	10x1	M22X1,5	8,2	32	18,5	30	9	55	27,5	15	27	100,5	10
9412 12-M12X1,5R	12x1,5	M12X1,5	8,2	29	20,5	19	9	57	28,5	15	17	77	10
9412 12-M16X1,5R	12x1,5	M16X1,5	8,2	29	20,5	24	9	57	28,5	15	22	83	10
9412 12-M22X1,5R	12x1,5	M22X1,5	8,2	32	20,5	30	9	57	28,5	15	27	95,5	10
9412 15-M16X1,5R	15x1,5	M16X1,5	8,2	33,5	24,5	24	9	68	34	18	22	129,5	10
9412 15-M22X1,5R	15x1,5	M22X1,5	8,2	34	24,5	30	9	68	34	18	27	140,5	10

Branch Tee fittings Mod. 9410




CHARACTERISTICS										
Mod.	A	D	E	F	H	L	M	SW1	Weight (g)	Pack. (pcs)
9410 6-02	6x1	1/8 NPTF	17,5	14,5	7	45	22,5	9	30,5	10
9410 05-02	8x1	1/8 NPTF	18	17	7	50	25	11	42	10

General terms and conditions for sale are available on www.camozzi.com.

This document contains a brief description of the products offered by Camozzi Automation at the time of publication.


For more complete and up-to-date information about the Camozzi Automation product range, please refer to our online catalogue at <http://catalogue.camozzi.com/>.

Run Tee fittings Mod. 9422




CHARACTERISTICS													
Mod.	A	D	C	E	F	G	H	L	M	SW	SW1	Weight (g)	Pack. (pcs)
9422 6-M10X1R	6x1	M10X1	6	23	14,5	16	7	45,5	22,5	9	14	37,5	10
9422 6-M12X1,5R	6x1	M12X1,5	8,2	27,5	14,5	19	9	50,5	23	11	17	57	10
9422 6-M16X1,5R	6x1	M16X1,5	8,2	28	14,5	24	9	51	23	11	22	63,5	10
9422 8-M12X1,5R	8x1	M12X1,5	8,2	27,5	17	19	9	52,5	25	11	17	59,5	10
9422 8-M16X1,5R	8x1	M16X1,5	8,2	28	17	24	9	53	25	11	22	67	10
9422 8-M22X1,5R	8x1	M22X1,5	8,2	32	16,5	30	9	58,5	26,5	15	27	95	10
9422 10-M16X1,5R	10x1	M16X1,5	8,2	29	18,5	24	9	56,5	27,5	15	22	88	10
9422 10-M22X1,5R	10x1	M22X1,5	8,2	32	18,5	30	9	59,5	27,5	15	27	100	10
9422 12-M16X1,5R	12x1,5	M16X1,5	8,2	29	20,5	24	9	57,5	28,5	15	22	83	10
9422 12-M22X1,5R	12x1,5	M22X1,5	8,2	32	20,5	30	9	60,5	28,5	15	27	99,5	10

Run Tee fittings Mod. 9420




CHARACTERISTICS										
Mod.	A	D	E	F	H	L	M	SW	Weight (g)	Pack. (pcs)
9420 6-02	6x1	1/8 NPTF	17,5	14,5	7	40	22,5	9	30	10
9420 05-02	8x1	1/8 NPTF	18	17	7	43	25	11	42	10

135° Elbow fittings Mod. 9102




CHARACTERISTICS												
Mod.	A	D	C	E	F	G	H	M	SW	SW1	Weight (g)	Pack. (pcs)
9102 12-M16X1,5R	12x1,5	M16x1,5	8,2	54,9	21,3	24	9	29,5	15	22	64	10

Plug-In elbow connectors Mod. 9555




CHARACTERISTICS									
Mod.	A	G	T	E	F	M	SW	Weight (g)	Pack. (pcs)
9555 6-6	6x1	6	16,9	25	14,5	22,5	9	17	10
9555 8-8	8x1	8	18,7	27,2	16,5	25	11	23	10
9555 12-12	12x1,5	12	20,7	32,2	21	29,5	15	45	10

Y fittings Mod. 9450



CHARACTERISTICS											
Mod.	A	D	C	F	G	H	L	SW	SW1	Weight (g)	Pack. (pcs)
9450 8-M16X1,5R	8x1	M16X1,5	8,2	31,5	24	9	49,3	14	22	71,5	10
9450 12-M16X1,5R	12x1,5	M16X1,5	8,2	40	24	9	59,2	20	22	130,5	10
9450 12-M22X1,5R	12x1,5	M22X1,5	8,2	40	30	9	59,2	20	27	133	10


Elbow fittings Mod. 9402



CHARACTERISTICS												
Mod.	A	D	C	E	F	G	H	L	M	SW	SW1	Weight (g)
9402 8-M16X1,5R	8x1	M16X1,5	8,2	30	21	24	9	49	27,5	15	22	130
9402 8-M22X1,5R	8x1	M22X1,5	8,2	30	21	30	9	49	27,2	15	27	138
9402 12-M16X1,5R	12x1,5	M16X1,5	8,2	30	21	24	9	49	29,5	15	22	114,5
9402 12-M22X1,5R	12x1,5	M22X1,5	8,2	30	21	30	9	49	29,5	15	27	114,5

Shaped swivel connectors

Swivel studs Mod. D2912




CHARACTERISTICS									
Mod.	B	D	E	G	H	L	SW	Weight (g)	Pack. (pcs)
D2912 C1-M10X1B	C1	M10X1	14,3	18,5	8	29,3	17	22	10
D2912 C1-M12X1,5B	C1	M12X1,5	14,5	20	9	29,5	18	22,5	10
D2912 C1-M14X1,5B	C1	M14X1,5	14,5	22	9	29,5	20	25	10
D2912 C1-M16X1,5B/1*	C1	M16X1,5	15,8	25	9	30,8	22	34	10
D2912 C1-M18x1,5B/1*	C1	M18x1,5	15,8	27	9	30,8	24	40	10
D2912 C1-M22X1,5B/1*	C1	M22X1,5	16,3	32	9	31,3	28	48	10
D2912 C1-1/4	C1	G1/4	14,5	18,5	7	29,5	17	26,5	10

* usable with Mod. 9707 anti-rotation ring; compare SW.

Bulkhead swivel studs Mod. D2993



Supplied without nut;
Combine with D1593




CHARACTERISTICS											
Mod.	B	D	D1	G	H	h	h1	L	SW	Weight (g)	Pack. (pcs)
D2993 C1-M16X1,5-M22X1,5/1*	C1	M22X1,5	M16X1,5	32	21	2,5	10,5	42	28	75	10

* usable with Mod. 9707 anti-rotation ring; compare SW.

Bulkhead swivel connectors Mod. 9919




Supplied without nut;
Combine with D1593



CHARACTERISTICS										
Mod.	B	A	D	G	H	h	L	SW	Weight (g)	Pack. (pcs)
9919 C1-8-M20X1,5/1*	C1	8x1	M20X1,5	25	21	2,5	42	22	71	10
9919 C1-12-M24X1,5/1*	C1	12x1,5	M24X1,5	32	21	2,5	42	28	90	10

* usable with Mod. 9707 anti-rotation ring; compare SW.


Anti-rotation ring Mod. 9707



CHARACTERISTICS					
Mod.	H	D	SW	Weight (g)	Pack. (pcs)
9707 22-C1	11	31,7	22	4	10
9707 24-C1	11	31,7	24	4	10
9707 28-C1	11	35,7	28	5	10


Usable with Mod. D2912, D2993, 9919; compare SW.

Swivel Elbow fittings Mod. 9520



CHARACTERISTICS								
Mod.	A	B	E	F	G	M	Weight (g)	Pack. (pcs)
9520 6-C1	6x1	C1	19,5	14,5	22	26	32	10
9520 8-C1	8x1	C1	19,5	16,5	22	28	32	10
9520 10/7-C1	10x1,5	C1	19,5	18,5	22	30	42	10
9520 10/7,5-C1	10x1,25	C1	19,5	18,5	22	30	42	10
9520 10-C1	10x1	C1	19,5	18,5	22	30	42	10
9520 12-C1	12x1,5	C1	19,5	20,5	22	31	42	10
9520 15-C1	15x1,5	C1	21,5	24	22	34	62	10
9520 16/12-C1	16x2	C1	21,5	24	22	34	62	10

Swivel branch Tee fittings Mod. 9430




CHARACTERISTICS									
Mod.	A	B	E	F	G	L	M	Weight (g)	Pack. (pcs)
9430 6-C1	6x1	C1	19,5	14,5	22	4	2	46	10
9430 8-C1	8x1	C1	19,5	16,5	22	56	28	46	10
9430 10/7-C1	10x1,5	C1	19,5	18,5	22	60	30	64	10
9430 10-C1	10x1	C1	19,5	18,5	22	60	30	64	10
9430 12-C1	12x1,5	C1	19,5	20,5	22	62	31	64	10
9430 15-C1	15x1,5	C1	21,5	24	22	68	34	101	10

General terms and conditions for sale are available on www.camozzi.com.

This document contains a brief description of the products offered by Camozzi Automation at the time of publication.


For more complete and up-to-date information about the Camozzi Automation product range, please refer to our online catalogue at <http://catalogue.camozzi.com/>.

Swivel run Tee fittings Mod. 9440




CHARACTERISTICS									
Mod.	A	B	E	F	G	L	M	Weight (g)	Pack. (pcs)
9440 6-C1	6x1	C1	19,5	14,5	22	45,5	26	47	10
9440 8-C1	8x1	C1	19,5	16,5	22	47,5	28	47	10
9440 10/7-C1	10x1,5	C1	19,5	18,5	22	49,5	30	67	10
9440 10-C1	10x1	C1	19,5	18,5	22	49,5	30	67	10
9440 12-C1	12x1,5	C1	19,5	20,5	22	50,5	31	67	10
9440 15-C1	15x1,5	C1	21,5	24	22	55,5	34	100	10

Swivel Elbow adaptors Mod. D2220




CHARACTERISTICS										
Mod.	d	B	E	F	G	h (min)	M	SW	Weight (g)	Pack. (pcs)
D2220 M12X1,5-C1	M12X1,5	C1	22,5	21	22	10,5	18,5	20	50	10
D2220 M16X1,5-C1	M16X1,5	C1	22,5	21	22	10,5	18,5	20	39	10

Swivel branch Tee adaptors Mod. D2260



CHARACTERISTICS										
Mod.	d	B	E	F	G	h (min)	L	M	SW	Weight (g)
D2260 M12X1,5-C1	M12X1,5	C1	22,5	21	22	10,5	37	18,5	20	73
D2260 M16X1,5-C1	M16X1,5	C1	22,5	21	22	10,5	37	18,5	20	52


Swivel run Tee adaptors Mod. D2270



CHARACTERISTICS

Mod.	d	B	E	F	G	h (min)	L	M	SW	Weight (g)	Pack. (pcs)
D2270 M12X1,5-C1	M12X1,5	C1	22,5	21	22	10,5	41	18,5	20	73	10
D2270 M16X1,5-C1	M16X1,5	C1	22,5	21	22	10,5	41	18,5	20	52	10

Swivel 135° adaptors Mod. D2210




CHARACTERISTICS

Mod.	d	B	E	F	G	h (min)	L	M	SW	Weight (g)	Pack. (pcs)
D2210 M16X1,5-C1	M16X1,5	C1	28	21	19,5	10,5	53	28	20	50	10

Not compatible with anti rotation ring Mod. 9707


Inline connectors

■ Straight connectors Mod. 9580




CHARACTERISTICS							
Mod.	A	A1	F	F1	L	Weight (g)	Pack. (pcs)
9580 6	6x1	6x1	14	14	37,5	21	10
9580 8	8x1	8x1	16	16	41	27	10
9580 10/7	10x1,5	10x1,5	18	18	44	34	10
9580 10/7,5	10x1,25	10x1,25	18	18	44	34	10
9580 10	10x1	10x1	18	18	44	33	10
9580 12	12x1,5	12x1,5	20	20	45,5	43	10
9580 12-8	12x1,5	8x1	20	16	44	37	10
9580 15	15x1,5	15x1,5	24	24	52	87	10
9580 16/12	16x2	16x2	25	25	58	100	10
9580 18	18x2	18x2	27	27	57	109	10

■ Bulkhead connectors Mod. 9592



CHARACTERISTICS															
Mod.	A	B	C	C1	D	F	G	G1	H	h	L	SW	SW1	Weight (g)	Pack. (pcs)
9592 6-6-M18X1,5	6X1	6X1	6	7	M18X1,5	14,5	23	25,5	9	2,5	37,5	20	22	64	10
9592 8-8-M18X1,5	8X1	8X1	6	7	M18X1,5	16,5	25,5	25,5	9	2,5	41	22	22	64	10
9592 8-8-M20X1,5	8X1	8X1	6	5	M20X1,5	18,5	25,5	27,5	11	2,5	41	22	24	82	10
9592 12-8-M18X1,5	12X1,5	8X1	6	7	M18X1,5	20,5	25,5	25,5	9	2,5	44	22	22	79	10
9592 12-12-M24X1,5	12X1,5	12X1,5	7,5	6	M24X1,5	20,5	31	32,5	10	2,5	46	27	28	113	10
9592 15-15-M28X1,5	15X1,5	15X1,5	7	6	M28X1,5	25	34,5	37	13	2,5	52	30	32	158	10

Barb connectors Mod. 9851




CHARACTERISTICS

Mod.	A	N	F	H	L	Weight (g)	Pack. (pcs)
9851 8-6	8x1	6	16	16	38	17,5	10
9851 12-9	12x1,5	9	20	20	46,5	30	10

Barb profile according to DIN 73377 | 9851 8-6 allows to connect 8x1 to 9x1,5 tubing


Tee connectors Mod. 9540



CHARACTERISTICS

Mod.	A	A1	E	F	F1	L	M	SW	Weight (g)	Pack. (pcs)
9540 6	6x1	6x1	22,5	14,5	14,5	45	22,5	9	35,5	10
9540 8	8x1	8x1	25	17	17	50	25	11	53	10
9540 10/7	10x1,5	10x1,5	27,5	18,5	18,5	55	27,5	15	84	10
9540 10	10x1	10x1	27,5	18,5	18,5	55	27,5	15	81	10
9540 12	12x1,5	12x1,5	28,5	20,5	20,5	57	28,5	15	73,5	10
9540 15	15x1,5	15x1,5	34	24,5	24,5	68	34	18	129	10
9540 16/12	16x2	16x2	37	25,5	25,5	74	37	19	138	10
9540 8-8-6	8x1	6x1	23	17	14,5	50	25	11	50	10
9540 12-12-8	12x1,5	8x1	26,5	20,5	16,5	57	28,5	15	72	10

Y connectors Mod. 9560



CHARACTERISTICS

Mod.	A	A1	F	F1	L	SW	Weight (g)	Pack. (pcs)
9560 8	8x1	8x1	31,5	16,5	48,3	14	61	10
9560 12	12x1,5	12x1,5	40	21	59,2	14	130	10


General terms and conditions for sale are available on www.camozzi.com.

This document contains a brief description of the products offered by Camozzi Automation at the time of publication.

For more complete and up-to-date information about the Camozzi Automation product range, please refer to our online catalogue at <http://catalogue.camozzi.com/>.

Adaptors & Valves


Bulkhead adaptors Mod. D2502 and D2512



CHARACTERISTICS																	
Mod.	D	D1	d	d1	C	C1	G	G1	H	H1	h	h1	L	SW	SW1	Weight (g)	Pack. (pcs)
D2502 M22X1,5R-M22X1,5R-M16X1,5-L=39	M22X1,5	M22X1,5	M16X1,5	M16X1,5	8,2	8,5	30	28	9	10	10,5	10,5	40,5	27	24	79,5	10
D2502 M22X1,5R-M22X1,5R	M22X1,5	M22X1,5	-	-	8,2	8,5	30	28	9	10	-	-	40,5	27	24	84	10
D2512 M22X1,5R-M16X1,5R	M22X1,5	M16X1,5	M16X1,5	M10X1	8,2	8,5	30	25,5	9	10	10,5	-	49,5	27	22	88	10

Bulkhead adaptors Mod. D2592

Supplied without nut;
Combine with D1593




CHARACTERISTICS												
Mod.	D	D1	d1	G	H	H1	h	h1	L	SW	Weight (g)	Pack. (pcs)
D2592 M10X1-M16x1,5B-M16X1,5	M16x1,5	M16x1,5	M10x1	24	9	20	2	34,5*	34,5	22	43	10
D2592 M16X1,5-M16x1,5B-M22X1,5	M16x1,5	M22x1,5	M16x1,5	31	9	24	2	20	40	28	72	10
D2592 M16X1,5-M22x1,5B-M22X1,5	M22x1,5	M22x1,5	M16x1,5	31	9	24	2	39*	39	28	75	10

* Through-out thread.


Bulkhead reducers Mod. D2593

Supplied without nut;
Combine with D1593




CHARACTERISTICS									
Mod.	D	D1	G	h	H	L	SW	Weight (g)	Pack. (pcs)
D2593 M12x1,5-M18x1,5	M18x1,5	M12x1,5	25	2,5	24,5	30	22	45	10
D2593 M16X1,5-M22x1,5	M22x1,5	M16x1,5	31	2,5	24,5	30	28	62	10
D2593 M22x1,5-M28x1,5	M28x1,5	M22x1,5	35	2,5	24,5	30	32	80	10

Union Mod. D2543




CHARACTERISTICS					
Mod.	D	L	SW	Weight (g)	Pack. (pcs)
D2543 M10X1/1	M10x1	22	18	39	10
D2543 M12X1,5/1	M12x1,5	22	18	35	10
D2543 M16X1,5/1	M16x1,5	22	22	45	10
D2543 M22X1,5/1	M22x1,5	26	28	75	10

Reducer Mod. D2532




CHARACTERISTICS								
Mod.	D	D1	G	H	L	SW	Weight (g)	Pack. (pcs)
D2532 M12X1,5-M16X1,5B	M16x1,5	M12x1,5	24	9	14,5	22	19,5	10
D2532 M12X1,5-M22X1,5B	M22x1,5	M12x1,5	31	9	15	28	45	10
D2532 M14X1,5-M16X1,5B	M16x1,5	M14x1,5	24	9	24	22	19,5	10
D2532 M16X1,5-M22X1,5B	M22x1,5	M16x1,5	31	9	15	28	34	10

Hose adaptors Mod. D2602




CHARACTERISTICS										
Mod.	A	D	G	H	L	L1	L2	SW	Weight (g)	Pack. (pcs)
D2602 10-M16X1,5B	11,3	M16x1,5	24	9	46,5	32	10,2	22	31,5	10
D2602 10-M22X1,5B	11,3	M22x1,5	31	9	47	32	10,2	28	47	10
D2602 11-M16X1,5B	12,4	M16x1,5	24	9	46,5	32	10,7	22	32,5	10
D2602 11-M22X1,5B	12,4	M22x1,5	31	9	47	32	10,7	28	48,5	10
D2602 12-M16X1,5B	13,4	M16x1,5	24	9	46,5	32	10,7	22	34	10
D2602 12-M22X1,5B	13,4	M22x1,5	31	9	47	32	10,7	28	50	10
D2602 13-M16X1,5B	14,5	M16x1,5	24	9	49,5	35	10,2	22	36	10
D2602 13-M22X1,5B	14,5	M22x1,5	31	9	50	35	10,2	28	51,5	10

Elbow adaptors Mod. D2022




CHARACTERISTICS															
Mod.	d	D	C	E	F	G	H	h	M	SW	SW1	Weight (g)	Pack. (pcs)		
D2022 M16X1,5-M16X1,5R	M16X1,5	M16X1,5	8,2	28,5	21	24	9	10,5	26,5	15	22	60,5	10		
D2022 M16X1,5-M22X1,5R	M16X1,5	M22X1,5	8,2	30	21	30	9	10,5	26,5	15	27	71	10		
D2022 M22X1,5-M22X1,5R	M22X1,5	M22X1,5	8,2	33	27	30	9	11	22	24	27	88	10		

Branch Tee adaptors Mod. D2062




CHARACTERISTICS															
Mod.	d	D	C	E	F	G	H	h	L	M	SW	SW1	Weight (g)	Pack. (pcs)	
D2062 M16X1,5-M12X1,5R/1	M16X1,5	M12X1,5	8,2	29,5	21	19	9	10,5	53	26,5	15	17	77	10	
D2062 M16X1,5-M16X1,5R	M16X1,5	M16X1,5	8,2	30	21	24	9	12,5	37	18,5	20	22	70	10	
D2062 M16X1,5-M22X1,5R	M16X1,5	M22X1,5	8,2	32	21	30	9	10,5	37	18,5	20	27	84,5	10	
D2062 M22X1,5-M22X1,5R/1	M22X1,5	M22X1,5	8,2	33	27	30	9	11	44	32	26	27	122	10	

Run Tee adaptors Mod. D2072




CHARACTERISTICS															
Mod.	d	D	C	E	F	G	H	h	L	M	SW	SW1	Weight (g)	Pack. (pcs)	
D2072 M16X1,5-M12X1,5R/1	M16X1,5	M12X1,5	8,2	30	21	19	9	10,5	48,5	18,5	20	17	70	10	
D2072 M16X1,5-M16X1,5R	M16X1,5	M16X1,5	8,2	30	21	24	9	10	48,5	18,5	20	22	70	10	
D2072 M16X1,5-M22X1,5R	M16X1,5	M22X1,5	8,2	32	21	30	9	10	50,5	18,5	20	27	82	10	
D2072 M22X1,5-M22X1,5R/1	M22X1,5	M22X1,5	8,2	33,5	27	30	9	11	55,5	22	26	27	116	10	

Branch Tee adaptors Mod. D2003




CHARACTERISTICS									
Mod.	d	E	F	h	M	L	SW	Weight (g)	Pack. (pcs)
D2003 M16X1,5	M16X1,5	18,5	21	10	18,5	37	20	53	10
D2003 M22X1,5/1	M22X1,5	22	27	11	22	44	26	85	10

Branch Tee adaptors Mod. D2003...S01




CHARACTERISTICS													
Mod.	d	E	F	h	M	L	N	O	P	R	SW	Weight (g)	Pack. (pcs)
D2003 M16X1,5-S01	M16X1,5	18,5	21	10,5	18,5	37	5	18	2	9	21	68	10

Cross adaptors Mod. D2032




CHARACTERISTICS														
Mod.	d	D	C	E	F	G	H	h	L	L1	M	SW	SW1	Weight (g)
D2032 M16X1,5-M16X1,5R	M16X1,5	M16X1,5	8,2	29,5	21	24	9	10,5	56	57,5	28	16	22	110,5
D2032 M16X1,5-M22X1,5R	M16X1,5	M22X1,5	8,2	30	21	30	9	10,5	56	58	28	16	27	137

Bilateral Tee adaptors Mod. D2077




CHARACTERISTICS												
Mod.	D	d	C	E	F	G	H	h	M	SW	Weight (g)	Pack. (pcs)
D2077 M16X1,5-M16X1,5R	M16X1,5	M16X1,5	8,2	35	21	24	9	10,5	22	22	94,5	10
D2077 M16X1,5-M22X1,5R	M22X1,5	M16X1,5	8,2	35,5	21	30	9	10,5	22	27	98	10

Multiport adaptor Mod. D3043




CHARACTERISTICS											
Mod.	d	d1	C	E	M	L	H	F	Z	Weight (g)	Pack. (pcs)
D3043 M16X1,5-2D-M16X1,5-S01	M16X1,5	9	32	26,5	28	65	53	21	40,5	147	10

Plug (inner hex.) Mod. D2612




CHARACTERISTICS							
Mod.	D	H	L	G	SW	Weight (g)	Pack. (pcs)
D2612 M12X1,5R	M12X1,5	10	12	13	6	6,5	10
D2612 M16X1,5R	M16X1,5	10	12,5	17	8	13	10
D2612 M22X1,5R	M22X1,5	10	13	23	12	26	10

Plug (outer hex.) Mod. D2612




CHARACTERISTICS							
Mod.	D	H	L	G	SW	Weight (g)	Pack. (pcs)
D2612 M10x1B	M10x1	8	13	18	16	12	10
D2612 M12X1,5B	M12X1,5	9	14,5	20	18	15	10
D2612 M16X1,5B	M16X1,5	9	14,5	24	22	25	10
D2612 M22X1,5B	M22X1,5	9	15	31	28	37	10

Test point valve Mod. VPC2




CHARACTERISTICS									
Mod.	D	D1	H	G	G1	L	SW	Weight (g)	Pack. (pcs)
VPC2 M16X1,5B-M16X1,5	M16X1,5	M16X1,5	9	9	10	29	22	43	10
VPC2 M22X1,5B-M16X1,5	M22X1,5	M16X1,5	9	9	10	29	28	60	10

Bulkhead with test point & tube connection Mod. VPC2



CHARACTERISTICS											
Mod.	A	D	D1	C	H	h	L	SW	SW1	Weight (g)	Pack. (pcs)
VPC2 M16X1,5-8-M18X1,5	8X1	M18X1,5	M16X1,5	5,5	21	2,5	40	20	22	61	10
VPC2 M16X1,5-8-M20X1,5	8X1	M20X1,5	M16X1,5	5	21	2,5	40	22	24	71	10

Drain valve Mod. VDC2



CHARACTERISTICS									
Mod.	D	h	E	G	H	L	SW	Weight (g)	Pack. (pcs)
VDC2 M22X1,5B	M22X1,5	3,2	18,5	31	9	32,1	28	29	10
VDC2 M22X1,5B/1	M22X1,5	3,2	18,5	31	9	32,1	28	29	10

/1: drain valve with ring

■ Tyre inflator valve Mod. V604




A = rod position for tyre inflation
B = rod position for tank filling through
air intake for tyre inflation

2 = air supply
3 = drain
11, 12 = air outlets

Flow 2 ÷ 11 bar
at 6 bar ΔP 1: 1620 l/min


Flow 2 ÷ 12 bar
at 6 bar with no interruption: 400 l/min

Safety pressure: 10 bar
Q = 100 l/min; 8 bar Q = 0 l/min



CHARACTERISTICS																	
Mod.	C	D	D1	d	E	F	G	H	h	L	M	N	SW	SW1	SW2	Weight (g)	Pack. (pcs)
V604 M22X1,5R	8,2	M22X1,5	M16X1,5	M22X1,5	26	27	30	12	11	94,4	29	42,5	24	27	27	253	2

■ Bulkhead nut Mod. D1593




CHARACTERISTICS						
Mod.	D	G	L	SW	Weight (g)	Pack. (pcs)
D1593 M16x1,5	M16x1,5	24	6	22	11	10
D1593 M18x1,5	M18x1,5	-	7	22	11	10
D1593 M20x1,5	M20x1,5	-	5	24	9	10
D1593 M22x1,5	M22x1,5	31	8	28	22	10
D1593 M24x1,5	M24x1,5	-	6	28	13	10
D1593 M28x1,5	M28x1,5	-	6	32	16	10

■ Thread nut Mod. D1593



The nut is supplied
with NBR O-Ring



CHARACTERISTICS						
Mod.	D	G	L	SW	Weight (g)	Pack. (pcs)
D1593 1/8R/1	G1/8	-	6	14	5	10
D1593 M10x1R/1	M10x1	16	6	14	5	10
D1593 M12x1,5R/1	M12x1,5	19	8,2	17	10	10
D1593 M14x1,5R/1	M14x1,5	20	8,2	19	11	10
D1593 M16x1,5R/1	M16x1,5	24	8,2	22	14	10
D1593 M22x1,5R/1	M22x1,5	30	8,2	27	18	10

Accessories

■ Tubes Mod. TRN




Black tubes in polyamide (PA12)

According to standards:

- DIN 74324 (except for Mod. TRN 10/7-N)
- REACH REGULATION (EC N°1907/2006)
- EUROPEAN DIRECTIVE RoHS n° 2002/95/EC

CHARACTERISTICS						
Mod.	D/d	MAX pressure at 23°C (bar)	Weight (g/m)	Min. curve radius min. (mm)	Operating temperature (°C)	Size (m)
TRN 4/2 NX	4/2	49	9,6	16	-55°C ÷ +100°C	50
TRN 6/4 NX	6x1	29	16	30	-55°C ÷ +100°C	100
TRN 8/6 NX	8x1	21	22,4	40	-55°C ÷ +100°C	100
TRN 10/7-N	10x1,5	23	41,2	58	-40°C ÷ +80°C	50
TRN 10/7,5 N	10x1,25	20	39,4	60	-40°C ÷ +80°C	50
TRN 10/8 NX	10x1	16	28,8	60	-55°C ÷ +100°C	50
TRN 12/9 NX	12x1,5	21	50,4	60	-55°C ÷ +100°C	50
TRN 15/12 NX	15x1,5	16	64,9	90	-55°C ÷ +100°C	50
TRN 16/12 NX	16x2	21	89,7	95	-55°C ÷ +100°C	50
TRN 18/14 NX	18x2	18	102,5	100	-55°C ÷ +100°C	50

■ Release tool Mod. DRK



CHARACTERISTICS						
Mod.	A	G	H	L	Weight (g)	Pack. (pcs)
DRK 6	6	25	6	19	1	10
DRK 8	8	28,5	7	20	1	10
DRK 10	10	30,5	9	22	2	10
DRK 12	12	33	9	23	3	10
DRK 15	15	36	10	27	3	10
DRK 16	16	37	10	27,5	4	10
DRK 18	18	40	12	31	5	10

■ Tube cutting tools Mod. PNZ and PNZP



CHARACTERISTICS	
Mod.	
PNZ-12	For tubes with Ø up to 12 mm
PNZ-25	For tubes with Ø up to 25 mm
PNZP-12	For tubes with Ø up to 12 mm

Assortment boxes / Repair kits

For the pneumatic system of commercial vehicles and trailers.

Air brake & Air suspension > Series 9000 Accessories > Series 6000

Our TRUCK-DCASE kits enable drivers to repair tube damage or other small issues on the connections when out on the road or in the field if professional repair or maintenance is out of reach.

These repair kits contain fittings in the most common sizes, the necessary release tools, as well as a tube cutting device. The TRUCK-DCASE also contains concise user instructions.

MODEL TRUCK-DCASE/6000

Repair kit with Series 6000 fittings

The kit is supplied with:

2x 6580 4	2x 6580 10	1x PNZP-12
2x 6580 5	1x 6580 12	
2x 6580 6	1x 6580 14	
2x 6580 8		

NOTE: the 6000 fittings are only for use in auxiliary applications (no Air Brake, no suspension, no powertrain).



MODEL TRUCK-DCASE/9000

Repair kit with Series 9000 fittings

The kit is supplied with:

2x 9580 6	1x DRK 6	1x PNZP-12
2x 9580 8	1x DRK 8	
2x 9580 10	1x DRK 10	
2x 9580 12	1x DRK 12	



MODEL TRUCK-DCASE/9000+6000

Repair kit with Series 9000 and Series 6000 fittings

The kit is supplied with:

1x 6580 4	2x 6580 10	2x 9580 6	1x DRK 6
1x 6580 5	1x 6580 12	2x 9580 8	1x DRK 8
1x 6580 6	1x 6580 14	1x 9580 10	1x DRK 10
1x 6580 8		1x 9580 12	1x DRK 12
			1x PNZP-12

NOTE: the 6000 fittings are only for use in auxiliary applications (no Air Brake, no suspension, no powertrain).



DISCOVER THE COMPLETE RANGE OF CAMOZZI AUTOMATION FITTINGS FOR THE TRANSPORTATION SECTOR



Fitting Series:

- **Series 1000**
Brass universal nose fittings
- **Series 2000**
Brass adaptors
- **Series 5000**
Quick release couplings
- **Series 6000**
Single seal brass
super-rapid fittings
- **Series HP6000**
Single seal brass
super-rapid fittings
for lubrication
- **Series 7000**
Single seal composite
super-rapid fittings
- **Series 8000/H8000**
Dual seal brass super-rapid fittings
- **Series 9000**
Dual seal brass Air Brake fittings
(metric/collet design)
- **Series ND**
Single seal brass Air Brake fittings
(Inch/collet design)



More Product Lines:



■ VALVES AND SOLENOID VALVES



■ ACTUATORS



■ AIR TREATMENT



Automation

A Camozzi Group Company

camozzi.com

Contacts

CamoZZi Automation S.p.A.

Società Unipersonale
REGISTERED OFFICE
Via R. Rubattino, 81
20134 Milano
Italy
OPERATIONAL HEADQUARTERS
Via Eritrea, 20/I
25126 Brescia
Italy
Tel. +39 030 37921
transportation@camozzi.com

Customer Service

Tel. +39 030 3792790
service@camozzi.com

Export Department

Tel. +39 030 3792253
sales@camozzi.com

