



# BIBUS

**BIBUS s.r.o.**

Vídeňská 125  
619 00 Brno  
Czech Republic  
Phone: +420 547 125 300  
Email: bibus@bibus.cz

[www.bibus.cz](http://www.bibus.cz)


**CSK  
by Stieber**


Type CSK is a sprag type freewheel integrated into a 62 series ball bearing (except sizes 8 and 40). It is bearing supported, delivered grease lubricated and protected against dust of more than 0,3 mm.


**GFR..F2F3  
by Stieber**

Type GFR..F2F3 is a ramp & roller type clutches, self-contained, sealed and bearing supported with 7 different covers providing a wide range of mounting configurations. There are 17 model sizes with torque ranges up to 51,6600 lb.ft. (70000 Nm).


**RSCI  
by Stieber**

Type RSCI is a centrifugal throwout sprag type overrunning clutch with the inner race rotating. Only the inner race is designed for overrunning. There are 36 model sizes with torque ratings up to 184,500 lb.ft. (250000 Nm).


**Clutches & Brakes  
by Stromag**

An array of electric, hydraulic and pneumatic clutches and brakes are available that feature extended product life and reduced maintenance.


**Couplings  
by Stromag**

Highly flexible couplings developed for a range of applications. Offset, plug-in, multi-segment, universal and support coupling types are available.


**Drum Brakes  
by Stromag**

Protected against adverse environmental effects, Stromag drum brakes have precisely tuned safety functions. In hoisting and travelling drives, they keep construction machinery safely in place and retain the rotary drives in required position. They permit easy adjustment of the braking torque with a precise scale control. Applications: Mining & Cement, Hydro Power, Oil & Gas, Harbour & Shipping, Steel, Power.


**Dura-Flex® and  
Sure-Flex Plus®  
by TB Wood's**

Dura-Flex and Sure-Flex couplings are highly flexible and able to accommodate shaft misalignment while minimizing vibration and preventing damage to connected equipment.


**MX Spring Applied Calipers  
by Twiflex**

The Twiflex MX13, MX25, MX30 and MX40 series of disc brake calipers is suitable for use with discs of 12.7mm, 25.4mm, 30mm and 40 mm thick respectively. The SMX caliper is only suitable for use with discs 12.7mm thick. Minimum disc diameter is 300mm.


**Magnetic Capping Headsets  
and Chucks  
by Warner Electric**

These screw capping headsets utilize smooth torque magnetic technology and are drop-in replacements for most OEM capping headsets. Replacement chucks and knives also available.


**Precision, Beam, and General Purpose Couplings  
by Huco**

Precision and large precision bellows couplings provide excellent kinetic properties with torque capacity from 12 Nm to 500 Nm and speed range up to 5,000 RPM in standard form. Zero backlash single piece couplings are available in six beam (two stage), three beam (single stage), and single beam models with torque capacity from 25 Nm to 140 Nm and speed range up to 5,000 RPM in standard form. Various types of general purpose couplings are available with torque capacity from 12 Nm to 44 Nm.