

SIME Brakes Industrial Braking Systems



Stromag

Founded in 1932, Stromag has grown to become a globally recognized leader in the development and manufacture of innovative power transmission components for industrial drivetrain applications. Stromag engineers utilize the latest design technologies and materials to provide creative, energy-efficient solutions that meet their customer's most challenging requirements.

Stromag's extensive product range includes flexible couplings, disc brakes, limit switches, an array of hydraulically, pneumatically, and electrically actuated brakes, and a complete line of electric, hydraulic and pneumatic clutches.

Stromag engineered solutions improve drivetrain performance in a variety of key markets including energy, off-highway, metals, marine, transportation, printing, textiles, and material handling on applications such as wind turbines, conveyor systems, rolling mills, agriculture and construction machinery, municipal vehicles, forklifts, cranes, presses, deck winches, diesel engines, gensets and stage machinery.



VISIT US ON THE WEB AT **STROMAG.COM**

Altra Motion

Altra is a leading global designer and producer of a wide range of electromechanical power transmission and motion control components and systems. Providing the essential control of equipment speed, torque, positioning, and other functions, Altra products can be used in nearly any machine, process or application involving motion. From engine braking systems for heavy duty trucks to precision motors embedded in medical robots to brakes used on offshore wind turbines, Altra has been serving customers around the world for decades.

Altra's leading brands include **Ameridrives**, **Bauer** Gear Motor, **Bibby** Turboflex, **Boston** Gear, **Delevan**, **Delroyd** Worm Gear, **Deltran**, **Formsprag** Clutch, **Guardian** Couplings, **Huco**, **Jacobs** Vehicle Systems, **Kilian**, **Kollmorgen**, **Lamiflex** Couplings, **Marland** Clutch, **Matrix**, **Nuttall** Gear, **Portescap**, **Stieber**, **Stromag**, **Svendborg** Brakes, **TB Wood's**, **Thomson**, **Twiflex**, **Warner** Electric, **Warner** Linear and **Wichita** Clutch

VISIT US ON THE WEB AT **ALTRAMOTION.COM**



SIME Brakes

SECURITY - QUALITY - RELIABILITY


With more than 60 years of experience, Stromag provide high efficiency braking systems to equip steel industries, nuclear plants, port cranes, offshore winches and mass transports throughout the world.

Quality and innovation have always been the two essential features in the development of the company. Therefore Stromag provide disc brakes certified by recognized authorities such as DNV, ABS, TUV, Loyd's Register and EDF.

In 2018, ISO 9001 certification of our Quality management system was renewed under the version V2015 and our Safety management system was awarded OHSAS 18001 - V2007 certification.

Whatever the application, Stromag meet the global supply requirements with standard or fully customised braking systems solutions.

OUR KNOW-HOW AT YOUR DISPOSAL



RESEARCH & DEVELOPMENT DEPARTMENT

In a mutually beneficial way, Stromag create a strong relationship with their customers in order to understand their needs and provide them the best solution. With in-depth knowledge and experience in all key applications and markets, our teams keep constantly abreast of every changing needs and market development.



TRAINING

After sales service team can provide to its customers training sessions : upgrade operations on-site or trainings in the production center in La Guerche (France). Each training consists of two parts : theoretical in a classroom / practical in the work-shop.

Topics : products operation, periodic maintenance, settings, fault diagnosis.

BENEFITS

- A team of experts at your disposal
- Reactivity of the interventions
- Study of the specific requirements
- Secured installation

- Optimal operation of the braking systems
- Preventive maintenance
- Expertise sustainability

Reactivity, availability and listening at the customer are values which define our teams. We put all our experience and knowledge at your disposal:



DIAGNOSIS

The After Sales team shares its “know-how” with companies having an important fleet to help them to realise a self-diagnosis on their brakes systems to achieve their maximal reliability in compliance with the safety regulations. The diagnosis takes place in two stages : a complete on-site examination of the different devices and a detailed report with synthesis for a global visibility.



INTERVENTION

Stromag has many sub-structures in France and worldwide ; these allow our After Sales Service Department to operate very fast in the customer sites. Each member of our team has a qualified engineering background which means they are totally able to help and advise customers technically and commercially.



Stromag developed a Monitoring system which allows to connect your braking system to one or several monitoring modules.

CAN Bus enables an easy connection, transmission and processing of a great quantity of data. The modules offer a high degree of adaptability and allow utilisation of transmission means as : SD cards, mobile telephone, internet.

SIME Brakes PRODUCTS



Hydraulic
emergency brakes



Hydraulic
Power Packs




Drums &
couplings




Drum brakes
with thrust
bearing



Disc brakes
with thrust
bearing



Discs &
couplings



COMPLETE BRAKING SOLUTIONS




Electrical
power units



Electromagnetic
emergency brakes



Safety systems



Electromagnetic
service brakes

SOLUTIONS FOR YOUR APPLICATION



Solutions for **BOAT LIFTING SYSTEMS**

- Hydraulic service brakes type SHD
- Hydraulic emergency brakes type SH
- Custom Hydraulic Power Packs
- Touch-screen and control interfaces
- CRD systems for regulated braking
- Tailor made solutions



Solutions for **CONSTRUCTION INDUSTRIES**

- Hydraulic brakes
- Electromagnetic brakes
- Thrustors brakes
- Drum brakes
- Discs & Couplings
- Hydraulic Power Packs
- Electrical units
- Safety and control systems



Solutions for **PORTS**

- Hydraulic brakes
- Electromagnetic brakes
- Thrustors brakes
- Drum brakes
- Discs & Couplings
- Hydraulic Power Packs
- Electrical units
- Safety and control systems

HIGH CUSTOMERS SATISFACTION

SIME Brakes products and services comply with the requirements of our customers in terms of quality, safety, service life, easy maintenance and delivery times. The quality and environmental policy is an integral part of our company policy.

The certification ISO9001 of our Quality management system is renewed under the version ISO 9001 - V2015 in 2018, combined with OHSAS 18001 - V2007 certification.

With more than 60 years of experience in the supply of high efficiency braking systems, Stromag provides disc brakes certified by recognised organisations such as DNV, ABS, TUV, Loyd's Register and EDF.

SIME Brakes Industrial Braking Systems




Solutions for STEEL INDUSTRIES

- Hydraulic brakes
- Electromagnetic brakes
- Thrustors brakes
- Drum brakes
- Discs & Couplings
- Hydraulic Power Packs
- Electrical units
- Safety and control systems



Solutions for MARINE & OFFSHORE

- Hydraulic brakes
- Electromagnetic brakes
- Thrustors brakes
- Drum brakes
- Discs & Couplings
- Hydraulic Power Packs
- Electrical units
- Monitoring systems



Solutions for NUCLEAR INDUSTRIES

- Hydraulic brakes
- Electromagnetic brakes
- Thrustors brakes
- Drum brakes
- Discs & Couplings
- Hydraulic Power Packs
- Electrical units
- Monitoring systems

Lloyd's Register
Marine Design



CERTIFICATE OF DESIGN

This is to Certify that a represent
STROMAG FRANCE

assures design plans and data for the below
Bureau as to the degree of compliance the
assessments does not warrant certification
products to be used in ABS classification, well
the product is Type Approved.

PRODUCT : Brake
MODEL : Caliper SH18B Offshore

This Product Design Assessment (PDA) Certificate 12-G
the Rules or specifications used in the assessment are rev
This PDA is intended for a product to be installed on an
for structures on the date of the ABS Rules or specific
Use of the Product on an ABS classed vessel, Model or
representative of the vessel must be certified by
Type Designation action pad listed.

A. Machinery

Type Designation

B. Brake Details

Nominal Holding Force 1870N

Maximum Holding Force 1870N

Maximum Working Pressure 0.8 MPa

Minimum coefficient of friction dry cond

Type Designation action pad listed

C. Comments

All materials used apart from the E

Manufacture, Testing and Certificat

The friction coefficient of the brake

results are to be satisfactory.

FNAL ACCEPTANCE OF

Lloyd's Register, its officers and employees and their respe
Bureau Group - The Lloyd's Register Group employs no re
and has no authority to make any representations or give any
of ABS, its members, its agents or other authorized entities. Any representations made by

These documents are the property of ABS. They are to be returned to ABS or destroyed without notice if they are no longer required.

Form 6498MAA (2011-01)



Appareil non électrique destiné
à l'exploitation dans les zones
dangereuses.

Non electrical equipment intend
for operation in dangerous areas.

Nicht-elektrisches Gerät zur Ver
wendung in gefährlichen Gebieten.

Appareil/Equipment/Gerät :

Frein à disque

Type(s) / Type(s) / Type(s) : SH 18 B

Manager/ Marking / Kennzeichnung :

Dépositaire / Applicant / Kennzeichner :

L'INERIS, organisme notifié et
mentionné sous le numéro 0080,

conformément à l'article 5 de la
Directive 94/9/CE du Conseil du 29
mars 1994, accorde réception du
dossier conformément à la procédure
accordée par l'article 8 à 10 de la
Directive.

La documentation technique
référant au produit SH 18 B

est conservée sous le numéro
d'empennage :

n° INERIS-CQH 028148/4.

Date de la validation :

2024.01.07

Signature :

Le Directeur Général de l'INERIS,
Rue des Saussaies, T. HOUSS
Délibéré Certification ATEX

Ce document ne peut être reproduit que sous ma responsabilité.

INERIS

Le document est émis à l'attention de l'organisme de certification.

Partie Technologique :
MFR + 33035 44 55 66 77

Institut national de
l'évaluation publique à caractère industriel et com

Altra Stromag France

18100 LA GUERCHE (LA LOIRE)

France

ISO 9001 : 2015

Design, manufacture, put at disposal or deliver brak

with relevant accessories for use in industr

and handling applications and machine pr

production and people transportation.

Technical support and service before an

and maintenance training and produc

This certificate is valid from 22 March 2017 until 14 Se

and remains valid subject to satisfactory surve

Issue 2, First Certification date 17

2016

Signature :

Le Directeur Général de l'INERIS,
Rue des Saussaies, T. HOUSS
Délibéré Certification ATEX

Ce document ne peut être reproduit que sous ma responsabilité.

INERIS

Le document est émis à l'attention de l'organisme de certificat

ation.

Partie Technologique :
MFR + 33035 44 55 66 77

Institut national de

l'évaluation publique à caractère industriel et com

SGS

Certificate FR16R18A2104

The management system of

Stromag France S.A.S.

avenue de l'Europe, BP 24

18100 LA GUERCHE (LA LOIRE)

France

ISO 9001 : 2015

For the following activities

Design, manufacture, put at disposal or deliver brak

with relevant accessories for use in industr

and handling applications and machine pr

duction and people transportation.

Technical support and service before an

and maintenance training and produc

This certificate is valid from 23 August 2016 until 2 February 2019

and remains valid subject to satisfactory surve

Issue 2, First Certification date February 2016

Signature :

Le Directeur Général de l'INERIS,
Rue des Saussaies, T. HOUSS
Délibéré Certification ATEX

Ce document ne peut être reproduit que sous ma responsabilité.

INERIS

Le document est émis à l'attention de l'organisme de certificat

ation.

Partie Technologique :
MFR + 33035 44 55 66 77

Institut national de

l'évaluation publique à caractère industriel et com

petitio

DNV GL

Certificate No:

TAS0000147

CATE

-3, SH15-1, SH15-2, SH15-3,

and platform lifting appliances

installation on all vessels classed

for DNV GL

DNV GL

Head of Section

Aldo Mazzocchi

Signature :

Le Directeur Général de l'INERIS,
Rue des Saussaies, T. HOUSS
Délibéré Certification ATEX

Ce document ne peut être reproduit que sous ma responsabilité.

INERIS

Le document est émis à l'attention de l'organisme de certificat

ation.

Partie Technologique :
MFR + 33035 44 55 66 77


Institut national de

l'évaluation publique à caractère industriel et com

petitio

SIME Brakes Industrial Braking Systems

Content




CONTENT

SERVICE BRAKES	12
ELECTROMAGNETIC SERVICE BRAKES	15
DRUM BRAKES	27
HYDRAULIC SERVICE BRAKES	35
THRUSTOR SERVICE BRAKES	39
EMERGENCY BRAKES	46
ELECTROMAGNETIC EMERGENCY BRAKES	49
HYDRAULIC EMERGENCY BRAKES TYPE SH	55
HYDRAULIC EMERGENCY BRAKES TYPES SHD / TH	83
ELECTRICAL POWER UNITS	98
HYDRAULIC POWER PACKS	114
CONTROL AND SAFETY SYSTEMS	128
DISCS & DRUMS	144
DISC COUPLINGS	158
CARDAN SHAFTS	174
HYDRAULIC BUFFERS	180
BARREL-ROLLER COUPLINGS	186

Service Brakes


SERVICE BRAKES




SIME Brakes Industrial Braking Systems

Service Brakes


ELECTROMAGNETIC BRAKES	
645-650-660 5K / 45 K discs Ø175 to 625	
1CA2-2CA2 3CA2-4CA2 discs Ø445 to 995	




DRUM BRAKES	
FNS-VS SDB drums Ø160 to 710	
SAB drums Ø6" to 30" (Ø152 to 762mm)	



HYDRAULIC BRAKES	
2TB-3TB-4TB discs Ø445 to 995	
1TSA-1TXA discs Ø625 to 995	



THRUSTOR BRAKES	
TDXB I and II FAV 10 to 50 discs Ø220 to 995	



SIME Brakes Industrial Braking Systems

Service Brakes

APPLICATIONS

- STEEL CRANES
- PORT CRANES
- NUCLEAR CRANES
- MASS TRANSPORTS





Photo courtesy of EDF



ELECTROMAGNETIC SERVICE BRAKES

MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none"> • FAILSAFE BRAKE BY SPRING APPLICATION • ELECTROMAGNETIC RELEASE • OPENING PROVING SWITCH 	<ul style="list-style-type: none"> • MECHANICAL RELEASE LEVER • HYDRAULIC RELEASE • CLOSING PROVING SWITCH • MANUAL RELEASE CONTROL SWITCH • HIGH TEMPERATURE, IRON AND STEEL CONDITIONS



645-650-660


- Association with discs Ø175 to 625
- Manual wear compensation
- Option:
Mounting on a vertical axis disc

**5K - 5D
45K - 45D**

- Association with discs Ø315 to 625
- Automatic wear compensation
- Option:
Mounting on a vertical axis disc

**4CA2 - 3CA2
2CA2 - 1CA2**

- Association with discs Ø445 to 995
- Automatic wear compensation
- Left and right hand calipers
- Option: Manual wear compensation



SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - 650 AND 660 CALIPERS

Revision number: T03150-01-G

Revision date: 10.04.2018

Fail safe braking
Spring application
Electromagnetic release
Manual lining wear compensation
Brake pads with wear indicator
Opening proving switch for PLC
With coil supply wire: 2 x 2mm², length 2m

Conditions of use:


- Ambiant temperature -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult SIME-Stromag.

Use:

- Service brake for application ≤ 150 stops/h

Options:

- Lowering system with lever
- Hydraulic lowering system
- Mounting on vertical axis disc
- Marine protection
- Closing proving switch
- Manual release switch



Opening proving switch :

250VAC max., 5A max., with interrupting capacity: 50VA max.
220VDC max., 5A max., with interrupting capacity: 50W max.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

The opening switch is delivered with 3 x 0.75mm² cable, length 2m

Weight: 19 kg
Dimensions in mm

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs		Thickness 15 mm										Thickness 30 mm						
Maximum speed of the disc for nominal torque		tr/mn	5000	4300	3600	3000	2400	2100	1900	1800	1500	3000	2700	2400	2100	1900	1800	1500
D	mm		175	220	260	315	395	445	495	550	625	315	355	395	445	495	550	625
d	mm	0-40	0-55	0-75	0-75	0-75	0-75	0-75	0-100	0-100	0-100	0-50	0-60	0-70	0-70	0-100	0-100	0-100
E	mm		118	128	143	173	213	238	263	293	328	173	193	213	238	263	293	328
F	mm		106	116	131	161	201	226	251	281	316	161	181	201	226	251	281	316
G	mm		85	85	85	75	60	50	45	45	25	75	60	60	50	45	45	25
I (approx. dimension)	mm		43	53	68	98	138	163	188	218	253	98	118	138	163	188	218	253
Caliper 650 :																		
Nominal torque for 1 caliper adjustable from 100% to 50%		N.m	110	130	150	190	260	300	350	390	460	190	220	260	300	350	390	460
Max. reaction on shaft	1 caliper N		1600										1600					
	2 calipers N		0	260	570	580	560	510	680	260	550	570	580	560	510	680		
Caliper 660 :																		
Nominal torque for 1 caliper adjustable from 100% to 60%		N.m	55	65	75	95	130	150	175	195	230	95	110	130	150	175	195	230
Max. reaction on shaft	1 caliper N		800										800					
	2 calipers N		0	130	285	290	280	255	340	130	275	285	290	280	255	340		

DISC BRAKE - 645 CALIPER

Revision number: T03250-01-E

Revision date: 10.04.2018

Fail safe braking
Spring application
Electromagnetic release
Manual wear compensation
Brake pads with wear indicator
Opening proving switch for PLC
With coil supply wire: 2 x 2mm², length 2m

Conditions of use:


- Ambiant temperature -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:

- Service brake for application ≤ 150 stops/h

Options:

- Lowering system with lever
- Hydraulic lowering system
- Mounting on vertical axis disc
- Marine protection
- Closing proving switch
- Manual release switch



Weight: 35 kg
Dimensions in mm

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Designation	Discs	solid and thickness 15 mm						self-ventilated and thickness 30 mm						
		380	520	600	700	780	920	380	440	520	600	700	780	
Nominal torque for 1 caliper adjustable from -30% to +20%	N.m	380	520	600	700	780	920	380	440	520	600	700	780	
Maximum speed of the disc for nominal torque	rpm	3000	2400	2100	1900	1800	1500	3000	2700	2400	2100	1900	1800	
D	mm	315	395	445	495	550	625	315	355	395	445	495	550	
d	mm	0-75	0-75	0-75	0-100	0-100	0-100	0-50	0-60	0-70	0-70	0-100	0-100	
E	mm	173	213	238	263	293	328	173	193	213	238	263	293	
F	mm	161	201	226	251	281	316	161	181	201	226	251	281	
G	mm	95	80	70	65	65	45	95	80	80	70	65	45	
I (approx. dimension)	mm	76	116	141	166	196	231	76	96	116	141	166	196	
Max. reaction on shaft	1 caliper 2 calipers	N N	3850						3850					
			405	405	810	895	780	1230	405	515	450	810	895	780
														1230

SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - 5K AND 5KR CALIPERS

Revision number: T03350-01-E

Revision date: 09.04.2018

Fail safe braking / Spring application

Electromagnetic release

Automatic wear compensation

Detection of full lining wear

Brake pads with wear indicator

Opening proving switch

Association with discs th. 30mm (or 15mm in option)


With coil supply wire: 2 x 2mm², length 2m

Conditions of use:

- Ambiant temperature - 10°C to + 60°C
- Relative humidity ≤ 70 %
- Dust in atmosphere ≥ 65 µ
- Other conditions, consult us.

Options:

- Lowering system with lever
- Hydraulic lowering system
- Marine protection
- Vertical mounting
- Reduced torque
- Closing proving switch
- Manual release switch
- Association with discs th.15mm



Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

The opening switch is delivered with 3 x 0.75mm² cable, length 2m

Weight: 27 kg
Dimensions in mm

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs	315	355	395	445	495	550	625
Maximum speed of the disc for nominal torque	rpm	3000	2700	2400	2100	1900	1800
D	mm	315	355	395	445	495	550
d	mm	0-50	0-60	0-70	0-70	0-100	0-100
E	mm	100	120	140	160	190	220
F	mm	85	105	125	145	175	205
G	mm	160	164	170	180	185	195
I (approx. dimension)	mm	72	92	113	135	160	197
Caliper 5K :							
Nominal torque for 1 caliper adjustable from - 50% to +20%	N.m.	190	220	260	300	350	390
Maximum reaction on shaft	1 caliper N 2 calipers N				1950 1150		
Caliper 5KR :							
Nominal torque for 1 caliper adjustable from 100% to -50%	N.m.	95	110	130	150	175	195
Maximum reaction on shaft	1 caliper N 2 calipers N				815 480		

DISC BRAKE - 5KE CALIPER

Revision number: T03400-01-D

Revision date: 21.03.2016


Fail safe braking
 Spring application
 Electromagnetic release
 Electrical progressive braking
 Automatic wear compensation
 Detection of full lining wear
 Opening proving switch
 With coil supply wire: 2 x 2mm², length 2m

Conditions of use:

- Ambiant temperature - 10°C to + 60°C
- Relative humidity ≤ 70 %
- Dust in atmosphere ≥ 65 µ
- Other conditions, consult us.

Options:

- Hydraulic release
- Marine protection
- Vertical mounting



Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.
 220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

Opening switch is delivered with 3 x 0.75mm² cable, length 2 m

Weight: 45 kg
 Dimensions in mm

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs	315	355	395	445	495	550	625	
Progressive torque for 1 caliper adjustable from 0% to 100% *	N.m	190	220	260	300	350	390	460
Nominal torque for 1 caliper adjustable from 100% to -50%	N.m	190	220	260	300	350	390	460
Maximum speed of the disc for nominal torque	rpm	3000	2700	2400	2100	1900	1800	1500
D	mm	315	355	395	445	495	550	625
d	mm	0-50	0-60	0-70	0-70	0-100	0-100	0-100
E	mm	100	120	140	160	190	220	255
F	mm	85	105	125	145	175	205	240
G	mm	160	164	170	180	185	195	205
I (approx. dimension)	mm	72	92	113	135	160	197	233
Maximum reaction on shaft	1 caliper 2 calipers	N N		1950 1150				

* For electro with working rate of 40%

SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - 5D AND 5DR CALIPERS

Revision number: T03360-01-E

Revision date: 21.03.2016


Fail safe braking
Spring application
Electromagnetic release
Automatic wear compensation
Brake pads with wear indicator
Opening proving switch
With coil supply wire: 2 x 2mm², length 2m

Conditions of use:

- Ambiant temperature - 10°C to + 60°C
 - Relative humidity ≤ 70 %
 - Dust in atmosphere ≥ 65 µ
- Other conditions, consult us.

Options:

- Manual release lever
- Hydraulic release
- Marine protection
- Vertical mounting
- Reduced torque
- Closing proving switch
- Manual release switch



Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

The opening switch is delivered with 3 x 0.75mm² cable, length 2m

Weight: 27 kg
Dimensions in mm

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs	220 M30	260 M30	315 M30	315	355	395	445	495	550	625
Maximum speed of the disc for nominal torque	rpm	4300	3600	3000	3000	2700	2400	2100	1900	1800
D	mm	220	260	315	315	355	395	445	495	550
d	mm	20-55	30-55	35-60	0-50	0-60	0-70	0-70	0-100	0-100
E	mm	65	80	100	100	120	140	160	190	220
F	mm	50	65	85	85	105	125	145	175	205
G	mm	150	153	160	160	164	170	180	185	195
I (approx. dimension)	mm	51	68	88	88	108	128	151	176	213
Caliper 5D :										
Nominal torque for 1 caliper adjustable from - 50% to +20%	N.m.	130	150	190	190	220	260	300	350	390
Maximum reaction on shaft	1 caliper N 2 calipers N					1950 1150				
Caliper 5DR :										
Nominal torque for 1 caliper adjustable from 100% to -50%	N.m.	65	75	95	95	110	130	150	175	195
Maximum reaction on shaft	1 caliper N 2 calipers N					815 480				

DISC BRAKE - 5DE CALIPER

Revision number: T03410-01-D

Revision date: 22.03.2016


Fail safe braking
 Spring application
 Electromagnetic release
 Electrical progressive braking
 Automatic wear compensation
 Detection of full lining wear
 Opening proving switch
 With coil supply wire: 2 x 2mm², length 2m

Conditions of use:

- Ambiant temperature - 10°C to + 60°C
- Relative humidity ≤ 70 %
- Dust in atmosphere ≥ 65 µ
- Other conditions, consult us.

Options:

- Hydraulic release
- Marine protection
- Vertical mounting



Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.
 220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

Opening switch is delivered with 3 x 0.75mm² cable, length 2 m

Weight: 45 kg
 Dimensions in mm

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs	220M30	260M30	315M30	315	355	395	445	495	550	625	
Progressive torque for 1 caliper adjustable from 0% to 100% *	N.m	130	150	190	190	220	260	300	350	390	460
Nominal torque for 1 caliper adjustable from 100% to -50%	N.m	130	150	190	190	220	260	300	350	390	460
Maximum speed of the disc for nominal torque	rpm	4300	3600	3000	3000	2700	2400	2100	1900	1800	1500
D	mm	220	260	315	315	355	395	445	495	550	625
d	mm	20-55	30-55	35-60	0-50	0-60	0-70	0-70	0-100	0-100	0-100
E	mm	65	80	100	100	120	140	160	190	220	255
F	mm	50	65	85	85	105	125	145	175	205	240
G	mm	150	153	160	160	164	170	180	185	195	205
I (approx. dimension)	mm	51	68	88	88	108	128	151	176	213	248
Maximum reaction on shaft	1 caliper 2 calipers	N N				1950 1150					

* For electro with working rate of 40%

SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - 45K and 45D calipers

Revision number: T00140-01-J

Revision date: 10.04.2018

Fail safe braking
Spring application
Electromagnetic release
Automatic linings wear compensation
Opening proving switch
Coil with supply wire: 2 x 2mm², length 2m
Association with 30mm thick discs (or 15mm in option)
Shoes DIN (caliper 45D) for discs thickness 30mm only.

Conditions of use :


- Ambiant temperature -20°C to + 60°C
- Relative humidity ≤ 70 %
- Dust in atmosphere ≥ 65 µ
- Other conditions, consult us.

Use:

- Service brake for application ≤ 600 cycles / h
Possibility of quick manœuvres :
1000 cycles/h during 15s every 2 mn

Options:

- Lowering system with lever
- Hydraulic lowering system
- Manual wear compensation (RM)
- Marine protection
- SIDHT steel industry high temperature
- Bearing brackets for mounting in place of a caliper 645.
- Mounting on a vertical axis disc.
- Closing proving switch
- Manual release switch



Nota :

The 45K-RM and 45D-RM calipers (manual wear compensation option) have the same overall dimensions as the 45K and 45D calipers with automatic wear compensation.

* ATTENTION

For discs Ø315 to 395, the length of 137 max. is higher than the length L of the standard hub. Provide space at the rear of the hub by means of a spacer.

Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

Weight: 41 kg
Dimensions in mm

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Caliper delivered in standard with WS1-5 lining.

For energy applications, use WS1-3 (torque loss of 20%).

Designation	Discs	solid and thickness 15 mm (option)							ventilated and thickness 30 mm						
		315	355	395	445	495	550	625	315	355	395	445	495	550	625
D Disc diameter	mm	315	355	395	445	495	550	625	315	355	395	445	495	550	625
Nominal torque for 1 caliper adjustable from -30% to +20%	N.m	410	470	560	650	750	840	990	410	470	560	650	750	840	990
Maximum speed of the disc for nominal torque	r.p.m.	3000	2700	2400	2100	1900	1800	1500	3000	2700	2400	2100	1900	1800	1500
d	mm	0-75	0-75	0-75	0-75	0-100	0-100	0-100	0-50	0-60	0-70	0-70	0-100	0-100	0-100
E	mm	100	120	140	160	190	220	255	100	120	140	160	190	220	255
F	mm	50	70	90	110	140	170	205	50	70	90	110	140	170	205
G	mm	160	164	170	180	185	195	205	160	164	170	180	185	195	205
I (calipers 45K, 45K-RM)	mm	75	95	116	138	168	200	236	75	95	116	138	168	200	236
I (caliper 45D)	mm								75	95	116	138	168	200	236
I (caliper 45D-RM)	mm								96	116	137	159	189	221	257
Maximum reaction on shaft	1 Caliper	N							4200						
	2 Calipers	N							2450						

DISC BRAKE - 4CA2 CALIPER

Revision number: T10049-01-D

Revision date: 22.03.2016

Fail safe braking
Braking by spring application
Electromagnetic release
Automatic wear compensation
Opening proving switch
Brake pads with wear indicator

Working conditions:


- Ambient temperature: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:

Any application up to 1000act/h

Options:

- Manual release lever
- Hydraulic release
- Manual wear compensation
- Flameproof protection
- Marine protection
- Closing proving switch
- Switch on release nut



Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs		445	495	550	625	705	795
Nominal torque for 1 caliper adjustable from -30 to +20%	N.m	950	1100	1270	1500	1750	2000
Maximum disc speed for nominal torque	r.p.m.	2100	1900	1800	1500	1300	1200
D	mm	445	495	550	625	705	795
d	mm	0-70	0-100	0-100	0-100	0-120	0-130
E	mm	130	160	180	215	255	295
F	mm	110	140	160	195	235	275
G	mm	225	235	240	250	260	275
I (approx. dimension)	mm	90	125	145	180	225	265
Maximum reaction on shaft	1 caliper N			7400			
	2 calipers N			4450			

Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - 3CA2 CALIPER

Revision number: T10050-01-D

Revision date: 09.04.2019

Fail safe braking
Braking by spring application
Electromagnetic release
Automatic wear compensation
Opening proving switch
Brake pads with wear indicator

Working conditions:


- Ambient température: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:

Any application up to 1000act/h

Options:

- Manual release lever
- Hydraulic release
- Manual wear compensation
- Load regulated lowering
- Steelworks flameproof protection
- Marine protection / • Special paint
- Closing proving switch
- Switch on release nut



Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs		445	495	550	625	705	795
Nominal torque for 1 caliper adjustable from -30 to +20%	N.m	1600	1850	2100	2500	2900	3350
Maximum disc speed for nominal torque	r.p.m.	2100	1900	1800	1500	1300	1200
D	mm	445	495	550	625	705	795
d	mm	0-70	0-100	0-100	0-100	0-120	0-130
E	mm	100	120	150	185	225	265
F	mm	80	100	130	165	205	245
G	mm	285	295	305	315	330	345
I (approx. dimension)	mm	90	115	145	180	225	265
Maximum reaction on shaft	1 caliper N	12300					
	2 calipers N	7400					

Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers). An opening switch used with other equipment than PLC must not be reused with a PLC.

DISC BRAKE - 2CA2 AND 1CA2 CALIPERS

Revision number: T10051-01-D / T10065-02-B

Revision date: 09.04.2019

Fail safe braking
Braking by spring application
Electromagnetic release
Automatic wear compensation
Opening proving switch
Brake pads with wear indicator

Working conditions:


- Ambient temperature: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Options:

- Manual wear compensation
- Steelworks flameproof protection
- Marine protection
- Special paint

Use:

Any application up to 600act/h



Discs		625	795	995
D	mm	625	795	995
d	mm	40-140	40-180	40-180
E	mm	157	250	345
F	mm	127	220	315
G	mm	353	385	415
I (approx. dimension)	mm	174	268	368

Response time at nominal torque : see the leaflet of the associated electrical power supply.

Discs	625	795	995	
2CA2				
Nominal torque for 1 caliper adjustable from -30 to +20%	N.m	3 800	5 150	6 700
Maximum disc speed for nominal torque	r.p.m.	1 500	1 200	900
Maximum reaction on shaft	1 caliper N	18 600		
	2 calipers N	12 600		

Discs	625	795	995	
1CA2				
Nominal torque for 1 caliper adjustable from -50 to 100%	N.m	6 610	8 800	11 370
Maximum disc speed for nominal torque	r.p.m.	310	250	200
Maximum reaction on shaft	1 caliper N	25 700		
	2 calipers N	16 300		


SIME Brakes Industrial Braking Systems

Service Brakes

APPLICATIONS

- MINING
- HYDRO POWER
- OIL & GAS
- HARBOUR & SHIPPING

- STEEL
- POWER
- CEMENT



DRUM BRAKES

MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none"> • FAILSAFE BRAKES • SPRING APPLIED ELECTROHYDRAULIC THRUSTOR RELEASED • ADJUSTABLE BRAKING TORQUE 	<ul style="list-style-type: none"> • OPENING PROVING SWITCH • FULL LINING WEAR INDICATORS • HAND RELEASE LEVER • HIGH TEMPERATURE, SPECIAL PROTECTION, DELAY. ...



SDB

- Ass. with drums Ø 160 to 710
- Standard DIN 15435
- Voltage: 230/400VAC 50Hz
- Automatic lining wear compensation
- Protection C4M



SAB


- Ass. drums Ø 6" to 30" (152 to 762mm)
- Standard AISE N.11 - 63.120
- Voltage: 230/460VAC 60Hz
- Automatic lining wear compensation
- Protection C4M



FNS-VS

- Ass. with drums Ø 160 to 710mm
- Standard DIN 15435
- Voltage: 230/400VAC 50Hz
- Protection C3M
- Option: certificat ATEX / thrustor

Braking torque (kN.m)



SIME Brakes Industrial Braking Systems

Service Brakes

DRUM BRAKE - SDB BRAKES

Revision number: T10110-01-G

Revision date: 21.01.2020

Standard DIN 15435


- Spring application braking
- Thrustor release
- Standard voltage 230/400 VAC 50Hz
- Protection level C4M
- Automatic lining wear compensation

• Brake shoe auto-aligning device

- Scale for torque adjustment
- Brake lever synchronization
- Aluminium shoes with non asbestos organic linings
- Self lubricated bushings at main hinge points
- Galvanized steel spindles and hinges

Operating conditions

- Ambient temperature : -20°C to 50°C
- Relative humidity no higher than 90%
- IP rating: IP65



Options :

HRL	Manual release lever with or without stop
BRLS	Switch for opening monitoring
LWI	Full lining wear indicators
SS1	Special Switch: Schneider XCKM 110H29
SS2	Special Switch: Schmersal Z4VH335 11Z
AV - DV	Thrustor delay : Ascent Valve or Descent Valve
SV 415V 50Hz	Special Voltage
SV 500V 50Hz	
SV 480V 60Hz	
SW	Steel Works (specific oil in the thrustor + heat resistant sealings)
SPA	Special paint according to the customer


Thrustor Technical Data :

Thrustor type	Power (W)	Current at 400 V (A)	Weight (kg)
TS 230/5	165	0.52	10
TS 300/5	200	0.46	14
TS 500/6	200	0.48	21
TS 800/6	330	1.42	24
TS 1210/6	330	1.44	39
TS 2010/6	450	1.45	39
TS 3010/6	550	1.46	40

DRUM BRAKE - SDB BRAKES

Revision number: T10110-01-G

Revision date: 21.01.2020



BRAKE TYPE	THRUSTOR	TORQUE (N.m.)		WEIGHT (kg)	DIMENSIONS (mm)													
		min.	max.		A	b	C	D	d	E	F	G1	G2	H	h1	i	k	n
SDB 160	TS 230/5	80	160	28	428	65	160	160	14	140	85	145	195	418	160	55	130	8
SDB 200	TS 230/5	110	260	35	470	70	160	200	14	172	90	165	255	490	160	55	145	10
SDB 250	TS 230/5	140	300	45	533		160	250	18	202	110	200	290	583	190	65	180	12
	TS 300/5	180	380	48		90												
	TS 500/6	300	600	53	570		195											
SDB 315	TS 230/5	180	340	70			160											
	TS 300/5	250	500	70	670	110		315	18	253	115	245	330	585	230	80	220	14
	TS 500/6	315	770	75			195											
	TS 800/6	630	1200	80														
SDB 400	TS 500/6	400	960	138	695		195	400	22	310	160	310	420	715	280	100	270	14
	TS 800/6	630	1500	140		140								775				
	TS 1210/6	1000	2400	155	810		240											
SDB 500	TS 800/6	800	1920	176										803				
	TS 1210/6	1250	3000	204	925	180	240	500	22	380	180	365	535	830	340	130	325	21
	TS 2010/6	2000	4800	204														
SDB 630	TS 1210/6	1800	3780	310														
	TS 2010/6	2500	6000	310	1150	225	240	630	27	465	220	450	600	1025	420	170	400	20
	TS 3010/6	4000	8500	315														
SDB 710	TS 2010/6	3150	6000	435	1180	225	240	710	27	520	240	500	630	1135	470	190	450	25
	TS 3010/6	5000	9600	441														

Service Brakes

DRUM BRAKE - SAB BRAKES

Revision number: T10110-02-F


Revision date: 13.02.2020

Standard AISE N. 11 - 63.120

- Spring application braking
- Thrustor release
- Standard voltage 230/460 VAC 60Hz
- Paint color RAL7021
- Protection level C4M
- Automatic lining wear compensation
- Brake shoe auto-aligning device
- Scale for torque adjustment
- Brake lever synchronization
- Aluminium shoes with non asbestos organic linings
- Self lubricated bushings at main hinge points
- Galvanized steel spindles and hinges

Operating conditions

- Ambient temperature : -20°C to 50°C
- Relative humidity no higher than 90%
- IP rating : IP65



Options :

AV - DV	Thrustor delay : Ascent Valve or Descent Valve
BRLS	Switch for opening monitoring
HRL	Hand release lever with or without stop
HRLM	Switch for hand release monitoring
LWI	Full lining wear indicators
SPA	Paint according to Customer Specification
SV	Special Voltage


Thrustor Technical Data :

Thrustor type	Power (W)	Current at 400 V (A)	Weight (kg)
TS 230/5	200	0.5	14
TS 300/5	200	0.5	14
TS 500/6	210	0.5	23
TS 800/6	330	1.2	24
TS 1210/6	330	1.2	39
TS 2010/6	450	1.3	39
TS 3010/6	550	1.4	40

DRUM BRAKE - SAB BRAKES

Revision number: T10110-02-F

Revision date: 13.02.2020



* Average friction factor of standard material combination $\mu = 0,4$.
All dimensions are in inches. In () mm

According to standard **AISE N. 11 - 63.120**

Brake type	Thruster TS	$M_{BR\ MAX}$ (lb-ft) *	A	b	C	D	d	E	F	H	h1	i	k	n	Weight (lb)
SAB - 6"	230/5	55-110	17	1.65	6.3	6 (152)	3/8 (9.5)	5.5	7.25	16.5	4.75 (120)	3 (76)	4 (102)	0.38	70
SAB - 8"	230/5	85-190	26.00	3.00	6.3	8 (203)	0.69 (17)	6.77	7.25	20	7.0 (178)	5.76 (146)	3.25 (83)	0.31	77
SAB - 10"	300/5	140-275	30.30	3.54	6.3	10 (254)	0.69 (17)	7.95	8.00	23.2	8.38 (213)	6.26 (160)	4.0 (102)	0.60	106
	500/6	220-440	31.00		7.7										116
SAB - 12"	300/5	170-345	37.00	5.51	6.3	12 (305)	0.81 (21)	10.40	11.00	23.4	9.88 (251)	9.0 (228)	5.75 (146)	0.60	155
	500/6	270-540			7.7										164
	800/6	430-855													176
SAB - 13"	300/5	180-375	37.00	5.51	6.3	13 (330)	0.81 (21)	10.40	11.00	23.4	9.88 (251)	9.0 (228)	5.75 (146)	0.60	160
	500/6	295-590			7.7										164
	800/6	460-930													176
SAB - 15"	500/6	330-665	40.20	6.49	6.3	15 (381)	1.06 (27)	12.20	13.25	28.4	12.13 (308)	10.76 (273)	7.5 (191)	0.60	300
	800/6	515-1030			9.45										308
	1210/6	840-1675	44.50												335
SAB - 16"	500/6	355-710	40.20	6.49	7.7	16 (406)	1.06 (27)	12.20	13.25	28.4	12.13 (308)	10.76 (273)	7.5 (191)	0.60	304
	800/6	550-1110			9.45										308
	1210/6	900-1800	44.50												335
SAB - 19"	800/6	665-1330	49.00	8.50	7.7	19 (483)	1.06 (27)	15.00	16.20	31.9	13.25 (337)	13 (330)	9.25 (235)	0.79	445
	1210/6	1055-2110			9.45					32.7					455
	2010/6	1700-3390													455
SAB - 23"	1210/6	1220-2440	63.40	10.98	9.45	23 (584)	1.31 (33)	17.50	18.75	41.0	15.88 (403)	16 (406)	11.75 (298)	0.79	695
	2010/6	1900-3870													695
	3010/6	2850-5760													705
	3010/12	3450-6900													
SAB - 30"	1210/6	1400-2800	68.00	14.01	9.45	30 (762)	1.56 (40)	21.50	23.00	44.5	20.75 (527)	19 (482)	15.0 (381)	1.18	950
	2010/6	2360-4720													950
	3010/6	3650-7370													980
	3010/12	4400-8800													

SIME Brakes Industrial Braking Systems

Service Brakes

DRUM BRAKE - FNS-VS 160 TO 400 BRAKES

Revision number: T03109-01-E


Revision date: 27.07.2016

Standard DIN 15435

Spring application
Thruster release
Protection level : C3M
Voltage : 230 / 400V 50 Hz
Other voltages, consult us.

AT High temperature
BT Low temperature
ATEX Certificat ATEX / Thrustor
BI Stainless steel bolts
CSA Opening proving switch
DD Lining wear indicators
DM Hand release lever

LM Locking lever to hold the brake open
PE Special paint : color / > C3M
PL Padlock for the locking lever
PR Reduced torque
RA Automatic lining wear compensation
VD Descent valve
 Brake not fitted with the thruster



BRAKE TYPE	THRUSTOR VS	TORQUE N.m.		WEIGHT kg	DRUM SHOE WIDTH	DIMENSIONS																
		min.	max.			B1	D1	D3	H3	I	K	A1	A2	A3	A4	B	C	F	G	H1	H2	J
160	I-256	118	235	28	60	65	160	11	130	55	120	614	420	140	177	116	160	110	20	424	364	90
200	I-256	125	250	29	75	70	200	14	160	55	145	664	510	185	178	116	160	125	19	405	355	90
250	I-256	128	255	35	95	90	250	18	190	65	180	710	580	220	210	116	160	130	13	425	413	100
315	I-356	235	470	40								769								499		
	II-506	275	550	59								769	690	260	223	159	160			595		
	II-506	438	875	62	118	110	315	18	230	80	220	820	820				195	180	18	620	588	120
	II-806	700	1400	63								820					195			635		
400	II-506	450	900	85	150	140	400	22	280	100	270	980	990	800	310	307	159	195	210	710	704	150
	II-806	760	1520	87								980	990	800	310	307	159	195				
	III-1306	1350	2700	107								975					164	240		710	775	

For higher torque, please consult us. Some types may present little differences in the form with the drawing

DRUM BRAKE - FNS-VS 500 TO 710 BRAKES

Revision number: T03109-01-E


Revision date: 27.07.2016

Standard DIN 15435

Spring application
Thruster release
Protection level : C3M
Voltage : 230 / 400V 50 Hz
Other voltages, consult us.

AT High temperature
BT Low temperature
ATEX Certificat ATEX / Thrustor
BI Stainless steel bolts
CSA Opening proving switch
DD Lining wear indicators
DM Hand release lever

LM Locking lever to hold the brake open
PE Special paint : color / > C3M
PL Padlock for the locking lever
PR Reduced torque
RA Automatic lining wear compensation
VD Descent valve
Brake not fitted with the thruster



BRAKE TYPE	THRUSTOR VS	TORQUE N.m.		WEIGHT kg	DRUM WIDTH	SHOE WIDTH B1	DIMENSIONS															
		min.	max.				D1	D3	H3	I	K	A1	A2	A3	A4	B	C	F	G	H1	H2	J
500	II-806	800	1600	125	190	180	500	22	340	130	325	1039			312	195						
	III-1306	1325	2650	145			1060	940			325	190	240	250	23	820	803	180				
	III-2006	2125	4250	147			1060				325	240										
630	III-1306	1450	2900	240	236	225	630	27	420	170	400	1240			435							
	III-2006	2325	4650	242			1240	1150	460			435	230	240	305	23	955	940	220			
	III-3006	3725	7450	244			1240				435											
	III-3012	3875	7750	258			1325				427											
710	III-2006	2875	5750	323	265	255	710	27	470	190	450	1405			250	240	340	29	1085	1067	250	
	III-3006	4300	8600	324			1405	1280	510	470		250										
	III-3012	4950	9900	338			1570															

For higher torque, please consult us. Some types may present little differences in the form with the drawing

SIME Brakes Industrial Braking Systems

Service Brakes

APPLICATIONS

- | | |
|---|--|
| <ul style="list-style-type: none">• PORT CRANES• ALL HOISTING APPLICATIONS• TRAVELLING CONTROL• MASS TRANSPORT | <ul style="list-style-type: none">• STEEL CRANES :
CHARGING AND LADDLE CRANES
SLAG AND SCRAP CRANES• BELT CONVEYORS - MINES |
|---|--|



HYDRAULIC SERVICE BRAKES

MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none"> • FAILSAFE BRAKES • BRAKING BY HYDROSPRING® SYSTEM • INTEGRAL ELECTRICAL CONNECTIONS • INTEGRAL HYDRAULICAL CONNECTIONS • AUTOMATIC WEAR COMPENSATION 	<ul style="list-style-type: none"> • ADJUSTABLE DELAY OF BRAKE CLOSING • MARINE PROTECTION




2TB - 3TB - 4TB

- Association with discs Ø445 to 995
- Options:
 - Torque setting
 - Controlled braking torque /stepped braking torque
 - Protective cover

1TSA - 1TXA

- Association with discs Ø625 to 995
- Torque setting

Braking torque (kN.m)



SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - 1TSA AND 1TXA CALIPERS

Revision number: T03681-01-A

Revision date: 15.02.2007

Fail safe

Braking by HYDROSPRING® system
Electrico-hydraulically released
Integral hydraulic power unit
Self contained electrical system
Lining wear compensation
Opening proving switch
Torque setting

Operating conditions :


- Ambient temperature : -10° C to +50° C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

• 1TXA:

Mounting of 2 calipers per disc, consult us.

Options:

- Linings with wear detection
- Adjustable delay brake closing system from 0.25 to 20 sec.
- Switch for PLC
- Marine protection



Weight: 160 kg

Response time at nominal torque ≤ 0.25 sec.

Caliper inclination from horizontal ± 15° maxi.

Other inclination, consult us.

Disc	Ø mm	625		705		795		995	
		Thickness mm	30 42	30	30 42	42			
Nominal torque for 1 caliper	1TSA	N.m	7920	9180	10620	14040			
	1TXA	N.m	9780	11300	13100	17300			
Disc speed for the nominal torque *	r.p.m.	≤ 1500		≤ 1300		≤ 1200		≤ 900	
D	mm	625		705		795		995	
E	mm	185		225		265		365	
F	mm	125		165		205		305	
G	mm	315		330		345		380	
I	mm	180		225		265		370	
1TSA									
Ø d ₁ min. for: 1 caliper (1 key) ●	mm	97	97	100	111	111	130		
2 calipers (2 keys) ●	mm	--	120	--	--	135	170		
1TXA									
Ø d ₁ min. for: 1 caliper (1 key)	mm	104	104	111	125	125	145		
1 caliper (shrink fit)	mm	104	104	107	110	110	118		
Maximum reaction on shaft: 1TSA ■	N	32 400							
1TXA	N	40 000							

Electric data :

- 3 phases AC supply
- Voltages :
 - 230V / 400V ±10% 50Hz
 - 415V ±5% 50Hz
 - 460V ±5% 60Hz
- Maximum consumption: 775 W
- Electrical casing: IP 55
- DC supply, other voltages and conditions: consult us.
- Opening proving switch:
 - 240V, 3A, 10VA AC
 - 250V, 0.3A, 10W DC

* For higher speed, consult us.

● or shrink fit

■ Mounting with 2 calipers: multiply by 0.6

DISC BRAKE - 2TB, 3TB AND 4TB CALIPERS

Revision number: T03664-01-C

Revision date: 24.08.2012


Fail safe
Braking by HYDROSPRING® system
Electrico-hydraulically released
Integral hydraulic power unit
Self contained electrical system
Lining wear compensation
Opening proving switch

Operating conditions:

- Ambient temperature : -10°C to +50°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Options:

- Torque setting
- Detection of full lining wear
- Adjustable delay brake closing system from 0.25 to 20secs
- Controlled braking torque **
- Marine protection
- Protective cover K
- Stepped braking torque **
- Redundant circuit with 2 solenoid valves



Weight: 160 kg

Response time at nominal torque ≤ 0.25s
Permissible inclination of the caliper ± 45° maximum
Other mountings: consult us.

Discs		445	495	550	625	705	795	995	
Nominal torque for 1 caliper:	2TB	N.m	2800	3250	3700	4400	5100	5900	7800
	3TB	N.m	1550	1800	2050	2450	2850	3250	4300
	4TB	N.m	775	900	1030	1230	1430	1630	2150
Maximum disc speed for nominal torque *	rpm	2100	1900	1800	1500	1300	1200	900	
D	mm	445	495	550	625	705	795	995	
E	mm	100	120	150	185	225	265	365	
F	mm	40	60	90	125	165	205	305	
G	mm	285	295	305	315	330	345	380	
L	mm	90	130	145	180	225	265	370	
d1 min. keyed for 1 caliper (steel St 70):	2TB	mm	73	75	77	80	82	87	92
	3TB	mm	60	62	63	66	67	71	76
	4TB	mm	48	49	50	52	53	57	58
d1 min. keyed for 2 calipers (steel St 70):	2TB	mm	79	83	87	92	96	101	110
	3TB	mm	65	68	71	75	79	82	91
	4TB	mm	53	55	57	60	63	66	69
Maximum reaction on shaft ■:	2TB	N			18000				
	3TB	N			10000				
	4TB	N			5000				

■ Mounting with 2 calipers, multiply by 0.6

*For higher speeds, consult us.

** Increased dimensions, consult us.

Electric data:

- Power unit motor:
3 phases:
230/400 V ±10%, 50 Hz,
0.37 kW, 4 poles
for mains:
230/400 V 50 Hz
or 415 V 50 Hz
or 460 V 60 Hz
- Options motor:
400/690 V ±10% 50Hz
255/440 V ±10% 50Hz
290/500 V ±10% 50Hz
280/480 V ±10% 60Hz
330/575 V ±10% 60Hz
- Other voltages, consult us.
- Electrical casing IP55
- Opening switch:
240 V, 3 A, 10 VA AC
250 V, 0.3 A, 10 W DC

SIME Brakes Industrial Braking Systems

Service Brakes

APPLICATIONS

- PORT CRANES
- HOIST, GANTRY AND TROLLEY MOTIONS
- BELT CONVEYORS
- MINES
- IRON AND STEEL INDUSTRY
- LADLE CRANES



THRUSTOR SERVICE BRAKES

MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none"> • FAILSAFE BRAKES • SPRING APPLIED • ELECTROHYDRAULIC THRUSTOR RELEASED • ADJUSTABLE BRAKING TORQUE 	<ul style="list-style-type: none"> • LINING FULL WEAR CONTROL SWITCH • HIGH TEMPERATURE STEEL WORKS (SIDHT) • HIGH TEMPERATURE THRUSTOR (HT)




TDXB.I - TDXB.II

- Lining wear automatic compensation
- Self-centering
- Opening proximity switch
- Options:
Closing and thruster stroke proximity switches

FAV10 - FAV15 - FAV21 - FAV40 - FAV50

- Lining wear automatic compensation
- Auto centering
- Thruster stroke and opening proving switches
- Options: Monitoring module



SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - TDXB-I BRAKE

Revision number: T10121-01-F

Revision date: 11.03.2019

Fail safe
Spring application / Thrustor release
Self-centering
Automatic lining wear compensation
Opening sensor
Low maintenance Teflon bushes
Lining full wear indicators
Manual release lever
Lining pads with DIN shape / Thrustors **TS**

Operating conditions:


- Ambient temperature: -25°C to +50°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Use:

- Service brake

Options :

- Closing sensor
- Thrustor limit stroke sensor
- Thrustor **TS** with option :
 - SW**: Oil Shell HF-E-32 / High Temp. seals
 - SV**: Special Voltage
- Custom color
- Thrustor **VS**
- Inductive sensors DC-AC 24-240V 50/60 Hz



DISCS (ØD)		315	355	395	445	495	550	625	705	795
NOMINAL TORQUE. 1 caliper *	TDXB-I 1	N.m	901	996	1104	1267	1437	1619	1877	2148
	TDXB-I 2	N.m	1490	1646	1826	2094	2374	2677	3102	3550
	TDXB-I 3	N.m	2075	2293	2543	2917	3307	3728	4321	5647
MAXIMUM DISC SPEED for nominal torque **		rpm	3000	2700	2400	2100	1900	1800	1500	1350
Maximum linear speed		m/s					50			
F		mm	57	70	80	100	125	155	190	230
G		mm	56	59				70		
H		mm	28	30			35			
MAXIMUM REACTION ON SHAFT	TDXB-I 1	N				6776				
	TDXB-I 2	N				11200				
	TDXB-I 3	N				16000				

* Nominal torque is adjustable from 100% to 70%

** For higher speeds, consult Stromag France

DISC BRAKE - TDXB-II BRAKE

Revision number: T10122-01-F

Revision date: 19.04.2019

Fail safe
Spring application / Thrustor release
Self-centering
Automatic lining wear compensation
Opening sensor
Low maintenance Teflon bushes
Lining full wear indicators
Manual release lever
Thrusters **TS**

Operating conditions:


- Ambient temperature: -25°C to +50°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Use:

- Service brake

Options :

- Closing sensor
- Thruster limit stroke sensor
- Thruster **TS** with option :
 - SW**: Oil Shell HF-E-32 / High Temp. seals
 - SV**: Special Voltage
- Custom color
- Thruster **VS**
- Inductive sensors DC-AC 24-240V 50/60 Hz



DISCS (ØD)			445	495	550	625	705	795	995
NOMINAL TORQUE. 1 caliper *	TDXB-II 1	N.m	4288	4928	5632	6592	7616	8768	11328
	TDXB-II 2	N.m	6030	6930	7920	9270	10710	12330	15930
	TDXB-II 3	N.m	8040	9240	10560	12360	14280	16440	21240
MAXIMUM DISC SPEED for nominal torque **		rpm	2100	1930	1740	1530	1354	1200	960
Maximum linear speed		m/s				50			
F		mm	93	118	145	183	255	268	368
		mm				D/2-129.5			
MAXIMUM REACTION ON SHAFT	TDXB-II 1	N			25600				
	TDXB-II 2	N			36000				
	TDXB-II 3	N			48000				

* Nominal torque is adjustable from 100% to 70%

** For higher speeds, consult Stromag France

SIME Brakes Industrial Braking Systems

Service Brakes

DISC BRAKE - FAV10-FAV15 BRAKES

Revision number: T10022-01-I

Revision date: 23.05.2013

Fail safe

Spring application / Thrustor release

Manual centering

Lining wear compensation

Linings with wear indicator wires

Thrustor stroke control switch

Opening proving switch

Stainless steel pins

Manual release lever

Protection class C5 standard ISO12944-2

Operating conditions:



- Ambient temperature: -20°C to +50°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Use:

- Service brake

Options :

- SIDHT : Steel works High Temperature
- HT : High Temperature Thrustor
- Thruster :
- VS-I-256 or Ed23/5 - 230/400V (FAV10)
- VS-I-356 or Ed80/5 - 230/400V (FAV15)




Weight without thrustor: 27 kg

Weight with thrustor : FAV10 : 40 kg. FAV15 : 44 kg

Torque and effort values are subject to a variation of ±10%

FAV10 and FAV15 calipers are associated with linings type WS1-5.

Discs (ØD)		220	260	315	355	395	445	495	550
Nominal torque. 1 caliper *	FAV10 N.m.	221	275	349	403	457	525	592	661
	FAV15 N.m.	265	330	410	485	550	630	710	795
Maximum disc speed for nominal torque **	rpm	4300	3600	3000	2700	2400	2100	1900	1800
F	mm	47	66	93	113	135	160	185	213
Maximum reaction on shaft	FAV10 N	2700							
	FAV15 N	3200							



* Braking torque is adjustable from 100% to 70% of nominal torque, friction factor $\mu = 0.37$

** For higher speeds, consult Stromag France

DISC BRAKE - FAV21-VS BRAKE

Revision number: T10044-02-F

Revision date: 20.12.2019

Fail safe
Spring application / Thrustor release
Auto centering
Lining wear compensation
Thrustor stroke control switch
Opening proving switch
Manual release lever
Stainless steel pins

Operating conditions:


- Ambient temperature: -20°C to +50°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us

Use:

- Service brake

Options :

- Lining full wear control switch
- MSF : Monitoring modul for FAV
- SIDHT : High Temperature Steel works
- HT : High Temperature Thrustor
- Thrustors Ed50/6 - Ed80/6




Weight with thrustor and lining pads : 130 kg
Torque and effort values are subject to a variation of ±10%
Lining quality **WS1-5** in standard.

Discs (ØD)	355	395	445	495	550	625	705
Nominal torque *.	N.m.	-	-	2260	2590	2990	3450
1 caliper	FAV213 VS II 1306	1300	1500	1700	1950	2250	-
	FAV212 VS II 806	700	750	900	1000	1150	1350
	FAV211 VS II 506						-
Max. disc speed for nominal torque **	rpm	2700	2400	2100	1900	1800	1500
F	mm	122	142	118	143	170	208
F	(D/2-56)						248
G	mm	67			136		
H	mm	32			57		
Maximum reaction on shaft	FAV213 VS II 1306	N	-		13600		
	FAV212 VS II 806	N	9100		10200		-
	FAV211 VS II 506	N	4500		5300		-

* Nominal torque is adjustable from 100% to 70%

** For higher speeds, consult Stromag France



Service Brakes

DISC BRAKE - FAV41-VS BRAKE

Revision number: T03524-02-D

Revision date: 08.11.2017

Fail safe
 Spring application / Thrustor release
 Auto centering
 Lining wear compensation
 Thrustor stroke control switch
 Opening proving switch
 Stainless steel pins
 Manual release lever for FAV411/412-VS
 Manual release system for FAV413-VS

Operating conditions:


- Ambient temperature: -20°C to +50°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us

Use:

- Service brake

Options :

- Lining full wear control switch
- MSF : Monitoring modul for FAV
- SIDHT : High Temperature Steel works
- HT : High Temperature Thrustor
- Thrusters : Ed301/10 - Ed201/10 - Ed121/10



Weight without thrustor : 180 kg / Weight with thrustor : 222 kg

Torque and effort values are subject to a variation of ±10%


The disc run-out must not exceed 0.08 % of the maximum radius and the disc axial displacement must be smaller than 0.5 mm.

Lining quality **WS1-5** in standard.

Discs (ØD)	445	495	550	625	705	795	995
Nominal torque. FAV413 VS-III-3010	-	-	-	9700	11200	12950	16700
1 caliper *	-	4960	5650	6600	7650	8800	-
(N.m)	2650	3050	3500	4100	4750	5450	-
Maximum disc speed for nominal torque (rpm) **	2100	1900	1800	1500	1300	1200	900
F (mm) (F=D/2-130)	93	118	145	183	223	268	368
Maximum reaction on shaft (N)	FAV413 VS-III-3010	38000					
	FAV412 VS-III-2010	26000					
	FAV411 VS-III-1310	16000					

* Nominal torque is adjustable from 100% to 70%

** For higher speeds, consult Stromag France



DISC BRAKE - FAV50 / FAV50-VS BRAKES

Revision number: T03525-01-D / T03525-02-E

Revision date: 08.11.2017 / 08.11.2017

Fail safe
Spring application / Thrustor release
Auto centering
Lining wear compensation
Thrustor stroke control switch
Opening proving switch
Stainless steel pins
Manual release system

Operating conditions:

- Ambient temperature: -20°C to +50°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Use:


- Service brake

Options :

- Lining full wear control switch
- MSF : Monitoring modul for FAV
- SIDHT : High Temperature Steel works
- HT : High Temperature Thrustor

FAV50 : Thrustor Ed-301/100

FAV50-VS : Thrustor VS-III-3010



Weight without thrustor: 180 kg

Weight with thrustor of **FAV503** : 220 kg. **FAV503-VS** : 224 kg.

Torque and effort values are subject to a variation of ±10%

Lining quality **WS1-5** in standard.

Discs (ØD)	625	705	795	995
Nominal torque.				
1 caliper * FAV503 / FAV503-VS	12360	14270	16500	21270
Maximum disc speed for nominal torque (rpm) **	1500	1300	1200	900
F (mm) (F=D/2-130)	183	223	268	368
Maximum reaction on shaft (N)	FAV503 / FAV503-VS			48 400


* Nominal torque is adjustable from 100% to 70%

** For higher speeds, consult Stromag France

SIME Brakes Industrial Braking Systems



Emergency Brakes

EMERGENCY BRAKES




SIME Brakes Industrial Braking Systems

Emergency Brakes



A COMPLETE BRAKING SOLUTION



SIME Brakes Industrial Braking Systems

Emergency Brakes

APPLICATIONS

- STEEL INDUSTRY
- NUCLEAR PLANTS



ELECTROMAGNETIC EMERGENCY BRAKES

MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none">• FAILSAFE BRAKE BY SPRING APPLICATION• ELECTROMAGNETIC RELEASE• MANUAL LINING WEAR COMPENSATION• OPENING PROVING SWITCH• DETECTION OF FULL LINING WEAR	<ul style="list-style-type: none">• LOAD REGULATED LOWERING



2SA

Air gap switch




OSA

- Option :
 - Manual release lever
 - Hydraulic release
 - Mounting on a vertical axis disc
 - Flameproof / Marine protection...



OOSA

- Option :
 - Manual release lever
 - Hydraulic release
 - Flameproof protection
 - Marine protection



SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - OSA CALIPER

Revision number: T03750-01-F

Revision date: 22.03.2016

Fail safe braking
Braking by spring application
Electromagnetic release
Manual lining wear compensation
Detection of full lining wear
Opening proving switch

Operating conditions:



- Ambiant temperature: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:


The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains.

Options:

- Manual release lever
- Hydraulic release
- Load regulated lowering
- Flameproof protection
- Marine protection
- Mounting on a vertical axis disc




Sole plate location - top view



C = Cable gland PG16
OS = Opening switch, cable gland PG16

Weight: 200 kg
Dimensions in mm

Support and disc installation



Response time at nominal torque :
see the leaflet of the associated electrical power supply.
Force values are subject to a variation of ±10%.

Designation	Caliper		OSA
	Lining *	US2-1	US2-1
Braking force BF	Static N	27 900	
	Dynamic N	31 000	
Linear speed of the disc	m/s		≤ 10
Dynamic braking torque	1000 mm N.m	13 400	
BT (N.m) for 1 caliper	1200 mm N.m	16 500	
and disc ØD (mm)	1500 mm N.m	21 100	
	2000 mm N.m	28 900	
BT for other ØD (mm)	N.m		BT = BF (D/2000 - 0.068)
F	mm		F = (0.4475 × ØD) - 150
G	mm		G = 196 + (0.2231 × ØD)

Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity : 50VA maxi
220VDC maxi., 5A maxi., with interrupting capacity : 50W maxi
Compatible with PLC (Programmable Logic Controllers).
An opening switch used with other equipment than PLC must not be reused with a PLC.

* **US2-1**: disc temperature during one braking ≤ 150°C
US2-5: disc temperature during one braking ≤ 350°C.
optional. consult us.

DISC BRAKE - OOSA CALIPER

Revision number: T03770-01-E

Revision date: 22.03.2016

Fail safe braking
Braking by spring application
Electromagnetic release
Manual lining wear compensation
Detection of full lining wear
Opening proving switch

Operating conditions:


- Ambiant temperature: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:

The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains.

Options:

- Manual release lever
- Hydraulic release
- Load regulated lowering
- Flameproof protection
- Marine protection



Response time at nominal torque :
see the leaflet of the associated electrical power supply.
Force values are subject to a variation of ±10%.

Designation	Caliper		OOSA
	Lining *		US2-1
Braking force BF	Static N		54 000
	Dynamic N		60 000
Linear speed of the disc	m/s		≤ 10
Dynamic braking torque	1000 mm N.m		25 900
BT (N.m) for 1 caliper and 1 disc ØD (mm)	1200 mm N.m		31 900
	1500 mm N.m		40 900
	2000 mm N.m		55 900
BT for other ØD (mm)	N.m	BT = BF (D/2000 - 0.068)	
F	mm	F = (0.4475 × ØD) - 150	
G	mm	G = 196 + (0.2231 × ØD)	

Opening proving switch :

250VAC maxi., 5A maxi., with interrupting capacity : 50VA maxi
220VDC maxi., 5A maxi., with interrupting capacity : 50W maxi
Compatible with PLC (Programmable Logic Controllers).
An opening switch used with other equipment than PLC must not be reused with a PLC.

* **US2-1:** disc temperature during one braking ≤ 150°C
US2-5: disc temperature during one braking ≤ 350°C.
optional. consult us.

NOTES

DISC BRAKE - 2SA CALIPER

Revision number: T03781-01-D

Revision date: 22.03.2016

Fail safe braking
Braking by spring application
Electromagnetic release
Manual lining wear compensation
Opening proving switch
Air gap switch

Operating conditions:


- Ambiant temperature: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:

The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains.

Options:

- Detection of full lining wear
- Load regulated lowering



Torque and force values are subject to a variation of ±10%

Response time at nominal torque :

see the leaflet of the associated electrical power supply.

• Opening proving switch:

250VAC maxi., 5A maxi., with interrupting capacity : 50VA maxi
220VDC maxi., 5A maxi., with interrupting capacity : 50W maxi
Compatible with PLC (Programmable Logic Controllers).

An opening switch used with other equipment than PLC must not be reused with a PLC.

• Air gap switch:

240V. 3A AC
250V. 0.27A DC

* US2-1: disc temperature during one braking ≤ 150°C

US2-5: tdisc temperature during one braking ≤ 350°C


SIME Brakes Industrial Braking Systems

Emergency Brakes

APPLICATIONS

- STEEL CRANES
- PORT CRANES
- NUCLEAR CRANES

- OFFSHORE APPLICATIONS
- BOATLIFTS
- MINES AND CONVEYORS



HYDRAULIC EMERGENCY BRAKES TYPE SH

MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none"> • FAILSAFE BRAKE BY SPRING APPLICATION • HYDRAULIC RELEASE • OPENING PROVING SWITCH • LINING WEAR INDICATORS 	<ul style="list-style-type: none"> • LINING WEAR PROVING SWITCH • PROGRESSIVE BRAKING SYSTEM • OFFSHORE PROTECTION • LINING TEMPERATURE SENSOR • HIGH TEMPERATURE, IRON AND STEEL CONDITIONS



SH

- Association with disc thicknesses : depending on the type of caliper : 12.7 - 15 - 20 - 30 or 42 mm.


SHS

- Caliper mounted on a support
- Tailor-made solutions for any installation : banana supports

SHC

- Caliper and Hydraulic Power Pack mounted on the same support
- Option: Electrical unit

Braking torque (kN.m)



SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SH1 CALIPER

Revision number: T10097-01-H

Revision date: 07.06.2019

Emergency brake
Fail to safe
Spring application
Hydraulic release
Linings with wear indicators
Holding tool for maintenance operation
Manual wear centering and compensation
Association with discs thickness:
12.7 (1/2"), 15, 20 and 30mm.
Lining pads type **US2-1** or **ES3-7**
Lining pads with full wear indicators
Protection C5-M M

Operating conditions:


- Ambient temperature:
Dynamic braking : -30°C to +70°C
Brake applied (parking): -40°C to +70°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µm
- Other conditions: consult us.

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains.
- Other use, consult us.

Options:

- Opening proving switch (**OS**)
- Lining wear proving switch (**WS**)
- All non-standard disc thickness > 12.7mm (1/2")
- Lining temperature sensor (**T**)
- Mechanical release tool (**DM**)
- **SH1** : caliper requiring no manual wear compensation:
 - braking force before lining wear = +10% maxi.
 - braking force after lining wear = -10% maxi.



Electrical data:

Inductive switches of opening and wear (options):
3 wires PNP NO
12 to 24 VDC 200mA
with male connector M12 / 5 positions
according to standard IEC61076-2-101 / code A

Sensor PT100 (option)
Detection of the temperature threshold : 100°C ± 5
Cable length = 2.5 meters
2 wires red/yellow

R	136.6 Ω	95°C
	138.5 Ω	100°C
	140.4 Ω	105°C

C = Spacers according to disc thickness

G = Linings : Thickness of new lining 8 mm
Thickness to wear 6 mm

Each 1mm of wear on each side: manual centering and compensation

OS = Opening switch (option)

WS = Lining wear switch (option)

P = 2 oil ports 1/4"G per half-caliper
Bleeder screws delivered separately

T = PT100 sensors (option)

ØD = Disc diameter = 300 mm minimum



e = Disc thickness

DISC BRAKE - SH1 CALIPER

Revision number: T10097-01-H

Revision date: 07.06.2019

Disc and support :



Torque and effort values are subject to a variation of ±10% - Closing time at nominal torque ≤ 0.3s

Designation	Caliper SH1-		5	4	3	2	1	5	4	3	2	1		
	Lining *		US2-1						ES3-7					
Braking force BF for air gap disc/lining of 2x1mm	Dynamic	N	11 000	8 000	6 000	4 000	3 000	11 000	8 000	6 000	4 000	2 000		
	Static	N	9 680	7 040	5 280	3 520	2 640	9 900	7 200	5 400	3 600	1 800		
Linear speed of the disc ●	m/s		≤ 10						≤ 50					
Dynamic braking torque BT (m.N) for 1 caliper and disc ØD (mm) / 300 ≤ D ≤ 1000 mm	N.m		BT = BF (D/2000-0.037)											
Regulation pressure	Minimum Maximum	bar bar												
Setting pressure limit valve of hydraulic unit	bar													
Total volume of oil displaced for air gap disc/lining of:	2 x 1mm (nominal opening) 2 x 3mm (wear+opening) 2 x 7mm SH1 (wear+open.)	cm ³												

* **ES3-7:** disc temperature during one braking ≤ 600°C

US2-1: disc temperature during one braking ≤ 100°C

● For higher speed, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHS1 AND SHC1 CALIPERS

Revision number: T10099-01-F

Revision date: 10.06.2016

Emergency brake
Fail to safe
Spring application
Hydraulic release
Holding tool for maintenance operation
Manual wear centering and compensation
Possible association possible with discs thickness:
12.7 to 30 mm.
Lining pads type **US2-1** or **ES3-7**
Lining pads with full wear indicators
Protection : Caliper **SHS1** : C5-M M
HPP **CE1L** : C4 M

Operating conditions:

- Ambient temperature:
Caliper **SHS1**:
Dynamic braking : -30°C to +70°C
Brake applied (parking): -40°C to +70°C
HPP **CE1L** : -20°C to +70°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µm
- Other conditions: consult us.

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains.
- Other use, consult us.

Options:

- Opening proving switch (**OS**)
- Lining wear proving switch (**WS**)
- Lining temperature sensor (**T**)
- SHS1L - SHC1L** : caliper with no need of manual wear compensation:
 - braking force before lining wear = +10% maxi.
 - braking force after lining wear = -10% maxi.
- CE1L** HPP options : see "Installation and maintenance" leaflet quoted below.

SHS1 = SH1 caliper with integral support

SHC1 = SH1 caliper with integral **CE1L** hydraulic power pack.

L = Linings :

Thickness of new lining 8 mm
Thickness to wear 6 mm
Each 1 mm of wear on each side:
manual centering and compensation

OS = Opening proving switch (option)

WS = Wear proving switch (option)

P = Oil ports 1/4"G

Bleeder screws delivered separately


T = PT100 sensors (option)

ØD : from 300 to 1000 mm



e = disc thickness

Dimensions in mm

Weight : **SHC1** = 61 kg **SHC1L** = 68 kg
SHS1 = 39 kg **SHS1L** = 46 kg



Dimension with all options CE1L



Necessary overall dimension


Calipers fastening :
4 bolts M12 class 10-9 (not provided)
Tightening torque = 77 Nm ± 30%

DISC BRAKE - SHS1 AND SHC1 CALIPERS

Revision number: T10099-01-F

Revision date: 10.06.2016

Installation instructions :



Electrical data:

Opening and wear inductive switches (options)

3 wires PNP NO
12 to 24 VDC 200mA
with connector M12 / 5 positions
according to standard IEC61076-2-101 / code A

Sensor PT100 (option)

Detection of the temperature threshold : 100°C ± 5
- R = 136.6 Ω at 95 °C
- R = 138.5 Ω at 100°C
- R = 140.4 Ω at 105°C
Cable length = 2.5 meters
2 wires red/yellow

Torque and effort values are subject to a variation of ±10% - Closing time at nominal torque ≤ 0.3s

Designation	Caliper SHS1-SHC1-		5	4	3	2	1	5	4	3	2	1						
	Lining *		US2-1						ES3-7									
Braking force BF for air gap disc/lining of 2x1mm	Dynamic	N	11 000	8 000	6 000	4 000	3 000	11 000	8 000	6 000	4 000	2 000						
	Static	N	9 680	7 040	5 280	3 520	2 640	9 900	7 200	5 400	3 600	1 800						
Linear speed of the disc ●	m/s		≤ 10				≤ 50											
Dynamic braking torque BT (m.N) for 1 caliper and disc ØD (mm) 300 ≤ D ≤ 1000 mm	N.m		$BT = BF (D/2000 - 0.037)$															
Regulation pressure	Minimum	bar	150															
Maximum	bar		170															
Setting pressure limit valve of HPP	bar		190															
F			$F = (0.483 \times D) - 14$															
G			$G = (0.129 \times D) + 118$															

* **ES3-7:** disc temperature during one braking ≤ 600°C

US2-1: disc temperature during one braking ≤ 100°C

● For higher speed, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SH5 CALIPER

Revision number: T03865-02-C

Revision date: 23.09.2010

Emergency brake
Fail safe
Spring application
Hydraulic release
Opening proving switches
Lining wear detector

Operating conditions :


- Ambient temperature: -10°C to +60°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Use :

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.

Options :

- Automatic lining wear compensation (WACS)
- Lining wear control switch
- Progressive braking system
- Marine protection
- Caliper on support with integral hydraulic power unit



Opening proving switch :

250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.

220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.


Compatible with PLC
(Programmable Logic Controllers).
An opening switch used with other equipment than PLC must
not be reused with a PLC.

DISC BRAKE - SH5 CALIPER

Revision number: T03865-02-C

Revision date: 23.09.2010


Disc and support :



Standard disc thickness: $30 \leq e \leq 50$ mm.
Other thickness, consult us. Dimensions in millimetre

Dimension at the closest point (perpendicular on the radius)

The support F face must be rectilinear on this length



Torque and effort values are subject to a variation of $\pm 10\%$

Response time at nominal torque : see the leaflet n° G08555-01

Désignation	caliper		SH5-6		SH5-5		SH5-4		SH5-3		SH5-2	
	Lining *		US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3
Braking force BF for 1mm of air gap disc/lining	Static N	63 000	43 200	51 300	35 100	37 800	25 900	21 200	14 500	9 600	6 500	
	Dynamic N	70 000	48 000	57 000	39 100	42 000	28 800	23 600	16 200	10 700	7 300	
Linear speed of the disc	m/s	≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 10	≤ 50
Dynamic braking torque BT (N.m) for 1 caliper and disc ØD (mm)	995 mm N.m 1200 mm N.m 1500 mm N.m 2000 mm N.m	29430 36610 47110 64610	20 180 25 100 32 300 44 300	23 960 29 810 38 360 52 610	16 440 20 440 26 310 36 080	17 660 21 960 28 260 38 760	12 110 15 060 19 380 26 580	9 920 12 340 15 880 21 780	6 810 8 470 10 900 14 950	4 490 5 590 7 200 9 870	3 070 3 810 4 910 6 730	
BT for other ØD (mm)	N.m	BT = BF (D/2000 - 0.077)										
Regulation pressure	minimum bar maximum bar	180 200		140 160		110 140		85 115		40 60		
Setting pressure of the limit valve of hydraulic power unit	bar	210		190		165		140		80		
Total volume of oil displaced	cm³	35 for one stroke disc/lining (nominal wear and opening)										

* US2-1: disc temperature during one braking $\leq 150^{\circ}\text{C}$

WS1-3: disc temperature during one braking $\leq 600^{\circ}\text{C}$

US2-5: disc temperature during one braking $\leq 350^{\circ}\text{C}$, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHC5 CALIPER

Revision number: T03867-02-D

Revision date: 26.10.2011

Emergency brake
Fail to safe
Spring application
Hydraulic release
Integral hydraulic power unit
Self contained electrical system
Opening proving switches
Lining wear detector

Operating conditions:



- Ambient temperature: -10°C to +50°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µ
- Other conditions: consult Stromag France.

Options:

- Automatic lining wear compensation (WACS)
- Lining wear control switch
- Progressive braking system
- Marine protection

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.




Dimensions in mm
Weight: 185 kg

DISC BRAKE - SHC5 CALIPER

Revision number: T03867-02-D

Revision date: 26.10.2011

Installation instructions



Electrical data

- Motor voltages :**
3 phases : 230/400 VAC 50 Hz
0.37 kW. 4 poles
for mains:
220-230-240VAC ±10% 50Hz
or 380-400-415VAC ±10% 50Hz
- Options motor :**
440 VAC 50Hz
500 VAC 50Hz
480 VAC 60Hz
575 VAC 60Hz
- Other voltages. consult us.
- Electrical casing IP55
- **Opening switch :**
250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.
Compatible with PLC
(Programmable Logic Controllers).
An opening switch used with other equipment
than PLC must not be reused with a PLC.

Torque and effort values are subject to a variation of ±10%
Response time at nominal torque : see the leaflet n° G08555-01.

Désignation	caliper		SHC5-6		SHC5-5		SHC5-4		SHC5-3		SHC5-2	
	Lining *		US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3
Braking force BF for 1mm of air gap disc/lining	Static	N	63 000	43 200	51 300	35 100	37 800	25 900	21 200	14 500	9 600	6 500
	Dynamic	N	70 000	48 000	57 000	39 100	42 000	28 800	23 600	16 200	10 700	7 300
Linear speed of the disc	m/s		≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 50
Dynamic braking torque BT (N.m) for 1 caliper and disc ØD (mm)	995 mm 1200 mm 1500 mm 2000 mm	N.m N.m N.m N.m	29430 36610 47110 64610	20 180 25 100 32 300 44 300	23 960 29 810 38 360 52 610	16 440 20 440 26 310 36 080	17 660 21 960 28 260 38 760	12 110 15 060 19 380 26 580	9 920 12 340 15 880 21 780	6 810 8 470 10 900 14 950	4 490 5 590 7 200 9 870	3 070 3 810 4 910 6 730
BT for other ØD (mm)	N.m		BT = BF (D/2000 - 0.077)									
Setting pressure of the limit valve of hydraulic power unit	bar		210		190		165		140		80	
F G L	mm mm mm		F = (0.4719 x D) - 122.5 G = (0.1652 x D) + 232.5 L = (D / 2) - 181									

* **US2-1:** disc temperature during one braking ≤ 150°C

WS1-3: disc temperature during one braking ≤ 600°C

US2-5: disc temperature during one braking ≤ 350°C, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SH9A CALIPER

Revision number: T10077-01-B

Revision date: 30.05.2013

Emergency brake
Fail safe
Spring application
Hydraulic release
Opening proving switches.

Operating conditions:

- Ambient temperature: -10°C to +60°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µ
- Other conditions: consult us.


- US2-1, US2-5 for low energy braking ≤ 1 MJ
 - EF3-1 for high energy braking ≤ 15 MJ
- Other use. consult us

Options:

- Lining wear control switch
- Switch for P.L.C. (induction sensor)
- Marine protection
- Caliper on support with integral HPP
- Option GF

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.



Opening proving switch:



240V 1.5A AC
250V 0.1A DC
with a 5 x 0.75mm² wire
of 5m length

DISC BRAKE - SH9A CALIPER

Revision number: T10077-01-B

Revision date: 30.05.2013

Disc and support :



Torque and effort values are subject to a variation of $\pm 10\%$

Response time at nominal torque ≤ 0.3 s

Designation	Caliper	SH9A-3			SH9A-2			SH9A-1			
		Lining *	US2-1	US2-5	EF3-1	US2-1	US2-5	EF3-1	US2-1	US2-5	EF3-1
Braking force BF for 1mm air gap	Static N	94 500	90 000	70 500	80 100	76 200	60000	66 150	63 000	49 600	
	Dynamic N	105 000	100 000	78 200	89 000	84 700	66 500	73 500	70 000	55 000	
Linear speed of the disc for BF	m/s		≤ 10	≤ 30	$\leq 50 \bullet$	≤ 10	≤ 30	$\leq 50 \bullet$	≤ 10	≤ 30	$\leq 50 \bullet$
Dynamic braking torque BT (N.m) for 1 caliper and disc ΘD (mm) **	995 mm	N.m	44 150	42 050	32 880	37 420	35 620	27 960	30 910	29 440	23 130
	1500 mm	N.m	70 670	67 300	52 630	59 900	57 000	44 750	49 470	47 110	37 020
	2000 mm	N.m	96 920	92 300	72 180	82 150	78 180	61 380	67 840	64 610	50 770
BT for other ΘD (mm)	N.m		BT = BF (D/2000 - 0.077)								
Regulation pressure	Minimum bar	180		150		110		140			
	Maximum bar	200		180		110		140			
Setting pressure of HPP limit valve	bar	225		210		165					
Total volume of oil displaced	cm ³	55 for one disc/linings stroke (nominal wear and opening)									

* US2-1: disc temperature during one braking $\leq 150^\circ\text{C}$

US2-5: disc temperature during one braking $\leq 350^\circ\text{C}$

EF3-1: High energy braking, disc temperature during one braking $\leq 600^\circ\text{C}$

** For disc $\Theta D < 995$ mm, consult us.

● For higher speed, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHC9A CALIPER

Revision number: T10078-01-B

Revision date: 13.06.2014

Emergency brake
Fail to safe
Spring application
Hydraulic release
Integral hydraulic power unit
Self contained electrical system
Opening proving switches
Protection class C3L standard ISO12944-2

Operating conditions:


- Ambient temperature: -10°C to +60°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Options:

- Lining wear control switch
- Switch for P.L.C.
- Protection class C4M standard ISO12944-2

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains.
 - US2-1, US2-5 for low energy braking ≤ 1 MJ
 - EF3-1 for high energy braking ≤ 15 MJ
- Other use, consult us




Dimensions in mm
Weight: 230 kg

DISC BRAKE - SHC9A CALIPER

Revision number: T10078-01-B

Revision date: 13.06.2014

Installation instructions



Electrical data

- Motor voltages:
3 phases:
230/400 V ±10%. 50 Hz
0.37 kW
for voltage of 3 phases mains:
230 V 50 Hz
or 400 V 50 Hz
or 415 V 50 Hz
or 440 V 60 Hz
or 460 V 60 Hz
- Options voltage of 3 phases mains:
440 V ±10% 50Hz
500 V ±10% 50Hz
480 V ±10% 60Hz
- Other voltages, consult us.
- Electrical casing IP55
- Opening switch:
240V. 1.5A AC
220V. 0.1A DC
with cable 5 x 0.75mm² length 5m

Torque and effort values are subject to a variation of ±10%
Closing time at nominal torque ≤ 0.3s

Designation	Caliper		SHC9A-3			SHC9A-2			SHC9A-1						
	Lining *		US2-1	US2-5	EF3-1	US2-1	US2-5	EF3-1	US2-1	US2-5	EF3-1				
Braking force BF for 1mm air gap	Static N	94 500	90 000	70 500	80 100	76 200	60 000	66 150	63 000	49 600					
	Dynamic N	105 000	100 000	78 200	89 000	84 700	66 500	73 500	70 000	55 000					
Linear speed of the disc for BF	m/s	≤10	≤30	≤ 50●	≤10	≤30	≤ 50●	≤10	≤30	≤ 50●					
Dynamic braking torque BT (N.m) for 1 caliper and disc ØD (mm) **	995 mm N.m	44 150	42 050	32 880	37 420	35 620	27 960	30 910	29 440	23 130					
	1500 mm N.m	70 670	67 300	52 630	59 900	57 000	44 750	49 470	47 110	37 020					
	2000 mm N.m	96 920	92 300	72 180	82 150	78 180	61 380	67 840	64 610	50 770					
BT for other ØD (mm)	N.m	BT = BF (D/2000 - 0.077)													
Regulation pressure	Minimum bar	180		150		110		140							
	Maximum bar	200		180											
Setting pressure of limit valve of hydraulic power unit	bar	225			210			165							
F G L	mm mm mm	F = (0.4719 x D) - 113 G = (0.1652 x D) + 236.7 L = (D / 2) - 190													

* US2-1: disc temperature during one braking ≤ 150°C

US2-5: disc temperature during one braking ≤ 350°C

EF3-1: High energy braking, disc temperature during one braking ≤ 600°C

** For disc ØD < 995 mm, consult us

● For higher speed, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SH15 CALIPER

Revision number: T03905-01-B

Revision date: 01.10.2010

Emergency brake
Fail safe
Spring application
Hydraulic release
Opening proving switches
Lining wear detector

Operating conditions:


- Ambient temperature: -10°C to +60°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Options:

- Lining wear control switch
- Progressive braking system
- Marine protection
- Caliper on support with integral hydraulic power pack

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains, Other use. consult us.



Dimensions in mm
Weight: 250kg

Opening proving switch :

250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.


220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.

Compatible with PLC
(Programmable Logic Controllers).
An opening switch used with other equipment than PLC must
not be reused with a PLC.

DISC BRAKE - SH15 CALIPER

Revision number: T03905-01-B

Revision date: 01.10.2010



Torque and effort values are subject to a variation of $\pm 10\%$

Response time at nominal torque : see the leaflet n° G08555-01

Designation	Caliper		SH15-3		SH15-2		SH15-1	
	Lining *		US2-1	US2-4	US2-1	US2-4	US2-1	US2-4
Braking force BF for 1mm of air gap disc/lining	Static	N	133 000	99 000	110 000	80 000	90 000	66 000
	Dynamic	N	150 000	110 000	120 000	88 000	100 000	73 000
Linear speed of the disc	m/s		≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 50
Dynamic braking torque BT (N.m) for 1 caliper and disc $\varnothing D$	1000 mm	N.m	61 500	45 100	49 200	36 080	41000	29930
	1200 mm	N.m	76 500	56 100	62 200	44 880	51 000	37 230
	1500 mm	N.m	99 000	72 600	79 200	58 080	66 000	48 180
	2000 mm	N.m	136 500	100 100	109 200	80 080	91 000	66 430
BT for other $\varnothing D$ (mm)	N.m		$BT = BF(D/2000 - 0.09)$					
Regulation pressure	minimum	bar	150		140		110	
	maximum	bar	180		160		140	
Setting pressure of limit valve of the hydraulic unit	bar		205		205		165	
Total volume of oil displaced	cm^3		85 for one stroke disc/lining (nominal wear and opening)					

* **US2-1**: disc temperature during one braking $\leq 150^\circ\text{C}$

US2-4 : disc temperature during one braking $\leq 600^\circ\text{C}$

US2-5: disc temperature during one braking $\leq 350^\circ\text{C}$, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHC15 CALIPER

Revision number: T03906-03-C

Revision date: 29.08.2018

Emergency brake
Fail safe
Spring application
Hydraulic release
Integral hydraulic power pack
Opening proving switches
Lining wear detector

Operating conditions:


- Ambient temperature: -10°C to +60°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Options:

- Lining wear control switch
- Progressive braking system
- Marine protection
- Self contained electric system

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.




Dimensions in mm
Weight: 435kg

DISC BRAKE - SHC15 CALIPER

Revision number: T03906-03-C

Revision date: 29.08.2018

Installation instructions



Electrical data

- Motor voltages :

3 phases : 230/400VAC ±10% 50Hz
2.2kW, 4 poles

- Options motor :

690VAC ±10% 50Hz
500VAC ±10% 50Hz
230/400VAC ±10% 50Hz with PTC sensor
Other voltage, consult us.

- Opening switch :

250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.

Compatible with PLC
(Programmable Logic Controllers).
An opening switch used with other equipment
than PLC must not be reused with a PLC.

Torque and effort values are subject to a variation of ±10%
Response time at nominal torque : see the leaflet n° G08555-01.

Designation	Caliper		SHC15-3		SHC15-2		SHC15-1	
	Lining *		US2-1	US2-4	US2-1	US2-4	US2-1	US2-4
Braking force BF for 1mm of air gap disc/lining	Static N	133 000	99 000	110 000	80 000	90 000	66 000	
	Dynamic N	150 000	110 000	120 000	88 000	100 000	73 000	
Linear speed of the disc	m/s		≤ 10	≤ 50	≤ 10	≤ 50	≤ 10	≤ 50
Dynamic braking torque BT (N.m) for 1 caliper and disc ØD	1000 mm 1200 mm 1500 mm 2000 mm	N.m N.m N.m N.m	61 500 76 500 99 000 136 500	45 100 56 100 72 600 100 100	49 200 62 200 79 200 109 200	36 080 44 880 58 080 80 080	41 000 51 000 66 000 91 000	29 930 37 230 48 180 66 430
BT for other ØD (mm)	N.m		BT = BF (D/2000 - 0.09)					
F G	mm mm		F = (0.433 x D) -154.2 G = (0.250 x D) + 286.2					
Setting pressure of limit valve of the hydraulic unit	bar		205		205		165	

* **US2-1:** disc temperature during one braking ≤ 150°C

US2-4 : disc temperature during one braking ≤ 600°C

US2-5: disc temperature during one braking ≤ 350°C, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SH18B CALIPER

Revision number: T03907-01-B

Revision date: 08.10.2010

Emergency brake
Fail safe
Spring application
Hydraulic release
Opening proving switches
Lining wear detector

Operating conditions:


- Ambient temperature: -10°C to +60°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Options:

- Lining wear control switch
- Progressive braking system
- Marine protection
- Caliper on support with integral hydraulic power pack

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.



Dimensions in mm
Weight: 270kg

Opening proving switch :

250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.


220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.

Compatible with PLC
(Programmable Logic Controllers).
An opening switch used with other equipment
than PLC must not be reused with a PLC.

DISC BRAKE - SH18B CALIPER

Revision number: T03907-01-B

Revision date: 08.10.2010



Torque and effort values are subject to a variation of $\pm 10\%$
Response time at nominal torque : see the leaflet n° G08555-01

Designation	Caliper		SH18B	
	Lining *		US2-1	US2-4
Braking force BF for 1mm of air gap disc/lining	Static	N	160 000	117 400
	Dynamic	N	180 000	130 500
Linear speed of the disc	m/s		≤ 10	≤ 50
Dynamic braking torque BT (N.m) for 1 caliper and disc ØD	1000 mm	N.m	73 800	53 500
	1200 mm	N.m	91 800	66 500
	1500 mm	N.m	118 800	86 100
	2000 mm	N.m	163 800	118 700
BT for other ØD (mm)	N.m		$BT = BF(D/2000 - 0.09)$	
Regulation pressure	minimum	bar	180	
	maximum	bar	200	
Setting pressure of limit valve of the hydraulic unit	bar		225	
Total volume of oil displaced	cm ³		85 for one stroke disc/lining (nominal wear and opening)	

* US2-1: disc temperature during one braking $\leq 150^\circ\text{C}$

US2-4: disc temperature during one braking $\leq 600^\circ\text{C}$

US2-5: disc temperature during one braking $\leq 350^\circ\text{C}$, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHC18B CALIPER

Revision number: T03907-03-B

Revision date: 15.10.2010

Emergency brake
Fail safe
Spring application
Hydraulic release
Integral hydraulic power pack
Opening proving switches
Lining wear detector

Operating conditions:


- Ambient temperature: -10°C to +60°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Options:

- Lining wear control switch
- Progressive braking system
- Marine protection

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.




Dimensions in mm
Weight: 450kg

DISC BRAKE - SHC18B CALIPER

Revision number: T03907-03-B

Revision date: 15.10.2010

Installation instructions



Electrical data

- Motor voltages:

3 phases : $230/400VAC \pm 10\% 50Hz$
2.2kW. 4 poles

- Options motor:

$690VAC \pm 10\% 50Hz$
 $500VAC \pm 10\% 50Hz$
 $230/400VAC \pm 10\% 50Hz$ with PTC sensor
Other voltage, consult us.

- Opening switch:

250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.

220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.

Compatible with PLC
(Programmable Logic Controllers).
An opening switch used with other equipment
than PLC must not be reused with a PLC.

Torque and effort values are subject to a variation of $\pm 10\%$
Response time at nominal torque : see the leaflet n° G08555-01.

Designation	Caliper		SHC18B	
	Lining *		US2-1	US2-4
Braking force BF for 1mm of air gap disc/lining	Static	N	160 000	117 400
	Dynamic	N	180 000	130 500
Linear speed of the disc			≤ 10	≤ 50
Dynamic braking torque BT (N.m) for 1 caliper and disc ØD	1000 mm	N.m	73 800	53 500
	1200 mm	N.m	91 800	66 500
	1500 mm	N.m	118 800	86 100
	2000 mm	N.m	163 800	118 700
BT for other ØD (mm)	N.m		$BT = BF(D/2000 - 0.09)$	
F G	mm mm		$F = (0.433 \times D) - 154.2$ $G = (0.250 \times D) + 286.2$	
Setting pressure of limit valve of the hydraulic unit	bar		225	

* **US2-1**: disc temperature during one braking $\leq 150^\circ C$

US2-4 : disc temperature during one braking $\leq 600^\circ C$

US2-5: disc temperature during one braking $\leq 350^\circ C$, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SH25 CALIPER

Revision number: T03915-01-B

Revision date: 21.10.2010

Emergency brake
Fail safe
Spring application
Hydraulic release
Opening proving switches
Lining wear detector

Operating conditions:



- Ambient temperature: -10°C to +60°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Options:

- Lining wear control switch
- Progressive braking system
- Marine protection
- Caliper on support with integral hydraulic power pack

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.



Dimensions in mm
Weight : 440kg

Opening proving switch :

250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.

220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.

Compatible with PLC
(Programmable Logic
Controllers).


An opening switch used with other equipment
than PLC must not be reused with a PLC.

DISC BRAKE - SH25 CALIPER


Revision number: T03915-01-B

Revision date: 21.10.2010

Disc and support



Dimensions in mm.



Torque and effort values are subject to a variation of ±10%
Response time at nominal torque : see the leaflet n° G08555-01

Designation	Caliper		SH25-2		SH25-1	
	Lining *		US2-1	US2-4	US2-1	US2-4
Braking force BF for 1mm of air gap disc/lining	Static N	N	225 000	165 000	160 000	120 000
	Dynamic N	N	250 000	184 000	180 000	134 000
Linear speed of the disc	m/s		≤ 10	≤ 50	≤ 10	≤ 50
Dynamic braking torque BT (N.m) for 1 caliper and disc ØD (mm)	1500 mm	N.m	155 250	114 260	111 780	83 210
	2000 mm	N.m	217 750	160 260	156 780	116 710
	2500 mm	N.m	280 250	206 260	201 780	150 210
	3000 mm	N.m	342 750	252 260	246 780	183 710
BT for other ØD (mm)	N.m		BT = BF (D/2000 - 0.129)			
Regulation pressure	minimum	bar	180		140	
	maximum	bar	200		160	
Setting pressure limit valve of hydraul. Unit	bar		225		205	
Total volume of oil displaced	cm³		140 for one stroke disc/lining (nominal wear and opening)			

* US2-1: disc temperature during one braking ≤ 150°C

US2-4: disc temperature during one braking ≤ 600°C

US2-5: tdisc temperature during one braking ≤ 350°C, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHC25 CALIPER

Revision number: T03916-02-C

Revision date: 15.06.2011

Emergency brake
Fail safe
Spring application
Hydraulic release
Integral hydraulic power unit
Opening proving switches
Lining wear detector

Operating conditions:


- Ambient temperature: -10°C to +60°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions: consult us.

Options:

- Lining wear control switch
- Progressive braking system
- Marine protection
- Self contained electric system

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.




Dimensions in mm
Weight: 770 kg

DISC BRAKE - SHC25 CALIPER

Revision number: T03916-02-B

Revision date: 15.06.2011

Installation instructions



Electrical data

- Motor voltages :**
3 phases : 230/400VAC ±10% 50Hz
2.2kW. 4 poles
- Options motor :**
690VAC ±10% 50Hz
500VAC ±10% 50Hz
230/400VAC ±10% 50Hz with PTC sensor.
Other voltage, consult us.
- Opening switch :**
250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.
220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.
Compatible with PLC
(Programmable Logic Controllers).
An opening switch used with other equipment
than PLC must not be reused with a PLC.

Torque and effort values are subject to a variation of ±10%
Response time at nominal torque : see the leaflet n° G08555-01.

Designation	Caliper	SHC25-2		SHC25-1	
		Lining *	US2-1	US2-4	US2-1
Braking force BF for 1mm of air gap disc/lining	Static N	225 000	165 000	160 000	120 000
	Dynamic N	250 000	184 000	180 000	134 000
Linear speed of the disc	m/s	≤ 10	≤ 50	≤ 10	≤ 50
Dynamic braking torque BF (N.m) for 1 caliper and a disc ØD (mm)	N.m	155 250	114 260	111 780	83 210
1500 mm	N.m	217 750	160 260	156 780	116 710
2000 mm	N.m	280 250	206 260	201 780	150 210
2500 mm	N.m	342 750	252 260	246 780	183 710
3000 mm	N.m				
BT for other ØD (mm)	N.m	BT = BF (D/2000 - 0.129)			
F	mm	F = (0.433 × D) - 62			
G	mm	G = (0.250 × D) + 390			
Maximum setting pressure limit valve of hydraulic power unit	bar	225		205	

* **US2-1** : disc temperature during one braking ≤ 150°C

US2-4 : disc temperature during one braking ≤ 600°C

US2-5 : disc temperature during one braking ≤ 350°C, optional, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SH32 CALIPER

Revision number: T10040-01-C

Revision date: 15.06.2012

Emergency brake
Fail safe
Spring application
Hydraulic release
Opening proving switches
Lining wear indicator wires

Operating conditions:

- Ambient temperature: -10°C to +60°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µ


Other conditions: consult us.

Options:

- Lining wear proving switches
- Progressive braking system
- Marine protection


Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.



6 holes Ø45
for tie-rods M42 (class 10-9)
(not provided by Stromag France)

Disc ØD	1000	1500	2000	2500	3000
	≥ 95°	≥ 70°	≥ 53°	≥ 45°	≥ 38°



Standard disc thickness :
 $30 \leq e \leq 50$ mm.
Other thickness.
consult us.

Dimensions in mm
Weight : 600 kg

Opening proving switches

Wear proving switches (optional) :

250VAC maxi., 5A maxi.,
with interrupting capacity: 50VA maxi.

220VDC maxi., 5A maxi.,
with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers).



An opening switch used with other equipment
than PLC must not be reused with a PLC.

DISC BRAKE - SH32 CALIPER

Revision number: T10040-01-C

Revision date: 15.06.2012

Disc and support



IMPORTANT

BRAKING FORCE and **TORQUE** values correspond to lining quality **US2-1** and disc steel S235JR or S355JR (standard NF EN10025), these values are subject to a variation of ±10%.

Response time at nominal torque ≤ 0.3s

Designation	Caliper		SH32
	Lining		US2-1
BRAKING FORCE BF for air gap disc/lining of 2 x 1.5 mm	Dynamic N Static N		333 800 300 000
BRAKING FORCE BF for air gap disc/lining of 2 x 2 mm	Dynamic N Static N		320 000 288 000
Linear speed of the disc	m/s		≤ 10
DYNAMIC BRAKING TORQUE BT for 1 caliper and disc ØD (mm)	N.m		BT = BF (D/2000 - 0.129)
Regulation pressure	minimum maximum	bar bar	180 200
Setting pressure limit valve of hydraulic unit	bar		225
Total volume of oil displaced for air gap disc/lining of 2 x 2 mm	cm ³		191 for one stroke disc/lining

SIME Brakes Industrial Braking Systems

Emergency Brakes

APPLICATIONS

SHD:

- TOWER CRANES - BOOM CRANES
- OFFSHORE APPLICATIONS
- WINDTURBINES

TH/THC9:

- AERONAUTIC APPLICATIONS
- PORT CRANES



Photo courtesy of Comansa - Special project



HYDRAULIC EMERGENCY BRAKES TYPES SHD / TH

MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none"> • FAILSAFE BRAKE BY SPRING APPLICATION. • HYDRAULIC RELEASE • OPENING PROVING SWITCH • LINING WEAR INDICATORS 	<ul style="list-style-type: none"> • LINING WEAR PROVING SWITCH



SHD

- Single-spring hydraulical caliper
- A large range from SHD1 to SHD18
- Options:
 - Automatic lining wear compensation
 - Manual release tool - Positive braking
 - Integrated HPP - Marine protection


TH9

- Option :
 - Disc thickness 42 mm

THC9

- Caliper and Hydraulic Power Pack mounted on the same support
- Option: Electrical unit

Braking torque (kN.m)



SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHD1 CALIPER

Revision number: T10098-01-F

Revision date: 05.06.2019

Emergency brake
Fail to safe
Spring application
Hydraulic release
Mechanical holding of the brake in open position
for pads changing
Manual wear centering and compensation
Possible association with discs thickness: 12.7
(1/2"), 20 and 30mm.
Lining pads type **US2-1** or **ES3-7**
Lining pads with full wear indicators
Protection C5-M M

Operating conditions:



- Ambient temperature:
Dynamic braking : -30°C to +70°C
Brake applied (parking): -40°C to +70°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µm
- Other conditions: consult us.

Use:

- The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, consult us.

Options:

- Opening proving switch (**OS**)
- Lining wear proving switch (**WS**)
- All non-standard disc thickness > 12.7mm (1/2")
- Lining temperature sensor (**T**)
- Mechanical release tool (**DM**)
- **SHD1L**: caliper with manual wear compensation at half wear:
 - braking force before wear = +10% maxi.
 - braking force at half wear = -10% maxi.



C = Spacers according to disc thickness
G = Linings : Thickness of new lining 8 mm
Thickness to wear 6 mm

Each 1 mm of wear on each side:
manual centering and compensation

OS = Opening proving switch (option)

WS = Wear proving switch (option)

P = 2 oil ports 1/4"G

Bleeder screw delivered separately

T = PT100 sensor (option)

ØD : from 300 to 1000 mm

e = disc thickness

Dimensions in mm
Weight = 24 kg

Electrical data

Inductive switches of opening and wear (options):

3 wires PNP NO
12 to 24 VDC 200mA
with connector M12 / 5 positions
according to standard :
IEC61076-2-101 / code A

Sensor PT100 (option)

Detection of the temperature threshold :
100°C ± 5

- R = 136.6 Ω at 95 °C
- R = 138.5 Ω at 100°C
- R = 140.4 Ω at 105°C


Cable length = 2.5 meters
2 wires red/yellow

DISC BRAKE - SHD1 CALIPER

Revision number: T10098-01-F

Revision date: 05.06.2019


Installation instructions :



Steel S235JR or S355JR
Standard NF EN10025

Standard disc thickness :
 $e = 12.7 \text{ (1/2")}$, 20 and 30 mm $^{+0.15}_{-3}$
 Other thickness, consult us.

Support machining tolerances :



Torque and effort values are subject to a variation of ±10%
 Closing time at nominal torque ≤ 0.3 s

Designation	Caliper SHD1-		5	4	3	2	1	5	4	3	2	1
	Lining *		ES3-7				US2-1					
Braking force BF for air gap disc/lining of 2x1mm	Dynamic	N	11 000	8 000	6 000	4 000	2 000	11 000	8 000	6 000	4 000	3 000
	Static	N	9 900	7 200	5 400	3 600	1 800	9 680	7 040	5 280	3 520	2 640
Linear speed of the disc ●	m/s		≤ 50				≤ 10					
Dynamic braking torque BT (m.N) for 1 caliper and disc ØD (mm) / $300 \leq D \leq 1000$ mm	N.m		BT = BF (D/2000-0.037)									
Regulation pressure	Minimum Maximum	bar bar						150				
Regulation pressure	Maximum	bar						170				
Setting pressure limit valve of hydraulic unit	bar							190				
Total volume of oil displaced for air gap disc/lining of:	2 x 1mm (nominal opening) 2 x 2mm (wear+opening) 2 x 4mm SHD1L (wear+open.)	cm³ cm³ cm³						5 cm³ 9 cm³ 18 cm³				

* ES3-7: disc temperature during one braking $\leq 600^{\circ}\text{C}$

US2-1: disc temperature during one braking $\leq 100^{\circ}\text{C}$

● For higher speed, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHD2 CALIPER

Revision number: T03851-05-B

Revision date: 04.09.2012

Spring application

Hydraulic release

Opening proving switch (compatible for PLC)

Lining wear proving switch (compatible for PLC)

Marine protection

Working conditions:

- Ambient temperature: -20°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ


Other conditions, consult us.

Use:

- Emergency stopping brake in case of overspeed or loss of electrical supply

Options :

- Thermistors for detection of the maximum temperature of the disc




DISC BRAKE - SHD2 CALIPER


Revision number: T03851-05-B

Revision date: 04.09.2012

Installation instructions :



Support machining tolerances :



Response time at nominal torque < 0.3s
Torque and effort values are subject to a variation of $\pm 10\%$

Designation	Caliper		SHD2-3	SHD2-2	SHD2-1
	Lining				
Braking force BF for air gap disc/lining of 2x1mm	Dynamic	N	23 000	15 400	10 540
Linear speed of the disc ●	m/s		< 50		
Dynamic braking torque BT (m.N) for 1 caliper and disc ØD (mm)	630 mm	N.m	5 870	3 930	2 690
	710 mm	N.m	6 790	4 540	3 110
	800 mm	N.m	7 820	5 240	3 580
	1000 mm	N.m	10 120	6 780	4 640
		N.m	BT = BF (D/2000 - 0.06)		
Regulation pressure	Minimum	bar	180	110	85
	Maximum	bar	200	140	115
Setting pressure limit valve of hydraulic unit	bar		210	165	140
Total volume of oil displaced Max. oil volume of the jack	cm ³	cm ³	8 per stroke (for a nominal disc/lining stroke of 1 mm per side)		
			45		

- For higher speed, consult us.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHD5 CALIPER

Revision number: T03861-08-A

Revision date: 29.11.2010

Fail safe braking
Braking by spring application
Hydraulic release
Opening proving switch
Lining wear proving switch

Working conditions:


- Ambient temperature: -20°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:

- Emergency stopping brake in case of overspeed or loss of electrical supply


Options:

- Automatic lining wear compensation (WACS)
- Manual release tool (DM)
- Positive braking
- Detection of full lining wear
- Temperature detection of the linings
- Switch for PLC
- Marine protection



Opening and wear proving switches :
240V. 5A. 50VA AC
220V. 5A. 50W DC
2 m length cable (3 x 0.75 mm²)

Dimensions in mm
Weight: 105 kg




DISC BRAKE - SHD5 CALIPER

Revision number: T03861-08-A

Revision date: 29.11.2010



Installation instructions :



Torque and effort values are subject to a variation of $\pm 10\%$
Response time at nominal torque $\leq 0.3\text{s}$

Designation	Caliper		SHD5-6	SHD5-5	SHD5-4	SHD5-3	SHD5-2	SHD5-1
	Lining		WS1-3					
Braking force BF for 1.25 mm of air gap disc/lining	Dynamic	N	33 000	27 000	23 000	18 000	15 000	13 500
Linear speed of the disc for BF	m/s		< 50					
Dynamic braking torque BT (N.m) for a caliper mounted on a disc ØD (mm)	710 mm	N.m.	9 180	7 500	6 400	5 000	4 170	3 760
	1000 mm	N.m.	13 960	11 420	9 730	7 610	6 350	5 720
	1500 mm	N.m.	22 210	18 170	15 480	12 110	10 100	9 090
			N.m					
			BT = BF (D/2000 - 0.077)					
Regulation pressure	Min.	bar	110	110	85	60	60	60
	Max.	bar	140	140	115	80	80	80
Setting pressure limit valve hydraul. pack	bar		165	165	140	105	105	105
Total volume of oil displaced	cm ³		15.9 per stroke (for nominal disc/lining stroke of 1.25 mm per side)					
Max. oil volume of the jack	cm ³		76					

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHD5A-M2 CALIPER

Revision number: T10131-02-E

Revision date: 27.09.2018

Fail safe braking
Braking by spring application
Hydraulic release
Opening proximity switch
Holding tool
Detection of full lining wear
Protection level C3-H standard ISO 12944-2
VCI packing

Working conditions:


- Ambient temperature: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions. consult us.

Use:

- Emergency stopping brake in case of overspeed or loss of electrical supply
- Service life : 200 000 cycles

Options:

- Wear proximity switch
- Closing proximity switch
- Low temperature:
 - dynamic braking: -30°C to +60°C
 - brake closed (park position): -40°C to +60°C
- Protection level C5M-H



Electrical data :

Opening proximity switch:

3 wires PNP NO
10 to 58 VDC 200 mA
delivered with connector M12

Closing and wear switches: optional




DISC BRAKE - SHD5A-M2 CALIPER

Revision number: T10131-02-E

Revision date: 27.09.2018



Installation instructions :



Torque and effort values are subject to a variation of $\pm 10\%$
Response time at nominal torque ≤ 0.3 s

Designation	Caliper SHD5A-...-M2		1	2	3	4	5	6	7	8
	Lining		US2-1							
Braking force BF for 1 mm of air gap disc/lining	Dynamic	N	15500	17700	20000	28000	33000	41000	48000	56000
	Static	N	13650	15600	17600	24650	29050	36100	42250	49300
Linear speed of the disc for BF	m/s		< 10							
Dynamic braking torque BT for a caliper mounted on a disc ØD (mm) Dmax.=1500 mm	N.m		BT = BF (D/2000 - 0.065)							
Regulation pressure	Min.	bar	60	60	85	85	110	140	140	180
	Max.	bar	80	80	115	115	140	160	160	200
Setting pressure limit valve hydraulic pack	bar		105	105	140	140	165	190	190	225
Total volume of oil displaced	cm ³		12.7 per stroke (for nominal disc/lining stroke of 1 mm per side)							
Max. oil volume of the jack	cm ³		76							

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHD9 CALIPER

Revision number: T10042-01-E

Revision date: 31.08.2017

Fail safe braking
Braking by spring application
Hydraulic release
Opening proximity switch for PLC
(induction sensor)
Lining wear detectors
Association with discs thickness 30 mm

Working conditions :


- Ambient temperature: -10°C to +60°C
- Relative humidity $\leq 70\%$
- Dust in atmosphere $\geq 65\mu\text{m}$
- Other conditions, consult us.

Use :

- Emergency stopping brake in case of overspeed or loss of electrical supply

Option :

- Lining wear proximity switch
- Discs thickness $24 \leq e < 30$ mm.
- Option GF :
 - Ambient temperature:
 - Dynamic braking : -30°C to +60°C
 - Parking braking : -40°C to +60°C
- Marine protection



Electrical data :


Opening proximity switch

Standard caliper and caliper option GF
3 wires PNP NO
10 to 58 VDC 200 mA
with connector M12

Wear proximity switch (option):

Temperature -10°C to +60°C
3 wires PNP NO
10 to 58 VDC 200 mA
with connector M12

Temperature -40°C to +60°C / Option GF
3 wires PNP NO
10 to 36 VDC 200 mA
with connector M12




Weight: 148 kg
Dimensions in mm

DISC BRAKE - SHD9 CALIPER


Revision number: T10042-01-E

Revision date: 31.08.2017

Installation instructions :



Support machining tolerances :



Torque and effort values are subject to a variation of $\pm 10\%$
Response time at nominal torque ≤ 0.3 s

Designation	Caliper	SHD9-6		SHD9-5		SHD9-4		SHD9-3		SHD9-2		SHD9-1	
		Lining *	US2-1	US2-5	US2-1	US2-5	US2-1	US2-5	US2-1	US2-5	US2-1	US2-5	US2-1
Braking force BF for air gap disc/lining of 2x1mm	Dynamic	N	100 000	87 000	90 000	78 300	80 000	69 600	70 000	61 000	60 000	52 300	50 000
	Static	N	88 000	78 300	79 200	70 500	70 400	62 600	61 600	54 900	52 800	47 000	44 000
Linear speed of the disc	m/s	≤ 10											
Dynamic braking torque BT (m.N) for 1 caliper and disc ØD (mm) / D max ≤ 2000 mm	N.m	BT = BF (D/2000 - 0.093)											
Regulation pressure	Minimum Maximum	bar bar	180 200	170 190	150 170	120 140	110 130	90 110					
Setting pressure limit valve of hydraulic pack	bar	220	210	190	160	160	130	130					
Total volume of oil displaced for air gap disc/lining of: 2 x 1mm (nominal opening)	cm³	28											
2 x 1.5mm (nominal opening and wear before setting)	cm³	39											

* **US2-1:** disc temperature during one braking $\leq 150^{\circ}\text{C}$

US2-5: disc temperature during one braking $\leq 350^{\circ}\text{C}$.

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - SHD18 CALIPER

Revision number: T10129-01-A

Revision date: 13.01.2017

Fail safe braking
Braking by spring application
Hydraulic release
Opening proximity switch for PLC
(induction sensor)
Full lining wear indicators
Association with discs thickness 30 mm
Protection level C3 L standard NF ISO9223

Working conditions :



- Ambient temperature: -20°C to +60°C
 - Relative humidity ≤ 70%
 - Dust in atmosphere ≥ 70µm
- Other conditions, consult us.

Use :

- Emergency stopping brake in case of overspeed or loss of electrical supply

Option :

- Lining wear proximity switch
- Protection level C5-M-M standard NF ISO9223



Electrical data :

Opening proximity switch and wear proximity switch (option):
3 wires PNP NO
10 to 58 VDC 200 mA
with connector M12

Dimensions in mm
Weight: 395 kg


DISC BRAKE - SHD18 CALIPER

Revision number: T10129-01-A

Revision date: 13.01.2017



Installation instructions :



Torque and effort values are subject to a variation of ±10%
Response time at nominal torque ≤ 0.3s

Designation	Caliper		SHD18-3	SHD18-2	SHD18-1
	Lining *		US2-1		
Braking force BF for air gap disc/lining of 2x1mm	Dynamic N		180 000	150 000	120 000
	Static N		162 000	135 000	108 000
Linear speed of the disc	m/s		≤ 10		
Dynamic braking torque BT (m.N) for 1 caliper and disc ØD (mm) / D max ≤ 2000mm	N.m		BT = BF (D/2000 - 0.09)		
Regulation pressure	Minimum bar	195	160	130	
	Maximum bar	205	170	140	
Setting pressure limit valve of hydraulic unit	bar	225	190	160	
Total volume of oil displaced for air gap disc/lining of: 2 x 1 mm (nominal opening)	cm ³		48		
2 x 2 mm (nominal opening + wear before setting)	cm ³		82		

* **US2-1:** disc temperature during one braking ≤ 150°C

SIME Brakes Industrial Braking Systems

Emergency Brakes

DISC BRAKE - TH9 CALIPER

Revision number: T03830-01-C

Revision date: 13.12.2010

Fail safe
Spring applied
Hydraulic release (mineral oil)
Opening proving switch
Wear proving switch
Lining wear detector

Working:


- Ambient temperature: -10°C to +60°C
- Relative humidity ≤ 70%
- Dust in atmosphere ≥ 65µ
- Other conditions, consult us.

Use:

Service brake to operate with full or variable torque
Emergency brake in case of overspeed or loss of electrical supply

Option:

Disc thickness 42 mm



Designation	Caliper		TH9-3		TH9-2		TH9-1	
	Lining *		US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3
Braking force BF for 1mm of air gap disc/lining	Static N	81 000	54 000	52 650	38970	28 350	22 140	
	Dynamic N	90 000	60 000	58 500	43 300	31 500	24 600	
Linear speed of the disc	m/s	≤10	≤50	≤10	≤50	≤10	≤50	
Dynamic braking torque BT (N.m) for 1 caliper and a disc ØD (mm)	1000 mm Nm	38 880	25 920	25 270	18 700	13 600	10 620	
	1200 mm Nm	47 880	31 920	31 120	23 030	16 750	13 080	
	1500 mm Nm	61 380	40 920	39 890	29 530	21 480	16 770	
	2000 mm Nm	83 880	55 920	54 520	40 350	29 350	22 920	
BT for other ØD (mm)	Nm	BT = BF (D/2000 - 0.068)						
Positioning when D<3000mm	F mm	(0.4713 x D) - 172						
Above it. consult us	G mm	(0.1669 x D) + 212						
Regulation pressure	minimum bar	140		85		60		
	maximum bar	160		115		80		
Setting pressure limit valve of hydr. unit	bar	190		140		105		
Total volume of oil displaced	cm³	58 for one stroke disc/lining (nominal wear and opening)						

* US2-1: disc temperature during one braking ≤ 150°C

WS1-3: disc temperature during one braking ≤ 600°C

US2-5: disc temperature during one braking ≤ 350°C, optional, consult us.

Torque and force values are subject to a variation of ±10%.

Response time at nominal torque : see leaflet n° G08555-01.

Opening and wear switches :

250VAC maxi., 5A maxi., with interrupting capacity: 50VA maxi.

220VDC maxi., 5A maxi., with interrupting capacity: 50W maxi.

Compatible with PLC (Programmable Logic Controllers).

A switch used with other equipment than PLC must not be reused with a PLC.

Opening and wear switches are delivered with wire 5 x 0.75mm² and length 1m each

DISC BRAKE - THC9B CALIPER

Revision number: T03836-01-C

Revision date: 24.08.2012

Fail safe
Spring application
Hydraulic release
Integral hydraulic power unit
Self contained electric system
Opening proving switch
Lining wear control switch
Lining wear detector

Operating conditions:


- Ambient temperature: -10°C to +60°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µ
- Other conditions, please contact us.

Use:


The brake should be applied only in case of emergency stop, overspeed or shutdown of electric mains. Other use, please contact us.

Options:

- Progressive braking system
- Disc thickness 42 mm



Installation instructions



Permissible inclination of the caliper :
±15° maximum regarding the horizontal.
For other mounting, please contact us.

Weight: 180 kg
Dimensions in mm

Designation	Caliper		TH9-3		TH9-2		TH9-1	
	Lining *		US2-1	WS1-3	US2-1	WS1-3	US2-1	WS1-3
Braking force BF for 1mm of air gap disc/lining	Static N	81 000	54 000	52 650	38 970	28 350	22 140	
	Dynamic N	90 000	60 000	58 500	43 300	31 500	24 600	
Linear speed of the disc	m/s	≤10	≤50	≤10	≤50	≤10	≤50	
Dynamic braking torque BT (N.m) for 1 caliper and a disc ØD (mm)	1000 mm Nm	38 880	25 920	25 270	18 700	13 600	10 620	
	1200 mm Nm	47 880	31 920	31 120	23 030	16 750	13 080	
	1500 mm Nm	61 380	40 920	39 890	29 530	21 480	16 770	
	2000 mm Nm	83 880	55 920	54 520	40 350	29 350	22 920	
BT for other ØD (mm)	Nm	BT = BF (D/2000 - 0.068)						
Positioning when D<3000mm	F mm	(0.4713 x D) - 172						
Above it. consult us	G mm	(0.1669 x D) + 212						
Setting pressure limit valve of hydr. pack	bar	190		140		105		

* **US2-1:** disc temperature during one braking ≤ 150°C

WS1-3: disc temperature during one braking ≤ 600°C

US2-5: disc temperature during one braking ≤ 350°C, optional, consult us.

Electrical data:

HPP motor: 3 phases: 230/400V ±10% 50Hz 0.37kW, 4 poles
for mains: 230/400 V 50 Hz or 415 V 50 Hz or 460 V 60 Hz

Motor option: 400/690V ±10% 50Hz
255/440V ±10% 50Hz
290/500V ±10% 50Hz
280/480V ±10% 60Hz
330/575V ±10% 60Hz


Other voltage, please contact us.
Electrical casing IP55

Opening and wear proving switches:

U mini 24V AC or DC
U maxi 250V AC ou 220 V DC
I mini 0.1A AC or DC
I maxi 5A AC or DC
interrupting capacity :
mini : 2.4VA AC or 2.4W DC
maxi : 50VA (AC) ou 50W (DC)

Electrical Power Units

ELECTRICAL POWER UNITS



MAIN CHARACTERISTICS

- | | |
|---|--|
| <ul style="list-style-type: none"> DESIGNED TO GIVE OPTIMUM PERFORMANCE FROM THE ELECTROMAGNETIC CALIPERS AC LINE SUPPLY:
AB8, AC64, AC32, AS100, 4200 AND 4205 DC LINE SUPPLY: DC64, DC32 AND DS100 | <ul style="list-style-type: none"> HIGH "CALL" VOLTAGE TO REDUCE OPENING RESPONSE TIME AUTOMATIC REDUCTION TO AN ECONOMICAL "HOLD" VOLTAGE A "CUT-OUT" CIRCUIT GIVING A VERY SHORT BRAKE ACTION |
|---|--|



AC64 & AC32

- Simplicity of adjustment and use.
- Weights and size reduced.
- Quick diagnosis of fault through the use of 6 LEDs.
- Standard mains:
230/500 VAC, 115/220 VDC

AS100

- Other mains: 115 VAC, 500/700 VAC, 24 VDC et 48 VDC
- Available in:
 - Polycarbonate enclosure (CP): IP66, IK8
 - or Steel enclosure (CA): IP66, IK9

4200 & 4205 / AB8

- 4205** unit enables electrically controlled lowering.
- AB8** unit is used with "E" series calipers for progressive braking torque control.

POWER UNITS	CALIPERS											
	660	650	650E	645 - 45K	5D - 5DR	5DE	4CA2	3CA2	2CA2 - 1CA2	OSA	OOSA	2SA
AC64 - DC64												
AC32 - DC32												
AS100 - DS100												
4200												
4205												
AB8												

SIME Brakes Industrial Braking Systems

Electrical Power Units

DISC BRAKE - ELECTRICAL POWER UNIT AC64-50 CA

Revision number: T04560-01-D

Revision date: 20.07.2011

Compact power supply operating on alternating single or two-phase mains.
For SIME Disc Brakes with 50 V coil.
type : 660/650-5K/5D-645-45K-4WD-4CA2
Steel case

Operating Conditions:

- Casing protection standard IP66 IK09
- Ambient temperature : -20°C to +60°C

Electrical Data :


Single or two-phase mains AC
230 to 500V AC ± 10% 50/60Hz

EC marking of conformity :

- 2006/95/EC directive BT (standard EN60204-1)
- 2004/108/EC directive CEM
(standards EN61000-6-2 EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper
(cannot be combined with anti-condensation)
- Anti-condensation kit
- Polycarbonate case IP66 IK08



Time of calipers closing (time between mains cut-off and application of 66% of nominal torque).

Caliper	660-5KR-5DR	650-650E 5K-5D-5KE-5DE	645-45K	4WD	4CA2
Tr 66 (ms)	100	100	120	300	200

Caliper		660-650-650E	5K-5D-5KR/DR 5KE-5DE	645	45K	4WD	4CA2
Maximum number of calipers		2	2	2	2	2	1
Resistance at 20°C per caliper	Ω	6.68	6.68	4.52	4.52	4.52	3.08
Maximum number of actuations per hour and ambient temperature θ	θ ≤ 40°C	150	1000	150	1000	60	1000
	40°C < θ ≤ 60°C	150	600	150	600	60	600
Mains current absorbed per caliper	Max	A	4	4	6	6	9
	Economy	A	0.6	0.6	0.75	0.75	1
Maximum return resistance of the cable connecting the caliper to the power supply	Ω	2	2	1	1	1	1 *
Max. length of the connecting cable (Power supply - caliper) for 1 caliper per cable. depending on cable section	2.5 mm ²	m	100	100	50	50	50 *
	4 mm ²	m	160	160	80	80	80 *
	6 mm ²	m	240	240	120	120	120 *
Protection to be provided in head of control contactor on mains input	Number of caliper	1	2	1	2	1	2
	Fuse aM	A	1	2	2	4	4
	Circuit-breaker curve C	A	1	2	2	4	4

DISC BRAKE - ELECTRICAL POWER UNIT AC64-50 CP

Revision number: T04500-01-D

Revision date: 19.07.2011

Compact power supply operating on alternating single or two-phase mains.
For S Disc Brakes with 50 V coil.
type : 660/650-5K/5D-645-45K-4WD-4CA2
Polycarbonate case

Operating Conditions:

- Casing protection standard IP66 IK08
- Ambient temperature : -20°C to +60°C

Electrical Data :


Single or two-phase mains AC
230 to 500V AC ± 10% 50/60Hz

EC marking of conformity :

2006/95/EC directive BT (standard EN60204-1)
2004/108/EC directive CEM
(standards EN61000-6-2 EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Steel case IP66 IK09



ELECTRICAL DANGER : THIS PRODUCT IS NOT INSULATED

Control and power electronic of power supply is not insulated and is under mains voltage. The power supply must be installed by qualified personnel, used to handle this equipment type and aware of risks inherent in their utilization.

* If the ambient temperature of the caliper 4CA2 is higher than 60°C, the maximum return resistance and the maximum length of the connecting cable given in the above table must be divided by 2.

SIME Brakes Industrial Braking Systems

Electrical Power Units

DISC BRAKE - ELECTRICAL POWER UNIT AC32-50 CA

Revision number: T10005-02-C

Revision date: 22.02.17

Compact power supply operating on alternating single or two-phase mains.
For SIME disc brakes with 50 V coil.
type : 4CA2 - 3WD - 3CA2 - 2CA2 - 1CA2
Steel case

Operating Conditions:

- Casing protection standard IP66 IK10
- Ambient temperature : -20°C to +60°C

Electrical Data :


Single or two-phase mains AC
230 to 500V AC ± 10% 50/60Hz

EC marking of conformity :

- 2006/95/CE directive Low Voltage (standard EN60204-1)
- 2004/108/CE directive EMC (standards EN61000-6-2 and EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Polycarbonate case IP66 IK08



Caliper	4CA2	3WD	3CA2	2CA2 - 1CA2	2CA2 + 20% - 1CA2 + 20%
Maximum number of calipers	2	1	1		1
Resistance at 20°C per caliper	Ω	3.08	1.63	1.01	0.75
Maximum number of actuations per hour and ambient temperature θ	θ ≤ 40°C	1000	60	1000	1000
	40°C < θ ≤ 60°C	600	60	600	300
Mains current absorbed per caliper	Max	A	9	16	20
	Economy	A	1	1.5	2
Maximum connecting cable return resistance between caliper and supply unit	Ω	1	0.75	1	0.5
Maximum connecting cable length (caliper-input) according to the cable section	2.5mm ²	m	50	35	50
	4mm ²	m	80	60	80
	6mm ²	m	120	90	120
	10mm ²	m	205	155	205
Protection to be provided in head of control contactor on mains input	Fuse aM	A	6	4	6
	Circuit-breaker curve C	A	8	6	10

DISC BRAKE - ELECTRICAL POWER UNIT AC32-50 CP

Revision number: T10005-01-E

Revision date: 04.04.2018

Compact power supply operating on alternating single or two-phase mains.
For SIME disc brakes with 50 V coil.
type : 4CA2 - 3WD - 3CA2 - 2CA2 - 1CA2
Polycarbonate case

Operating Conditions:

- Casing protection standard IP66 IK08
- Ambient temperature : -20°C to +60°C

Electrical Data :


Single or two-phase mains AC
230 to 500V AC ± 10% 50/60Hz

EC marking of conformity :

- 2006/95/CE directive Low Voltage (standard EN60204-1)
- 2004/108/CE directive EMC (standards EN61000-6-2 and EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Steel case IP66 IK10



ELECTRICAL DANGER : THIS PRODUCT IS NOT INSULATED

Control and power electronic of power supply is not insulated and is under mains voltage. The power supply must be installed by qualified personnel, used to handle this equipment type and aware of risks inherent in their utilization.

SIME Brakes Industrial Braking Systems

Electrical Power Units

DISC BRAKE - ELECTRICAL POWER UNIT AS100-50 CA

Revision number: T10035-02-B

Revision date: 19.10.2015

Compact power supply operating on alternating single or two-phase mains.
For SIME disc brakes with 50 V coil.
type : OSA - OOSA
Steel case

Operating Conditions:

- Casing protection standard IP66 IK10
- Ambient temperature : -20°C to +60°C

Electrical Data :


Single or two-phase mains AC
230 to 500V AC ± 10% 50/60Hz

EC marking of conformity :

- 2006/95/CE directive Low Voltage (standard EN60204-1)
- 2004/108/CE directive EMC (standards EN61000-6-2 and EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Steel case IP66 IK08



Caliper		0SA		0OSA
Maximum number of calipers		1		1
Resistance at 20°C per electromagnet		1.01		1.01
Maximum number of actuations per hour and ambient temperature θ	θ ≤ 60°C	100	100	100
Mains current absorbed	Max	A	28	36
	Economy	A	3.5	3.6
Maximum connecting cable return resistance between caliper and supply unit		Ω	3.5	1
Maximum connecting cable length (caliper input) according to the cable section	2.5 mm ²	m	170	50
	4 mm ²	m	275	80
	6 mm ²	m	415	120
	10 mm ²	m	715	205
Protection to be provided in head of control contactor on mains input	Fuse aM	A	6	8
	Circuit-breaker curve C	A	16	16

DISC BRAKE - ELECTRICAL POWER UNIT AS100-50 CP

Revision number: T10035-01-B

Revision date: 19.10.2015

Compact power supply operating on alternating single or two-phase mains.
For SIME disc brakes with 50 V coil.
type : OSA - OOSA
Polycarbonate case

Operating Conditions:

- Casing protection standard IP66 IK08
- Ambient temperature : -20°C to +60°C

Electrical Data :


Single or two-phase mains AC
230 to 500V AC ± 10% 50/60Hz

EC marking of conformity :

- 2006/95/CE directive Low Voltage (standard EN60204-1)
- 2004/108/CE directive EMC (standards EN61000-6-2 and EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Steel case IP66 IK10



ELECTRICAL DANGER : THIS PRODUCT IS NOT INSULATED

Control and power electronic of power supply is not insulated and is under mains voltage. The power supply must be installed by qualified personnel, used to handle this equipment type and aware of risks inherent in their utilization.

SIME Brakes Industrial Braking Systems

Electrical Power Units

DISC BRAKE - ELECTRICAL POWER UNIT DC64-50 CP

Revision number: T04530-01-F

Revision date: 25.02.2019

Compact power supply operating on direct mains.
For SIME disc brakes with 50V coil.
type : 660/650-5K/5D-645-45K-4WD-4CA2
Polycarbonate case

Operating conditions:

- Casing protection standard IP66 IK08
- Ambient temperature : -20°C to +60°C

Electrical data :

Mains DC : 100 to 275 V DC ± 10%
Possible operation in 115 V AC ± 20%

EC marking of conformity :


2006/95/EC directive BT (standard EN60204-1)
2004/108/EC directive CEM (EN61000-6-2 EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Steel case IP66 IK09

ELECTRICAL DANGER : THIS PRODUCT IS NOT INSULATED

Control and power electronic of power supply is not insulated and is under mains voltage.



Caliper	660-650-650E	5K-5D-5KR-5DR 5KE-5DE	645	45K	4WD	4CA2
Maximum number of calipers	2	2	2	2	2	1
Resistance at 20°C per caliper (Ω)	6.68	6.68	4.52	4.52	4.52	3.08
Maximum number of actuations per hour and ambient temperature θ	θ ≤ 40°C 40°C < θ ≤ 60°C	150 150	1000 600	150 150	1000 600	60 60
Mains current absorbed per caliper	Max (A) Economy (A)	3.5 0.4	3.5 0.4	5 0.5	5 0.5	9 0.75
Maximum return resistance of the cable connecting the caliper to the power supply (Ω)	2	2	1	1	1	1 *
Max. length of the connecting cable (Power supply - caliper) for 1 caliper per cable, depending on cable section	2.5 mm² (m) 4 mm² (m) 6 mm² (m)	100 160 240	100 160 240	50 80 120	50 80 120	50 * 80 * 120 *
Protection to be provided in head of control contactor on mains input	Number of caliper Fuse aM (A) Circuit-breaker curve C (A)	1 1 1	2 2 2	1 2 2	1 2 2	1 4 4

* If the ambient temperature of the caliper 4CA2 is higher than 60°C.

the maximum return resistance and the maximum length of the connecting cable given in the above table must be divided by 2.

DISC BRAKE - ELECTRICAL POWER UNIT DC32-50 CP

Revision number: T10007-01-G

Revision date: 09.04.2018

Compact power supply operating on direct mains.
For SIME disc brakes with 50V coil.
type : 4CA2 - 3WD - 3CA2 - 2CA2
Polycarbonate case

Operating conditions:

- Casing protection standard IP66 IK08
- Ambient temperature : -20°C to +60°C

Electrical data :


Mains DC : 110 to 275V DC ± 10%
Possible operation in 115 V AC ± 20%

EC marking of conformity :

- 2006/95/CE directive Low Voltage (standard EN60204-1)
- 2004/108/CE directive EMC (standards EN61000-6-2 and EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Steel case IP66 IK10



ELECTRICAL DANGER : THIS PRODUCT IS NOT INSULATED

Control and power electronic of power supply is not insulated and is under mains voltage. The power supply must be installed by qualified personnel, used to handle this equipment type and aware of risks inherent in their utilization.

Caliper	4CA2	3WD	3CA2	2CA2 1CA2	2CA2 + 20% 1CA2 + 20%
Maximum number of calipers	2	1	1		1
Resistance at 20°C per caliper (Ω)	3.08	1.63	1.01		0.75
Maximum number of actuations per hour and ambient temperature θ	θ ≤ 40°C	1000	60	1000	1000
	40°C < θ ≤ 60°C	600	60	600	300
Mains current absorbed per caliper	Max (A)	9.9	18	24.1	36.9
	Economy (A)	1.5	1.6	1.8	2.3
Maximum connecting cable return resistance between caliper and supply unit (Ω)	1	0.75	1		0.5
Max. length of the connecting cable (Power supply/caliper) for 1 caliper per cable, depending on cable section	2.5mm² (m)	50	35	50	25
	4mm² (m)	80	60	80	40
	6mm² (m)	120	90	120	60
	10mm² (m)	205	155	205	100
Protection to be provided in head of control contactor on mains input	Fuse aM (A)	6	6	6	10
	Circuit-breaker curve C (A)	8	8	10	16

SIME Brakes Industrial Braking Systems

Electrical Power Units

DISC BRAKE - ELECTRICAL POWER UNIT DS100-50 CP

Revision number: T10037-01-B

Revision date: 15.11.2016

Compact power supply operating on direct mains.
For SIME disc brakes with 50 V coil
type : OSA - OOSA
Polycarbonate case

Operating Conditions:

- Casing protection standard IP66 IK08
- Ambient temperature : -20°C to +60°C

Electrical Data :


Mains DC : 110 to 275V DC ± 10%
Possible operation in 115 V AC ± 20%

EC marking of conformity :

- 2006/95/CE directive Low Voltage (standard EN60204-1)
- 2004/108/CE directive EMC (standards EN61000-6-2 and EN61000-6-4)

Options:

- Closure delay of the caliper
- Disengageable closure delay of the caliper (cannot be combined with anti-condensation)
- Anti-condensation kit
- Steel case IP66 IK10



ELECTRICAL DANGER : THIS PRODUCT IS NOT INSULATED

Control and power electronic of power supply is not insulated and is under mains voltage.

The power supply must be installed by qualified personnel used to handle this equipment type and aware of risks inherent in their utilization.

Caliper	OSA	OSA	OOSA
Maximum number of calipers	1	2	1
Resistance at 20°C per electromagnet	Ω	1.01	1.01
Maximum number of actuations per hour and ambient temperature θ	θ ≤ 60°C	100	100
Mains current absorbed	Max	A	33
	Economy	A	2.6
Maximum connecting cable return resistance between caliper and supply unit	Ω	3.5	1
Maximum connecting cable length (caliper-input) according to the cable section	2.5 mm ²	m	170
	4 mm ²	m	275
	6 mm ²	m	415
	10 mm ²	m	715
Protection to be provided in head of control contactor on mains input	Fuse aM	A	8
	Circuit-breaker curve C	A	16

DISC BRAKE - ELECTRICAL POWER UNIT TYPE 4200

Revision number: T04800-01-C

Revision date: 21.10.2015

2 presentations are available:
 - C for casing protected version
 - P for plate mounted version


Note:

if 2 calipers are driven by the same power supply (or the 2 coils of the caliper OOSA) they must be connected in series (refer to the installation and maintenance leaflet)




Operating conditions:

- Line voltage:
 - direct: 115V to 600VDC ± 10%
 - single or three phases:
115V to 500VAC ± 10% 50/60Hz
- Ambiant temperature: -20°C to +55°C

Type C4200 casing protected version
(casing IP 66 standard EN60529)



Type P4200 plate mounted version
(for cabinet assembly)



CALIPER	Type	4CA		3CA		OSA		OOSA		2SA		
		Number	1	2	1	2	1	2	1	2	1	
Maximum number of actuations per hour at 40°C		700		1000		100		100		100		
Power consumption of the power supply	Maximum	W	1695	3215	1355	2480	2850	5380	5380	8205	15 815	
	Economy	W	105	140	130	175	305	480	480	205	300	
Max. connecting cable return resistance caliper to supply unit (for 1 coil)		Ω	1		1		1		1		1	
Delayed fuse rating to be provided between power supply and mains :												
direct :	115 VDC	A	25	X	25	X	25	X	25	X	25	
	230 VDC	A	25		25		25		25		35	
	400 to 600 VDC	A	25		25		25		25		35	
single phase :	115 VAC	A	25	X	25	X	25	X	25	X	35	
	230 VAC	A	25		25		25		25		35	
	400 VAC	A	25		25		25		25		35	
	500 VAC	A	25		25		25		25		25	
3 phases :	230 VAC	A	25		25		25		25		25	
	400 VAC	A	16		16		16		25		25	
	500 VAC	A	16		16		16		16		16	
		Forbidden association										

SIME Brakes Industrial Braking Systems

Electrical Power Units

DISC BRAKE - ELECTRICAL POWER UNIT TYPE 4205

Revision number: T04810-01-B

Revision date: 21.10.2015

Designed for normal control or progressive release of electrical calipers to perform lowering maneuvers.

2 presentations are available:


- C for casing protected version
- P for plate mounted version

Operating conditions:

- Line voltage:
 - direct: 115V to 600VDC \pm 10%
 - single or three phases:
115V to 500VAC \pm 10% 50/60Hz
- Ambiant temperature: -20°C to +55°C




Type C4205 casing protected version (casing IP 66 EN60529)

Weight: 17kg



Type P4205 plate mounted version
(for cabinet assembly)

Weight: 8kg



DISC BRAKE - ELECTRICAL POWER UNIT TYPE 4205

Revision number: T04810-01-B

Revision date: 21.10.2015

Notes:

- Lowering a load is performed manually, with or without vertical speed control, by progressively releasing the calipers (between 100% and 50% of the nominal torque)
- 2 calipers driven by the same power supply (or the 2 coils of the caliper OOSA) must be connected in series (refer to the installation and maintenance leaflet)
- For lowering with calipers 4CA2, contact us.

Note : by insulated kinematics (e.g.: a drum), the lowering command is performed only for one of the **4205** electrical supply units. This unit is called the "master".
One "master" unit can drive up to 5 "slave" units.

CALIPER	Type Number	4CA2		3CA2		OSA		OOSA		2SA	
		1	2	1	2	1	2	1	2	1	2
Maximum number of actuations per hour at 40°C		700		1000		100		100		100	
Power consumption of the power supply	Maximum W	1695	3215	1355	2480	2850	5380	5380	8205	15 815	
	Economy W	105	140	130	175	305	480	480	205	300	
Max. connecting cable return resistance caliper to supply unit (for 1 coil)		Ω		1		1		1		1	
Delayed fuse rating to be provided between power supply and mains :											
direct :	115 VDC	A	25	X	X	25	X	X	25	X	X
	230 VDC	A	25		25			25		35	
	400 to 600 VDC	A	25		25			25		35	35
single phase :	115 VAC	A	25	X	X	25	X	X	25	X	X
	230 VAC	A	25		25			25		35	
	400 VAC	A	25		25			25		35	35
	500 VAC	A	25		25			25		25	25
3 phases :	230 VAC	A	25		25			25		25	X
	400 VAC	A	16		16			16		25	25
	500 VAC	A	16		16			16		16	16



Forbidden association

NOTES

DISC BRAKE - ELECTRICAL POWER UNIT TYPE AB8

Revision number: T04400-01-B

Revision date: 21/07/2016

Designed for control of the progressive braking effort by means of a foot pedal.

2 presentations are available:

- casing protected version C
- plate mounted version P


Matching CE markings:

- 73/23/CEE BT directive
- 89/336/CEE CEM directive
- (specifications EN50081-2 EN50082-2
EN6 0204-1)



Working conditions:

- Voltage(single phase)
 - 230/400V
 - or 400/415V
 - or 400/440V
 - or 400/460V
 - or 400/500V
- Working ambient temperature:
-20°C to +60°C

Type C AB8 protected version
(casing IP 669 standard DIN 40050)




Type P AB8 plate mounted version
(for cabinet assembly)



Control pedal:

it can drive 1 or 2 supply units AB8

Weight: 1.9kg




Caliper	650 E - 5 KE - 5 DE	
Number of calipers	1	2
Power consumption in Watts for an output voltage of 20V DC	115	230
Voltage	3 to 24V DC	
Maximum connecting cable return resistance (caliper to supply unit)	Ω	0.5
Primary fuse DIN "NH" type. "aM" class to be provided	230 V	1A
	400/415 V	1A
	440/460/500 V	1A
		2A

SIME Brakes Industrial Braking Systems

Hydraulic Power Packs

HYDRAULIC POWER PACKS



SIME Brakes Industrial Braking Systems

Hydraulic Power Packs

HYDRAULIC POWER PACKS	TANK	MAX. PRESSURE	ASSOCIATED CALIPERS	MAIN CHARACTERISTICS
C3BSH	4 L	180 bars	SHD2 - SHD5 SH5 - SH9 TH9	<ul style="list-style-type: none"> Vertical installation <u>Options:</u> <ul style="list-style-type: none"> MS: Special voltages motor OP1 / Y1-3 Z1-Z2: Delayed braking R: Braking torque adjustment AF: Lowering device
CSH	6 L	200 bars	SHD5 - SHD9	<ul style="list-style-type: none"> Vertical installation Customer-fitted solutions: <ul style="list-style-type: none"> Application of full braking force Adjustable and progressive application fo the braking force with non-application of the full braking force at beginning of the braking Electrical indicators (clogging, oil temperature and level)
CE8L	8 L	225 bars	SHD2 - SHD5 SH5 - SH9 SH15 - SH18B SH25 TH9	<ul style="list-style-type: none"> Horizontal or vertical installation. <u>Options:</u> <ul style="list-style-type: none"> MS / OP1 OP2: Manual lowering with dead man safety device OP3: Manual lowering with overspeed detection OP4: Indicator of the valves position CS2EV: Monitoring device of the 2 solenoid valves (OP1) Y5: Regulated braking or lowering of the load OP6: Tightness for Iron and steel industry Drip tray for HPP mounted horizontally Electrical power unit integrated to the HPP Electrical indicators: clogging, oil level and temperature...
CE12L	12 L	225 bars	SH15 - SH18B SH25 - SH32	<ul style="list-style-type: none"> Vertical installation. <u>Options:</u> <ul style="list-style-type: none"> MS / OP1 / OP2 / OP3 / OP4 / OP6 OP9: Output pressure switch Electrical power unit integrated to the HPP Electrical indicators: clogging, oil level and temperature...
ST210	63 L	225 bars	SH15 - SH18B SH25 - SH32	<ul style="list-style-type: none"> Vertical installation. <u>Options:</u> <ul style="list-style-type: none"> MS / OP1 / OP2 / OP3 / OP4 / OP6 OP9: Output pressure switch Electrical power unit integrated to the HPP Electrical indicators: clogging, oil level and temperature...

SIME Brakes Industrial Braking Systems

Hydraulic Power Packs

DISC BRAKE - C3BSH-ATH2 HYDRAULIC POWER PACK

Revision number: T05226-01-E

Revision date: 20.02.2014

Association with 1 caliper of **TH9**, **SH5** or **SH9A** range.

Maximal utilization pressure : 225 bars

Reservoir maximum oil volume : 4 L

Integrated electrical unit

Operating conditions:


- Ambient temperature: -10°C to +50°C
 - Relative humidity: ≤ 70%
 - Dust in atmosphere ≥ 65µm
 - Protection required against vertically falling water
- Other conditions: consult us.

Use:

- Frequency of operation : 100 op. / hour maxi.
Except for SH5-6 and SH9-3 calipers :
frequency of operation : 60 op. /hour maxi.

Options:

MS	Special motor
OP1	Enhanced security return circuit by 2 solenoid valves
R	Braking torque adjustment
AF	Manual lowering with a dead man safety design
OP6	Tight HPP for iron and steel industry
Y1-3	Caliper closing with stepped braking torque application
Z1-Z2	Delayed braking



DISC BRAKE - C3BSH-ATH2 HYDRAULIC POWER PACK

Revision number: T05226-01-E

Revision date: 20.02.2014



Electrical data

Motor M100

230/400VAC 50Hz 0.37 kW

4 poles 1500rpm

For mains 3 phases

Frequency 50 Hz

220-230-240VAC ±10% 50Hz

380-400-415VAC ±10% 50Hz

Frequency 60 Hz

480VAC ±10% 60Hz


Solenoid valve EV100

Coil under 48 VRAC


Pressure switch CP100

- Protection: IP 65
- 240 V AC. 1.5 A
- 250 V DC - 0.1 A

Electrical unit connections



Flow diagram



SIME Brakes Industrial Braking Systems

Hydraulic Power Packs

DISC BRAKE - CSH-02 / CSH-09 / CSH-10 HPP

Revision number: T10123-02-F

Revision date: 14.11.2018

Association with 1 or 2 caliper(s): see table 1

Motor 0.75 kW at 1500 rpm

Maximal utilization pressure : see table 1

Electrical indicators of oil temperature and level
(OP7-8)

Vertical installation

Soft-Braking :

Allow progressive and adjustable application of the braking force and non-application of the full braking force at the beginning of braking.



Operating conditions:

- Ambient temperature: -10°C to +50°C
- Relative humidity: ≤ 100%
- C4M L anti-corrosive protection level (according to ISO12944 standards)
- IP55 tightness level

Other conditions: consult us.

Use:


- Service life : 200 000 operations
- Frequency of operation : 60 op. / hour maxi.



Dimensions in mm
Weight without oil: 62 kg
Tank volume: 6 L

Table 1

HPP	Max. utilization Pressure	Association with the caliper
CSH-02	190 bar	SHD9-4-03
CSH-09	225 bar	SHD9-6-06
CSH-10	215 bar	SHD5A-8-M2-08




View without the motor

DISC BRAKE - CSH-02 / CSH-09 / CSH-10 HPP

Revision number: T10123-02-F

Revision date: 14.11.2018



Electrical data:

Motor M

230/400VAC 50Hz 0.75 kW
4 poles 1500rpm

For mains 3 phases

Frequency 50 Hz
220-230-240VAC ±10% 50Hz
380-400-415VAC ±10% 50Hz
Frequency 60 Hz
265-277-290VAC ±10% 60Hz
440-460-480VAC ±10% 60Hz

Pressure switch CP1

- Electrical design : DC PNP
 - Operating voltage : 9.6...32 VDC
 - Current consumption : < 25 mA
 - Insulation resistance : > 100 MΩ
 - Current rating : 500 mA
 - 2 switching outputs normally open / closed complementary
 - Connector M12 / 5 positions in accordance with IEC61076-2-101 standard / code A (not delivered)
- Solenoid valves EV1-EV2-EV3-EV4**
Coil under 24VDC with rectifier
DIN connector not provided

Electrical indicators of oil temperature and level OP7-8

Integrated to the visual oil level, the electrical indicators provide a temperature signal by means of a thermostat (NC) preset at 70°C (OP7) and a minimum oil level electric signal (INV) (OP8).

Electric part is completely separate from oil and insulated.

- Power commutable in DC : 40 W
- Power commutable in AC : 40 V.A.
- Current strength in DC - AC : 2 A
- Commutable voltage : 230 VDC/VAC
- Connector provided

SIME Brakes Industrial Braking Systems


Hydraulic Power Packs

DISC BRAKE - CSH-02 / CSH-09 / CSH-10 HPP

Revision number: T10123-02-F

Revision date: 14.11.2018

Flow diagram



NOTES

SIME Brakes Industrial Braking Systems

Hydraulic Power Packs

DISC BRAKE - CE8L HYDRAULIC POWER PACK

Revision number: T05570-01-D

Revision date: 26.02.2015

Maximal utilization pressure : 225 bars

Reservoir maximum oil volume : 8 L

Vertical or horizontal installation

Operating conditions:

- Ambient temperature: -10°C to +60°C
- Relative humidity: ≤ 70%
- Dust in atmosphere ≥ 65µm
- Protection required against vertically falling waters

Other conditions: consult us.

Use:

- Frequency of operation : 100 op. / hour maxi.


Association with the calipers :

CE8L-20	SH25-2. SH18B. SH9-3. SH5-6
CE8L-18	SH15-3. SH9-2
CE8L-16	SH25-1. SH15-2. SH5-5. TH9-3
CE8L-14	SH15-1. SH9-1. SH5-4
CE8L-11	SH5-3. TH9-2

Options :

MS	Motor 290/500VAC 50Hz or Motor 230/400 VAC with PTC sensor
EVS	EV coils voltage different from the standard
K1 or K2	Integrated electrical power unit
OP1	Enhanced security return circuit by 2 solenoid valves
CS2EV	Monitoring device of the 2 solenoid valves (of OP1)
OP1-OP2	Manual lowering with a dead man safety device.

OP1-OP3	Manual lowering with overspeed safety by solenoid valve 24VDC.
OP4	Indicator switch of the position of the control valve(s)
OP5	Visual or electrical clogging Indicator
OP6	HPP for iron and steel industry
OP8	Electrical indicator of oil minimum level
OP10	Drip tray for horizontal HPP
RV	Drain valve for reservoir
Y5	Regulated braking




Representation: CE8L-H
(horizontal position)
Dimensions in mm

DISC BRAKE - CE8L HYDRAULIC POWER PACK

Revision number: T05570-01-D

Revision date: 26.02.2015



Electrical data:

Motor M

230/400VAC 50Hz 2.2 kW
4 poles 1500rpm

For mains 3 phases

Frequency 50 Hz
220-230-240VAC $\pm 10\%$ 50Hz
380-400-415VAC $\pm 10\%$ 50Hz
Frequency 60 Hz
480VAC $\pm 10\%$ 60Hz


Solenoid valve EV1

Coil under 230VAC 50 or 60 Hz
single phase. 20W
Protection IP55

Pressure switch CP1

- Single-pole and snap-acting contact "OC"
- Protection: IP 66
- 240 V AC. 1.5 A
- 250 V DC. 0.1 A

Flow diagram



SIME Brakes Industrial Braking Systems

Hydraulic Power Packs

DISC BRAKE - CE12L HYDRAULIC POWER PACK

Revision number: T10001-01-F

Revision date: 26.02.2015

Maximal utilization pressure : 225 bars

Reservoir maximum oil volume : 12 L

Vertical or horizontal installation

Operating conditions:

- Ambient temperature: -20°C to +60°C
- Relative humidity: ≤ 100%
- Dust in atmosphere ≥ 30µm
- Protection required against vertically falling waters

Other conditions: consult us.

Use:

- Frequency of operation : 100 op. / hour maxi.


Association with the calipers :

CE12L-20	SH25-2. SH18B
CE12L-18	SH15-3
CE12L-16	SH25-1. SH15-2
CE12L-14	SH15-1


Options :

MS	Motor 500VAC 50Hz or Motor 230/400 VAC with PTC sensor
EVS	EV coils voltage different from the standard
K4	Integrated electrical power unit
OP1	Enhanced security return circuit by 2 solenoid valves
CS2EV	Monitoring device of the 2 solenoid valves (of OP1)
OP1-OP2	Manual lowering with a dead man safety device.

OP1-OP3	Manual lowering with overspeed safety by solenoid valve 24VDC.
OP4	Indicator switch of the position of the control valve(s)
OP5	Visual (OP5) or electrical (OP5E) clogging Indicator
OP6	HPP for iron and steel industry
OP7	Electrical indicator of oil temperature
OP8	Electrical indicator of oil minimum level
OP10	Drip tray for horizontal HPP
Y5	Regulated braking




Weight : 66 kg without oil
Model : CE12L-H
(horizontal position)
Dimensions in mm



DISC BRAKE - CE12L HYDRAULIC POWER PACK

Revision number: T10001-01-F

Revision date: 26.02.2015



Electrical data:

Motor M

230/400VAC 50Hz 4 kW
4 poles 3000rpm

For mains 3 phases

Frequency 50 Hz
220-230-240VAC $\pm 10\%$ 50Hz
380-400-415VAC $\pm 10\%$ 50Hz
Frequency 60 Hz
220-230-240VAC $\pm 10\%$ 60Hz
440-460-480VAC $\pm 10\%$ 60Hz


Solenoid valve EV1

Coil under 230VRAC 50 or 60 Hz
single phase, 20W
Protection IP55

Pressure switch CP1

- Single-pole and snap-acting contact "OC"
- Protection: IP 66
- 240 V AC. 1.5 A
- 250 V DC. 0.1 A

Flow diagram



SIME Brakes Industrial Braking Systems

Hydraulic Power Packs

DISC BRAKE - ST210 HYDRAULIC POWER PACK

Revision number: T05100-01-A

Revision date: 20.04.2002

Maximal utilization pressure : 225 bars

Reservoir volume : 78 L :

minimum oil volume = 42 L

maximum oil volume = 63 L

Operating conditions:

- Ambient temperature: -10°C to +50°C
- Relative humidity: ≤ 70%
- Particle size ≥ 40µm
- Protection required against direct harm such as vertical falling waters, sea spray or flams.

Other conditions: consult us.




Association with the calipers :

ST210-20	SH25-2, SH18B
ST210-17	SH15-3
ST210-15	SH25-1
ST210-13	SH15-2
ST210-10	SH15-1

Options :

MS	50 Hz : 240/415 V - 500 V 60 Hz : 260/460 V - 254/440 V
EVS	EV coils voltage different from the standard
K	Electrical unit (consult us)
OP1	Enhanced security return circuit by 2 solenoid valves
OP1-OP2	Manual lowering with a dead man safety device.
OP1-OP3	Manual lowering with overspeed safety by solenoid valve 24VDC.

OP4	Indicator switch of the position of the control valve(s)
OP5	Visual (OP5) or electrical (OP5E) clogging Indicator
OP6	HPP for iron and steel industry
OP7	Electrical indicator of oil temperature
OP8	Electrical indicator of oil minimum level
OP9	Output pressure switch




Weight without oil: 125 kg.
Dimensions in mm

DISC BRAKE - ST210 HYDRAULIC POWER PACK

Revision number: T05100-01-A

Revision date: 20.04.2002



Electrical data:

Motor

230/400VAC $\pm 5\%$ 50Hz 4 kW
280/480VAC $\pm 5\%$ 60Hz
4 poles 3000 rpm
Protection: IP 55 classe F

Solenoid valves

- Power: 17 W, coil class H.
- 12 and 24 VDC.
- 24VRAC, 110VRAC and 220VRAC


Pressure switch

- Cable gland PG11
- Protection: IP 65
- Watertight housing
- Terminal box

For mains 3 phases

Frequency 50 Hz
220-230-240VAC $\pm 10\%$ 50Hz
380-400-415VAC $\pm 10\%$ 50Hz
Frequency 60 Hz
220-230-240VAC $\pm 10\%$ 60Hz
440-460-480VAC $\pm 10\%$ 60Hz


Flow diagram



SIME Brakes Industrial Braking Systems

Safety systems

CONTROL AND SAFETY SYSTEMS



BRAKING SOLUTIONS FOR	APPLICATIONS
<ul style="list-style-type: none"> MONITORING THE HOISTING SPEED REGULATED DECELERATION SPEED REGULATION CONTROL CONSTANT DECELERATION SAFETY PERFORMANCE LEVEL PL d to PL e 	<ul style="list-style-type: none"> MASS TRANSPORTS : CABLEWAY, PASSENGERS ELEVATORS FUNICULARS, CHAIRLIFTS... STEEL INDUSTRY LADLE CRANE BELT CONVEYORS




SIDEOS One

- SAFETY SYSTEM
- configurable and secure module for speed monitoring.
- fitted with an efficient auto-control system.



CRD® / CRV®


- CONTROL SYSTEMS
- speed regulation with **CRV®** module.
- setting of the deceleration rate on the **CRD®** module.



AFR5

- MONITORING. CONTROL SYSTEMS for regulated braking.
- SAFETY SYSTEMS adapted to the customer installation.
- includes **SIDEOS One** and **CRD®** modules

ASSOCIATION OF 2 SIDEOS One - Detection of any kinematic linkage break



SIME Brakes Industrial Braking Systems

Safety systems

SAFETY SYSTEMS - SIDEOS ONE

Revision number: M10054-01-E

Revision date: 16.11.2018

Configurable and secure system for speed monitoring: redundant design and fault detection system (DC>99%) which secure the overall operation of the overspeed detection system.

Conform to the machine security standards :

NF EN ISO 13489-1

Performance level PL=d to PL=e

Category : 2 to 4

MTTFd = high DC = high

Operating conditions :

- Ambient temperature : -20°C to +60°C
- IP65 protected electrical casing

Electrical data :

- 2 versions
AC : 115/230 VAC ± 10% 50/60Hz or
DC : 24 VDC ± 15%
- Other voltages : consult us


EC marking of conformity :

- 2006/42/EC directive Machine
- 2014/35/UE Low voltage directive (standard NF EN 60204-1)
- 2014/30/UE EMC directive (standards NF EN 61000-6-2, NF EN 61000-6-4)

Options :

- Steel casing IP66 IK10
- Contact module

The **SIDEOS One** can be installed in a control enclosure on an DIN rail of 35mm, or fixed with M5 screws, see the drawing below.



In case of heavy vibrations, it is recommended to fasten the **SIDEOS One** on elastic buffers.

SAFETY SYSTEMS - SIDEOS ONE

Revision number: M10054-01-E

Revision date: 16.11.2018

The SIDEOS One is a configurable system for speed monitoring designed to secure the lifting of a handling equipment.

> It is set according to:

	Parameters
- The lifting characteristics	NC NS DT
- The selected functions	SP1-SP2-SP3 TS TS and DS RC
- The number of pulses to confirm an Overspeed	VS1 VS2 VS3
• Validation Overspeed 1, Static and Dynamic Slippings	
• Validation Overspeed 2	
• Validation Overspeed 3 and kinematic chain break	



Access to the parameters is protected by a locking mode.

> It receives:

- The speed signal(s) of the installation
- The functional orders of the lifting control of the handling equipment

> It monitors:	and detects, in case of wrong operation:
- the lifting speed(s)	- an Overspeed
- the lifting stop (deceleration)	- a Static Slipping
- the lifting stop positioning	- a Static Slipping
- the lifting operation direction	- a Dynamic Slipping
- the lifting kinematic chain	- a Differential Speed
- the encoder	- an encoder fault
- the functional orders of the control	- a Speed contact fault
- the output contactors or relays	- a contactor fault

> When it detects a fault, it pilots:

- the opening of the independent output contactors, their power contacts being inserted in the supply circuit of the safety brakes.

> It signals the triggering origin:

- via the alphanumeric display
- an auxiliary contact of the output contactors

> It secures the global operation of the speed monitoring system by means of:

- its redundant internal and external design and its monitoring system (DC > 99%) which allow the detection of all the internal and external failures.

> It records:

- The opening of the output contactors or relays and this even in case of power cut
- The 3 last Fault message

> It releases:

- the fault when the RESTART button is manually actuated, this action allows the control system to receive a distinct starting order.

It allows to obtain
a secured speed monitoring system
Category 2 PL d up to Category 4 PL e
according to the standard NF EN ISO 13849-1.

SIME Brakes Industrial Braking Systems


Safety systems

SAFETY SYSTEMS - SIDEOS ONE

Revision number: M10054-01-E

Revision date: 16.11.2018

Internal design



> External failures

The monitoring system of the **SIDEOS One** is designed to detect all the external signals failures by means of a redundant or logic treatment of the input signals.

It secures the operation of the speeds inputs, the contacts inputs, the System Fault outputs and the Overspeed outputs (DCavg>99%).

> Internal failures

The **SIDEOS One** detects all the internal faults (DCavg>99%), either during the operation, or during the AUTOTEST.

Faults, detected only during the AUTOTEST, do not lead to loss the safety function thanks to the redundant internal design.

It ensures :

- a cross-monitoring of its internal operation
- a dynamic test of the overspeed function every 360 pulses of the encoder
- the control of validity of the memories

> Cut-off and safe connection of the System Fault and Overspeed outputs supply

The **SIDEOS One** system, that cuts off the supply of the System Fault and Overspeed outputs, is designed to switch off the output supply whatever the fault present on the output.

> Autotest

The Autotest triggers automatically at power on (time 1.5s) or at a manual starting-up (RESTART) following a triggering of a **SIDEOS One** output (time 1s).

The AUTOTEST allows a global checking and ensures the **SIDEOS One** to operate correctly, if the AUTOTEST is validated.

NOTES

SIME Brakes Industrial Braking Systems

Safety systems

SAFETY SYSTEMS - CONSTANT DECELERATION CRD MODULE

Revision number: M08950-01-C

Revision date: 03.06.2015

1 - PRESENTATION

The CRD® module, combined with **5KE, 650E, TY5, TH** and **SH** type brakes allows a constant deceleration regulated braking (fig. 1) whatever the speed, the load and the kind of load, driving or resisting.

Applications: cableways, chairlifts, funiculars, lifts, belt conveyors, transporters

2 - PRINCIPLE

CRD® system (fig. 2) consists of:

- 1 or more brakes (progressive brakes type **5KE, 650E, TY5, TH** and **SH**).
- 1 hydraulic pack (**STE210Y5, CE8L-RY5**) or 1 electric power supply (AB8, ATP2, ATP24).
- 1 (or more) speed sensors (tachometric dynamo..).
- 1 **CRD®** module, it may be integrated into an **AFR5** enclosure supplied by Stromag France.

Two CRD® versions exist:

- **CRD-R**: a deceleration regulation board (fig.8) monitors power units type AB8, ATP2, ATP24 or an electronic amplifier for a proportional pressure limiter of an hydraulic power unit, customer supply the reference speed signal.
- **CRD-RC**: to the regulation board is connected a deceleration control board, fully independant from the regulation board (power suply, speed signal, scale and command).

Fig. 1





Fig. 2



SAFETY SYSTEMS - CONSTANT DECELERATION CRD MODULE

Revision number: M08950-01-C

Revision date: 03.06.2015

3 - OPERATION


3-1 Deceleration regulation

CRD® module allows a deceleration regulation according to a scale at the time of a normal or an emergency braking.

3-2 Deceleration control (CRD-RC version only)

Using a second speed sensor connected to "deceleration fault control board" insures that first board operating is correct (detected mis-functioning: braking is too low or too high, mechanical shaft or gear box failure, failure of a speed sensor or damaged wires).


Fig. 3



3-3 "S" curve deceleration

CRD® module allows user to select JERKS at begining and/or end of braking; duration of these "S" curves may be adjusted.


Fig. 4



3-4 Lowering

CRD® module provides lowering function (load is let down on command after a full successful braking, for security purpose) to X % of nominal speed (setting between 5 and 20%), at constant speed, or at variable speed (operator controlled auto "0" recentering joystick).

Fig. 5



Safety systems

SAFETY SYSTEMS - CONSTANT DECELERATION CRD MODULE

Revision number: M08950-01-C

Revision date: 03.06.2015

4 - PHYSICAL CHARACTERISTICS OF CRD® MODULE

This equipment receives speed signal from the speed sensor(s) and delivers an output signal (0...10V.) while following an internal or external speed scale. board(s) are:

4-1 In separate casing

- **dimensions:** see fig. 6a (**CRD-R**) & fig. 6b (**CRD-RC**); Location - enclosure must be installed onto a vertical support - will allow natural ventilation.
- **Environment:** Ambient temperature: -10°C to +50°C.
- The IP 559 casing is equipped with 5 cable glands PG 11 (**CRD-R**) or 5 cable glands PG 11 and 4 cable glands PG 9 (**CRD-RC**).
- **Mains power supply:** 230V AC ±10% 50/60Hz or 24V DC (20 to 30 V DC). Power consumption: 5W maxi. per board.

4-2 Inside control casing

- **dimensions:** see fig. 7a (**CRD-R**) & fig. 7b (**CRD-RC**);
- **Environment:** Ambient temperature: -10°C to +50°C.
- **Mains power supply:** 230V AC ±10% 50/60Hz or 24V DC (20 to 30 V DC). Power consumption: 5W maxi. per board.

5 - EQUIPMENT

Necessary equipment for braking will include:

5-1 Brakes

1.2. 4.... electrohydraulic calipers (type **TY5**, **TH** or **SH**) or electromagnetic (type **650E**, **5KE**).

5-2 Electric power supply (case of electromagnetic brakes)

Power supply associated to the brake will be capable of braking regulation (type **AC64-50** associated with **AB8** module).

5-3 Hydraulic power pack (hydraulic brakes SH or TH type)

Hydraulic power pack will be capable of regulating deceleration (for example: **STE 210 Y5** with proportional pressure limiter). An alternate motor may optionally be added (24 V. DC) to the main motor supplied by Mains, allowing deceleration regulation in case of Mains failure (**M2** option).

5-4 AFR5 Control casing (SH and TH brakes)

Initiate deceleration regulation, controls its logics and faults to keep all electrical components secure.

5-5 Back-up power supply (M2 option)

In case of mains failure, the need for deceleration regulation may involve installing a back-up power supply - Stromag France or customer supplied.

Fig. 6a




Fig. 6b




Fig. 7a





Fig. 7b




SAFETY SYSTEMS - CONSTANT DECELERATION CRD MODULE

Revision number: M08950-01-C

Revision date: 03.06.2015

Fig. 8

DECELERATION REGULATION BOARD



SIME Brakes Industrial Braking Systems

Safety systems

SAFETY SYSTEMS - SPEED REGULATION CRV MODULE

Revision number: M08955-01-B

Revision date: 03.06.2015

1 - PRESENTATION

Speed regulation with **CRV**, in combination with brakes type **5KE, 650E, TY5, TH** and **SH**, provides a regulated speed braking whatever the load quantity and load specificity, pulling or resisting.

Use: lowering, speed regulation.

Applications: cableways, chairlifts, funiculars, lifts, belt conveyors, transporters, cranes, etc...

2 - PRINCIPLE


CRV system (fig. 1) consists of:

- 1 or more brakes (progressive brakes type **5KE, 650E, TY5, TH** and **SH**);
- 1 hydraulic pack (**STE210Y5, CE8L-RY5**) or 1 electric power supply (AB8, ATP2, ATP24);
- 1 (or more) speed sensors (tachometric dynamo..);
- 1 **CRV** module, it may be integrated into an AFR5 enclosure supplied by Stromag France.

Two **CRV®** versions exist:

- **CRV-R**: a speed regulation board (fig. 8) monitors power units type AB8, ATP2, ATP24 or an electronic amplifier for a proportional pressure limiter of an hydraulic power unit ; customer suply the reference speed signal.
- **CRV-RC**: to the regulation board is connected a speed control board, fully independant from the regulation board (power suply, speed signal, scale and command).

Fig. 2



SAFETY SYSTEMS - SPEED REGULATION CRV MODULE

Revision number: M08955-01-B

Revision date: 03.06.2015

3 - OPERATION

3-1 Lowering - fig.2

CRV module allows choosing a lowering (regulated load lowering after stop. for security purpose) at X % of nominal speed, (setting between 5 and 20%), at constant speed, or at variable speed (potentiometer with automatic "0" restoring adjusted by operator).

3-2 Speed regulation - fig.3

CRV module allows a speed regulation set at X% of nominal speed (constant speed, factory set between 5 and 100% of nominal speed), failure of a speed sensor or damaged wires).

3-3 Speed control (CRV-RC only)

Using an additional speed sensor connected to "speed control" board allows a monitoring of the regulation (detected anomalies: speed too high or too low, mechanical breakdown of shafts or gearbox, speed sensor anomaly or damaged wiring).

Fig. 2





Fig. 3



Safety systems

SAFETY SYSTEMS - SPEED REGULATION CRV MODULE

Revision number: M08955-01-B

Revision date: 03.06.2015

4 - PHYSICAL CHARACTERISTICS OF CRV® MODULE

This equipment receives speed signal from the speed sensor(s) and delivers an output signal (0...10V.) while following an internal or external speed scale. board(s) are:

4-1 In separate casing

- **dimensions:** see fig. 4 (**CRV-R**) & fig. 5 (**CRV-RC**); Location - enclosure must be installed onto a vertical support - will allow natural ventilation.
- **Environment:** Ambient temperature: -10°C to +50°C.
- The IP 559 casing is equipped with 5 cable glands PG 11 (**CRV-R**) or 5 cable glands PG 11 and 4 cable glands PG 9 (**CRV-RC**).
- **Mains power supply:** 230V AC ±10% 50/60Hz or 24V DC (20 to 30 V DC). Power consumption: 5W maxi. per board.

4-2 Inside control casing

- **dimensions:** see fig. 6 (**CRV-R**) & fig. 7 (**CRV-RC**);
- **Environment:** Ambient temperature: -10°C to +50°C.
- **Mains power supply:** 230V AC ±10% 50/60Hz or 24V DC (20 to 30 V DC). Power consumption: 5W maxi. per board.

5 - EQUIPMENT

Necessary equipment for braking will include:

5-1 Brakes

1.2. 4.... electrohydraulic calipers (type **TY5**, **TH** or **SH**) or electromagnetic (type **650E**, **5KE**).

5-2 Electric power supply (case of electromagnetic brakes)

Power supply associated to the brake will be capable of braking regulation (type **AC64-50** associated with **AB8** module).

5-3 Hydraulic power pack (hydraulic brakes SH or TH type)

Hydraulic power pack will be capable of regulating deceleration (for example: **STE 210 Y5** or **CE8L-Y5** with proportional pressure limiter). On the **STE210Y5**, to the main motor supplied by Mains, an alternate motor may optionally be added (24 V. DC) to the main motor supplied by Mains, allowing speed regulation in case of Mains failure (**M2** option).

5-4 AFR5 Control casing (SH and TH brakes)

Initiate speed regulation, controls its logics and faults to keep all electrical components secure.

5-5 Back-up power supply (M2 option)

In case of mains failure, the need for speed regulation may involve installing a back-up power supply - Stromag France or customer supplied.

Fig. 4




Fig. 5




Fig. 6





Fig. 7




SAFETY SYSTEMS - SPEED REGULATION CRV MODULE

Revision number: M08955-01-B

Revision date: 03.06.2015

Fig. 8

SPEED REGULATION BOARD



Switches list

- S2: speed signal frequency range
- S3: speed signal selection: voltage or frequency
- S4: selection of speed signal amplification
- S5: speed signal filtration
- S9: regulation amplification = function P
- S10: TP16 output manual command to 10V. (black push button)
- S11: regulation filtration = fonction I
- S12: AB8 or ATP output selection
- S13: internal/external lowering potentiometer selection
- S15: regulation filtration = fonction I
- S16: regulation derivative = fonction D
- S17: TP16 output manual command to 0.3 V + action on S10 (black pushbutton)

Potentiometers list

- PT1: (factory setting)
- PT2: speed signal adjustment
- PT3: speed signal amplification
- PT6: internal potentiometer for scale
- PT8: speed is nil setting
- PT9: Ajustment of function D
- PT10: Maximum value adjustment of the external potentiometer

SIME Brakes Industrial Braking Systems

Safety systems

SAFETY SYSTEMS - AFR5 CONTROL ENCLOSURES

Revision number: M10105-01-E

Revision date: 03.06.2015

AFR5 control enclosures are designed for controlling and monitoring regulated braking systems.

They allow different braking modes :

- Constant deceleration (**CRD®** module)
ex. : Cableway : Pic du Midi (Bagnères de Bigorre)
- Constant deceleration and speed regulation (**CRD®** module)
ex. : Passengers elevator : Eiffel Tower in Paris
- Normal operation (AoN) and speed regulation for load lowering (**CRV®** module)
ex. : Steel industry ladle crane : HKM (Deutschland)

They can be designed to ensure a safety performance level up to PL d to the braking system.

They can includes :


- an Ethernet line towards the customer PLC,
- the braking management in case of power supply loss or regulated braking fault,
- the speed monitoring (**SIDEOS One**),
- the control of standby brakes or/and Hydraulic Power Packs to ensure the operation continuity in case of failure of one part of the braking system,
- a Human Machine Interface or Module.



Here is, for example, the diagram of the AFR5-HKM enclosure :

All or Nothing braking - Load lowering - Performance level PLd - Standby brakes - Data transmission to the customer PLC via ProFibus and secured ProFibus.

AFR5-HKM enclosure principle





SAFETY SYSTEMS - AFR5 CONTROL ENCLOSURES

Revision number: M10105-01-E


Revision date: 03.06.2015

HKM Braking System monitored and controlled by AFR5-HKM enclosure



Discs & drums

DISCS & DRUMS



MAIN CHARACTERISTICS

- DISCS ARE AVAILABLE ALONE OR WITH HUBS
- ALL DISCS CAN BE ASSOCIATED WITH THE DIFFERENT TYPES OF FLEXIBLE COUPLINGS
- DESIGNED TO RUN AT PERMANENT TEMPERATURE OF 200°C
- DRUMS ARE AVAILABLE ALONE OR WITH HUB
- DRUMS ARE ASSOCIATED WITH THE SIME BRAKES TYPES FNS AND SDB STANDARD DIN 15435



MONOBLOC & SOLID DISCS

- for low energy applications.



AUTO-VENTILATED DISCS

- comply with NF S 472 B standard.
- for high frequency and heavy duty braking cycles.
- high capacity of energy dissipation.



DRUMS

- flanged hub fitted with rubber bushes.
- uniform distribution of loads. even in case of misalignment.
- reduction of resonance effects at critical velocity.

Discs thicknesses and diameters

DISCS	Diameter →	Ø 175	Ø 220	Ø 260	Ø 315	Ø 355	Ø 395	Ø 445	Ø 495	Ø 550	Ø 625	Ø 705	Ø 795	Ø 995
SOLID	Th. 15 mm													
MONOBLOC	Th. 30 mm													
VENTILATED	Th. 30 mm													
	Th. 42 mm													

Drums widths and diameters

DRUMS	Diameter	Ø 160	Ø 200	Ø 250	Ø 315	Ø 400	Ø 500	Ø 630	Ø 710
DRUMS	Width	60	75	95	118	150	190	236	265

SIME Brakes Industrial Braking Systems

Discs & drums

DISC BRAKE - DISCS

Revision number: T08020-01-F

Revision date: 27.07.2017

DISCS OF BRAKES CHARACTERISTICS

1 - Dimensions

Refer to leaflets "Technical data and dimensions" relevant to the type of disc used.

For a new disc, the tolerance of the thickness dimension is :

±0.15

2 - Materials

Ventilated discs : Cast iron type EN-GJS-400-18-LT ou EN-GJS-350-22

Solid discs : Steel S355 K2

Hubs : Steel 25/34/42CrMo4

3 - Surface quality of the contact zone with lining (table 1)

Friction surface : Ra 1.6 to 3.2 in all directions
Centring zone : Idem

4 - Balancing

Only bare discs (except monoblocs).

Discs are balanced in "static" quality G6.3 :

- at the speed of 1800 rpm for discs $\varnothing \leq 550$ mm.
- at the maximum speed indicated in the "technical data" leaflets for discs $\varnothing > 550$ mm

The correction area is placed between the hub and the little diameter of the friction surface (see table 1).

For balancing with hub, with half-coupling or at high speed, consult us.

Table 1 - Dimensions of the friction surface

EXTERNAL DIAMETER	INNER DIAMETER				
	Thickness 15		Thickness 30		Thickness 42
	Monobloc disc	Monobloc disc	Ventilated disc	Solid disc	Ventilated disc
175	85	---	---	---	---
220	105	90	---	---	---
260	132	136	---	---	---
315	130	180	165	130	---
355	---	---	206	155	---
395	157	---	246	246	---
445	207	---	216	185	---
495	300	---	256	256	---
550	350	---	325	314	---
625	430	---	387	387	370
705	---	---	462	462	---
795	---	---	542	542	542
995	---	---	---	600	745

DISC BRAKE - DISCS

Revision number: T08020-01-F

Revision date: 27.07.2017

5 - Wear limit before the replacement of the disc

DANGER !

In case of an excessive wear of the disc the brake can operate out of its nominal range of setting and consequently lead to a loss of braking force.



The table 2 sums up the discs minimum thicknesses as before their replacement.

Table 2

Type of disc	Thickness unused (± 0.15) mm	Minimum thickness before replacement mm	Minimum web before replacement mm
Monobloc discs	30	27	6.5
Ventilated discs	30	27	6
	42	39	with core of 16 : 11 with core of 23 : 8
Solid discs	15	13	
	30	27	
	42	39	

Discs & drums


DISC BRAKE - MONOBLOC DISCS

Revision number: T02160-01-A

Revision date: 02.05.2003

Diameters: 220, 260 and 315 mm.

Thickness: 30 mm.




Designation	Ø	220 M 30	260 M 30	315 M30
J	kg/m ²	0.055	0.070	0.14
Weight	kg	11.2	10	12
Maximum speed	rpm	4300	3600	3000
d max. keyed shrink fit	mm	55	55	60
	mm	55	55	60

DISC BRAKE - SOLID DISCS

Revision number: T02100-01-A

Revision date: 01.03.2001

Thickness: 15 mm



Designation	175 P 15	220 P 15	260 P 15	315 P 15	395 P 15	445 P 15	495 P 15	550 P 15	625 P 15
J kg/m ²	0.01	0.03	0.06	0.13	0.30	0.48	0.77	1.16	1.93
Weight kg	4	7.6	13	18	24	28	43	49	59
Maximum speed tr/mn	5000	4300	3600	3000	2400	2100	1900	1800	1500
D mm	175	220	260	315	395	445	495	550	625
D ₁ mm	75	95	120	120	120	120	150	150	150
D ₂ mm	-	-	-	130	200	207	257	312	387
L mm	55	65	85	102	102	102	135	135	135
L ₁ mm	62.5	72.5	92.5	117	117	117	150	150	150
d max. keyed mm	0-40	0-55	0-75	0-75	0-75	0-75	0-100	0-100	0-100
shrink fit mm	40	65	80	80	80	80	100	100	100

SIME Brakes Industrial Braking Systems

Discs & drums

DISC BRAKE - VENTILATED AND SOLID DISCS


Revision number: T02220-01-B

Revision date: 26.11.2010

Diameter from 315 to 995 mm for solid discs P30
 Diameter from 315 to 795 mm for ventilated discs V30
 Thickness : 30mm

Material of discs and hubs
 Protection of discs
 Balancing
 Note : hubs are not balanced.

see leaflet T08020-01



Designation	Type	315		355		395		445		495		
		P30	V30	P30	V30	P30	V30	P30	V30	P30	V30	
J	Disc + hub	kg.m ²	0.234	0.148	0.379	0.243	0.588	0.352	0.94	0.581	1.492	
	Bare disc	kg.m ²	0.225	0.139	0.362	0.226	0.56	0.324	0.896	0.537	1.367	
Weight	Disc + hub	kg	21.7	14.7	27.5	18.5	34	23	46.5	31.5	65	
	Bare disc	kg	17	10	21	12	27	16	34	19	41	
Maximum speed	rpm	3000		2700		2400		2100		1900		
Maximum braking torque ■	N.m	1720		2987		4594		8798		14321		
D	mm	315		355		395		445		495		
D1	mm	139		172		177		184		230		
D2	mm	125		145		165		175		220		
D3	mm	105		125		140		146		190		
D4	mm	85		105		115		120		160		
D5	mm	80		95		105		110		150		
D6	mm	-	-	-	173	-	246	-	-	-	256	
D7	mm	-	-	-	151	-	171	-	-	-	226	
L	mm	102		102		102		135		135		
L1	mm	107		107		107		140		140		
L2	mm	127		129		131		166		168		
L3	mm	87		87		87		120		120		
L4	mm	28		28		28		30		38		
Bore	keyed	mm	50		60		70		75		100	
maxi. d ***	shrink fit	mm	50		60		70		75		100	
d1	mm	M10		M12		M14		M16		M18		
d2	mm	76.5		96.5		106.5		111.5		151.5		
d3	mm	M10		M12		M14		M16		M18		
N		9	9	9	9	9	12	12	12	12	12	
Tightening torque β	N.m	49		86		135		210		290		

- Maximum braking torque allowed by the bolts of disc and hub assembling.



ATTENTION !

The torque transmissible by shaft and keying must be checked.

** Tolerance on d and keying on Customer demand.

DISC BRAKE - VENTILATED AND SOLID DISCS

Revision number: T02220-01-B


Revision date: 26.11.2010

Diameter from 315 to 995 mm for solid discs P30
 Diameter from 315 to 795 mm for ventilated discs V30
 Thickness : 30mm

Material of discs and hubs
 Protection of discs
 Balancing

see leaflet T08020-01

Note : hubs are not balanced.



Designation	Type	550		625		705		795		995
		P30	V30	P30	V30	P30	V30	P30	V30	P30
J	Disc + hub kg.m ²	2.22	1.28	3.676	2.23	5.99	3.76	9.72	6.14	23.86
	Bare disc kg.m ²	2.09	1.15	3.506	2.06	5.69	3.46	9.23	5.65	22.51
Weight	Disc + hub kg	76	53	87.5	60.5	105	72	175.5	135.5	243
	Bare disc kg	52	29	68	41	86	53	110	70	170
Maximum speed	rpm	1800		1500		1300		1200		900
Maximum braking torque ■	N.m	14321		19915		27905		36384		73897
D	mm	550		625		705		795		995
D1	mm	275		343		418		498		-
D2	mm	220		235		265		300		380
D3	mm	190		205		230		260		330
D4	mm	160		170		195		220		280
D5	mm	150		150		180		210		260
D6	mm	-	314	-	387	-	462	-	542	-
D7	mm	-	226	-	246	-	271	-	310	-
L	mm	135		135		135		135		135
L1	mm	140		140		140		140		140
L2	mm	168		170		172		174		174
L3	mm	120		120		120		120		120
L4	mm	38		38		40		40		40
Bore maxi. d ** keyed	mm	100		100		125		140		180
d1	mm	M18		M20		M22		M24		M30
d2	mm	151.5		161.5		185.5		211.5		211.5
d3	mm	M18		M20		M22		M24		M30
N		12		12		12		12		12
Tightening torque β	N.m	290		410		550		710		1450

■ Maximum braking torque allowed by the bolts of disc and hub assembling.



ATTENTION !

The torque transmissible by shaft and keying must be checked.

** Tolerance on d and keying on Customer demand.

SIME Brakes Industrial Braking Systems

Discs & drums

DISC BRAKE - VENTILATED AND SOLID DISCS


Revision number: T02220-01-B

Revision date: 26.11.2010

Diameter 625 - 795 - 995
Thickness : 42mm

Material of discs and hubs
Protection of discs
Balancing
Note : hubs are not balanced.

see leaflet T08020-01



Designation	Type	625V42	795V42	995V42
J	Disc + hub kg.m ²	2.92	7.85	21.3
	Bare disc kg.m ²	2,5	6,5	20
Weight	Disc + hub kg	90	150	250
	Bare disc kg	45	77	177
Maximum speed	tr/mn	1500	1200	900
Maximul braking torque ■	N.m	36 384	73 897	73 897
D	mm	625	795	995
D1	mm	302	486	694
D2	mm	300	380	380
D3	mm	260	330	330
D4	mm	220	280	280
D5	mm	210	260	260
D6	mm	370	542	745
D7	mm	-	-	-
L	mm	141	141	141
L1	mm	140	140	140
L2	mm	186	186	186
L3	mm	120	120	120
L4	mm	40	40	40
Bore	mm	40-140	40-180	40-180
maxi. d *** keyed shrink fit	mm	140	180	180
d1	mm	M24	M30	M30
d2	mm	211	211	211
d3	mm	M24	M30	M30
N		12	12	12
Tightening torque β	N.m	710	1450	1450

■ Maximum braking torque allowed by the bolts of disc and hub assembling.

ATTENTION !
STOP The torque transmissible by shaft and keying must be checked.

*** Tolerance on d and keying on Customer demand.

NOTES

SIME Brakes Industrial Braking Systems

Discs & drums

DISC BRAKE - VENTILATED / SOLID DISCS - LONG HUBS

Revision number: T02222-01-D


Revision date: 07.01.2014

For TDXB and FAV brakes

MLP - diameter from 355 to 995 mm for solid discs P30
 MLV - diameter from 355 to 795 mm for ventilated discs V30
 Thickness : 30mm

Material of discs and hubs
 Protection of discs
 Balancing
 Note : hubs are not balanced.

see leaflet T08020-01



Designation	Type	315		355		395		445		495		550	
		P30	V30										
J	Disc + hub kg.m ²	0.245	0.159	0.382	0.246	0.593	0.357	0.946	0.587	1.515	0.991	2.243	1.303
	Bare disc kg.m ²	0.225	0.139	0.362	0.226	0.56	0.324	0.896	0.537	1.367	0.843	2.09	1.15
Weight	Disc + hub kg	22.5	15.5	30.5	21.5	37.6	26.6	51	36	73	55	84	61
	Bare disc kg	17	10	21	12	27	16	34	19	41	23	52	29
Maximum speed	rpm	3000		2700		2400		2100		1900		1800	
Maximum braking torque ■	N.m	1720		2987		4594		8798		14321		14321	
D	mm	315		355		395		445		495		550	
D1	mm	139		172		177		184		230		275	
D2	mm	125		145		165		175		220		220	
D3	mm	105		125		140		146		190		190	
D4	mm	85		105		115		120		160		160	
D5	mm	80		95		105		110		150		150	
D6	mm	-	-	-	173	-	246	-	-	-	256	-	314
D7	mm	-	-	-	151	-	171	-	-	-	226	-	226
L	mm	135		155		155		195		195		195	
L1	mm	140		160		160		200		200		200	
L2	mm	160		182		182		226		228		228	
L3	mm	120		140		140		180		180		180	
L4	mm	28		28		28		30		38		38	
Bore maximum d keyed **	mm	50		60		70		75		100		100	
d1	mm	M10		M12		M14		M16		M18		M18	
d2	mm	76.5		96.5		106.5		111.5		151.5		151.5	
d3	mm	M10		M12		M14		M16		M18		M18	
N		9		9		9		12		12		12	
Tightening torque	N.m	49		86		135		210		290		290	

■ Maximum braking torque allowed by the bolts of disc and hub assembling.



ATTENTION !

The torque transmissible by shaft and keying must be checked.

** Tolerance on d and keying on Customer demand.

DISC BRAKE - VENTILATED / SOLID DISCS - LONG HUBS

Revision number: T02222-01-D

Revision date: 07.01.2014

For TDXB and FAV brakes


MLP - diameter from 355 to 995 mm for solid discs P30
 MLV - diameter from 355 to 795 mm for ventilated discs V30
 Thickness : 30mm

The discs 625-2 and 705-2 are with the same hub and fixing than 795.

Material of discs and hubs
 Protection of discs
 Balancing

see leaflet T08020-01

Note : hubs are not balanced.



Designation	Type	625		625-2		705		705-2		795		995	
		P30	V30	P30	V30	P30	V30	P30	V30	P30	V30	P30	
J	Disc + hub Bare disc	kg.m ² kg.m ²	3.699 3.506	2.253 2.06	4.02 3.45	2.574 2.004	6.038 5.69	3.808 3.46	6.13 5.62	3.9 3.39	9.802 9.23	6.222 5.65	23.9 22.5
Weight	Disc + hub Bare disc	kg kg	96 68	69 41	116.5 63	89.5 36	117 86	84 53	136 82.5	103 49.5	191 110	151 70	271 170
Maximum speed	rpm	1500		1500		1300		1300		1200		900	
Maximum braking torque ■	N.m	19915		36384		27905		36384		36384		73897	
D	mm	625		625		705		705		795		995	
D1	mm	343		343		418		418		498		-	
D2	mm	235		300		265		300		300		380	
D3	mm	205		260		230		260		260		330	
D4	mm	170		220		195		220		220		280	
D5	mm	150		210		180		210		210		260	
D6	mm	-		387		-		462		462		-	
D7	mm	-		246		-		271		440		-	
L	mm	195		195		195		195		195		235	
L1	mm	200		200		200		200		200		244	
L2	mm	230		234		232		234		234		280	
L3	mm	180		180		180		180		180		220	
L4	mm	38		40		40		40		40		50	
Bore maximum d keyed **	mm	100		140		125		140		140		180	
d1	mm	M20		M24		M22		M24		M24		M30	
d2	mm	161.5		161.5		185.5		185.5		211.5		211.5	
d3	mm	M20		M24		M22		M24		M24		M30	
N		12		12		12		12		12		12	
Tightening torque β	N.m	410		710		550		710		710		1450	

■ Maximum braking torque allowed by the bolts of disc and hub assembling.



ATTENTION !

The torque transmissible by shaft and keying must be checked.

** Tolerance on d and keying on Customer demand.

SIME Brakes Industrial Braking Systems

Discs & drums


DRUM BRAKE - DRUMS SERIE PB & PB-C

Revision number: T01350-01-C

Revision date: 25.05.2018

Drums material :

$\varnothing A \leq 400$ mm : EN-GJL-250
 $\varnothing A > 400$ mm : EN-GJS-500-7



Designation		PB or PB-C...	200	250	315	400	500	630	710
J <input checked="" type="checkbox"/>	coupling + drum	kgm^2	0.062	0.156	0.426	1.310	4.02	10.82	21.45
	drum alone	kgm^2	0.052	0.137	0.393	1.229	3.718	10.518	19.958
Weight <input checked="" type="checkbox"/>	coupling + drum	kg	16.1	27.7	43.5	83	160	235	415
	drum alone	kg	12.5	22.6	35.9	70.1	130.5	205.5	333.4
Nominal torque		Nm	400	630	1000	2500	6100	6100	21000
Rotation speed nmax. *		rpm	3400	2750	2200	1700	2200	1800	1500
Dimensions in mm	A		200	250	315	400	500	630	710
	B		183.5	223.5	248.5	299	404	429	515.5
	E		3.5	3.5	3.5	4	4	4	5.5
	L2		60	75	90	110	150	150	220
	L3		120	145	155	185	250	275	290
	L7 min		72	87	93	110	150	165	175
	M2		21.5	36.5	51.5	51	91	91	148
	N2		95	116	127	160	202	202	290
	N3		95	116	127	160	202	202	195
	Q		155	175	200	245	315	315	460
	U		75	95	118	150	190	236	265
	R2		80	95	105	135	165	165	232
	R3		80	95	105	135	165	165	165
	W2		M8	M10	M10	M12	M12	M12	M20
	W3		M10	M12	M12	M16	M20	M20	M20
Bores in mm		D2	min / max <input checked="" type="radio"/>	19/60	28/75	35/80	35/100	100/125	100/125
		D3	min / max <input checked="" type="radio"/>	19/60	28/75	28/80	35/100	45/125	55/125
Pins		Number / size		6 /PN1	8 /PN1	10 /PN1	9 /PN2	16/PN2	18/PN3

Without specification on the order, couplings are delivered without boring.

* For speeds > nmax.. consult us.


For maximum bore.

Maximum bores for keyways according to ISO R773.

NOTES

Disc couplings

DISC COUPLINGS



MAIN CHARACTERISTICS	OPTIONS
<ul style="list-style-type: none"> IN ASSOCIATION WITH OUR MONOBLOC, SOLID AND VENTILATED DISCS 3 TYPES OF DISC COUPLINGS FOR A COMPLETE BRAKING SYSTEM SOLUTION 	<ul style="list-style-type: none"> LONG HUB ON MOTOR SIDE : SDKL .. SVKL .. SMLDF LONG HUB ON GEAR BOX SIDE : SDF-ML LONG HUBS ON MOTOR AND GEAR BOX SIDES : SDKL/SVKL-ML .. SMLDF-ML



PERIFLEX

- Highly-flexible rubber-fabric couplings
- Precise workmanship
- Monobloc, solid and ventilated discs : th.15 - 30 mm. Ø 175 - 795
- Torque range: 50 to 15.000 Nm
- Ambient temperature: -50°C to +80°C

SDF

- All steel coupling
- Two flanged sleeves with internal spur gear teeth
- Solid and ventilated discs : th. 30 mm. Ø 315 - 995
- Torque range: 1.500 to 36.700 Nm
- High misalignments = 1°30' per gear
- Ambient temperature: -20°C to +100°C

E - SVKL - SDKL

- Highly-Flexible coupling
- Fitted with a cam ring and a flexible element (shore A or shore D).
- Discs : **E**: th.15 - 30 mm. Ø 175 - 625
SVKL/SDKL: th. 30 mm. Ø 315 - 795
- Torque range:
 - E**: 200 to 3100 Nm
 - SVKL/SDKL**: 630 to 39700 Nm
- Ambient temperatures:
 - E**: -40°C to +120°C
 - SVKL/SDKL**: -25°C to +80°C

Benefits include

- Compensate extremely large offsets in every direction
- Allow radial mounting and dismantling without moving the machines
- Make torque transmission free from backlash
- Absorb torque peaks and damp occurring vibrations

Benefits include

- Disc mounting and dismantling without moving the machines back
- Closely controlled quality of the gearing profile for minimum end float and best alignment

Benefits include

- Easy assembly
- Easy dismantling of the complete coupling and cam Ring
- Damping of torsional vibrations
- Noise reduction and shock load accomodation
- No lubrication requirements

SIME Brakes Industrial Braking Systems

Disc couplings

DISC BRAKE - FLEXIBLE DISC COUPLING PNF-PNQ-PND

Revision number: T02805-01-D

Revision date: 15.05.2012

Flexible coupling PNF, PNQ and PND series

Discs thickness: 30mm

Rubber element and disc can be both removed without moving motor or gearbox back.


Use:

PNF and PNQ for horizontal motions only.
PND with lugs. compulsory for hoisting.

Option:

Solid Disc

Screws 1 and 2 not tightened to the torque at the delivery



Designation		Disc Coupling PNF, PNQ and PND	315V30		355V30			395V30			445V30			495V30			300-1				
			25	50	25	50	100	50	100	200	100-1	100-2	200-1	200-2	100-1	100-2	200-1	200-2	300-1	300-2	
Assembly	Nominal torque Cn		300	600	300	600	1200	600	1200	2500	1200	1200	2500	2500	1200	1200	2500	2500	4000	4000	
	Coupling Maximum torque Cmax	N.m	900	1800	900	1800	3600	1800	3600	7500	3600	3600	7500	7500	3600	3600	7500	7500	12000	12000	
	For use with calipers type		650-5K	645-5K	650	650	5K	650	645	645-5K		645-5K	4CA2	645-5K	4CA2	645-5K	4CA2	645-5K	4CA2	645-5K	4CA2
	Maximum speed tr/mn		3000	2500	2700	2500	2500	2400	2400	2000	2100	2100	2000	2000	1900	1900	1900	1900	1900	1900	
	J: PNF PNQ PND	kNm ²	0.180 0.182 0.187	0.240 0.252 0.267	0.283 0.286 0.291	0.333 0.344 0.360	0.456 0.483 0.512	0.370 0.382 0.397	0.589 0.616 0.645	1.08 1.116 1.140	0.776 0.803 0.832	0.656 0.683 0.71	1.475 1.516 1.541	1.545 1.586 1.61	1.266 1.293 1.322	1.272 1.299 1.328	1.655 1.696 1.721	1.68 1.721 1.746	1.60 1.64 1.66	1.62 1.65 1.67	
	Weight: PNF PNQ PND	kg	29.3 31.3 32.4	35.5 38.5 40.7	34.8 36.8 37.9	43 46 48.2	57 67 68.7	45.5 48.5 50.7	63 73 74.7	93 103 107.5	74 84 85.7	71 81 82.7	94 104 108.5	96 106 110.5	95 105 106.7	98.5 108.5 110	118 128 132.5	128 138.5 142.5	128.5 140 141.5	131 142.5 144	
Disc	ℓ	mm	315	350	315	340	380	340	380	402	413	515	435	568	400	443	435	525	562	582	
	PNF PNQ, PND	mm	366	393	366	383	445	383	445	467	478	580	500	633	465	508	500	590	622	642	
Disc	D D_2 D_s L L_1 d max. keyed d max. for shrink fit	mm	315	125	145	80	95	102	107	107	107	125	150	150	125	150	150	150	495	220	
		mm	125	80	95	102	107	102	107	107	107	110	135	135	140	140	140	140	100	100	
Coupling	d_3 d_4 k PNF k PNQ, PND O p d _i max. keyed PNF d _i max. keyed PNQ d _i max. keyed PND d _i max. for shrink fit	mm	210 80 59 110 38 138 55 55 55 50	263 95 67 110 44 161 65 65 65 60	210 80 59 110 44 138 55 55 55 50	263 95 67 110 42 138 55 55 55 60	310 125 75 140 42 178 65 65 65 80	310 125 75 140 42 178 65 65 65 80	370 150 85 150 48 192.5 90 90 90 90	370 150 85 150 42 178 90 90 90 90	370 150 85 150 46 192.5 100 100 100 100	310 125 75 140 42 178 90 90 90 90	310 125 75 140 42 178 90 90 90 90	370 150 85 150 46 192.5 100 100 100 100	370 150 85 150 46 192.5 100 100 100 100	402 160 95 155 50 282.5 100 110 110 100	402 160 95 155 50 305 325				
	Tightening torque on screw 1	N.m	20	25	20	25	45	25	45	55	45	45	55	55	45	45	55	55	60	60	
	Tightening torque on screw 2	N.m	49	49	86	86	86	135	135	135	210	210	210	290	290	290	290	290	290	290	
	Maximum permissible torque Ct and working conditions (ambient temperature $\leq 40^\circ\text{C}$)		>300 start/h : Ct=Cn/2.5 ≤300 start/h à 120 start/h : Ct=Cn/2 ≤120 start/h : Ct=Cn/1.5								NOTA : For shrink fit, k and ℓ are modified (consult us) At the delivery, screws 1 and 2 are not tightened to the torque In each case : engine start coupling Cd < Cmax										

DISC BRAKE - FLEXIBLE DISC COUPLING PNF-PNQ-PND

Revision number: T02805-01-D

Revision date: 15.05.2012

Flexible coupling **PNF**, **PNQ** and **PND** series

Discs thickness: 30mm

Rubber element and disc can be both removed without moving motor or gearbox back.

Use:


PNF and PNQ for horizontal motions only.

PND with lugs, compulsory for hoisting.

Option:

Solid Disc

Screws 1 and 2 not tightened to the torque at the delivery



Designation			Disc		550 V 30					625 V 30			705 V 30			795 V 30			
Coupling PNF, PNQ and PND			100	200-1	200-2	300-1	300-2	300-3	200	300	400	400	800	400	800	400	800	1500	
Assembly	Coupling Nominal torque Cn	N.m	1200	2500	2500	4000	4000	4000	2500	4000	6000	6000	10000	6000	10000	6000	10000	15000	
	Coupling Maximum torque Cmax	N.m	3600	7500	7500	12000	12000	12000	7500	12000	18000	18000	30000	18000	30000	18000	30000	45000	
	For use with calipers type			645	645	4CA2	645	4CA2	3CA2	4CA2	3CA2		3CA2		3CA2				
	Maximum speed tr/mn			1800	1800	1800	1800	1800	1800	1500	1500	1500	1300	1250	1200	1200	900		
	J:																		
	PNF	kNm ²	1.68	2.03	2.04	1.95	1.97	1.99	2.49	3.34	4.15	5.43	7.39	7.85	9.82	17.92			
	PNQ	kNm ²	1.70	2.07	2.08	1.98	2.00	2.03	2.53	3.38	4.25	5.52	7.54	7.95	9.96	18.17			
	PND	kNm ²	1.73	2.10	2.11	2.00	2.03	2.06	2.56	3.40	4.33	5.61	7.81	8.05	10.24	18.42			
	Weight:																		
	PNF	kg	101	124	126	123	131.5	134.5	137	151	182	191	258	207	283	587			
Disc	PNQ	kg	111	134.5	136.5	134	142.5	145.5	147.5	162.5	202	211	281	227	305.5	623.5			
	PND	kg	112.7	138.5	140.5	136	144.5	148.5	151.5	164	206	215	297.5	231	322.5	641.5			
	<i>l</i>	mm	400	435	450	470	535	580	450	470	575	495	635	495	635	810			
	PNF	mm	465	500	515	530	595	640	515	530	655	575	715	575	715	905			
	D	mm																	
	D ₂	mm																	
	D ₅	mm																	
	L	mm																	
	L ₁	mm																	
	d max. keyed	mm																	
Coupling	d	mm																	
	d ₃	mm	310	370	370	402	402	402	370	402	450	450	550	450	550	450	550	700	
	d ₄	mm	125	150	150	160	160	160	150	160	180	180	210	180	210	180	210	270	
	k PNF	mm	75	85	85	95	95	95	85	95	110	110	130	110	130	110	130	160	
	k PNQ, PND	mm	140	150	150	155	155	155	150	155	190	190	210	190	210	190	210	255	
	O	mm	42	46	46	50	50	50	46	50	70	70	120	70	120	70	120	150	
	p	mm	165	192.5	207.5	213	278	323	207.5	213	300	220	320	220	320	220	320	400	
	d ₅ max. keyed PNF	mm	90	100	100	110	110	110	100	100	110	110	130	110	130	110	130	18	
	d ₅ max. keyed PNQ	mm	90	100	100	110	110	110	100	100	110	120	120	120	120	120	140	180	
	d ₅ max. keyed PND	mm	90	100	100	110	110	110	100	100	110	120	120	120	120	120	140	180	
	d ₅ max. for shrink fit	mm	80	90	90	100	100	100	80	100	105	105	120	105	120	105	120	170	
Tightening torque for screw 1 N.m			45	55	55	60	60	60	55	60	110	110	200	110	200	110	200	240	
Tightening torque for screw 2 N.m			290	290	290	290	290	290	410	410	410	550	550	710	550	710	710		
Maximum permissible torque Ct and working conditions (ambient temperature ≤ 40°C)			>300 start/h : Ct=Cn/2.5 ≤300 start/h à 120 start/h : Ct=Cn/2 ≤120 start/h : Ct=Cn/1.5						NOTA : For shrink fit, k and <i>l</i> are modified (consult us) At the delivery, screws 1 and 2 are not tightened to the torque In each case : engine start coupling Cd< Cmax										

SIME Brakes Industrial Braking Systems

Disc couplings

DISC BRAKE - FLEXIBLE DISC COUPLING PNK

Revision number: T02561-01-B

Revision date: 25.11.2010

Flexible coupling PNK series

Solid disc thickness 15 mm

Rubber element and disc can both be removed
without disturbing motor or gearbox


Without lug.

Use:

For horizontal motions

For hoist motions, please consult us.

Screws 1 and 2 not tightened to the torque at the delivery



Designation		Disc	175P15			220P15			260P15			315P15		395P15		445P15		495P15		550P15		625P15	
			2	6	16	2	6	16	6	16	40	63	40	63	40	63	63	125	125	160			
Assembly	Coupling																						
	Nominal torque Cn Nm		50	100	200	50	100	200	100	200	400	800	400	800	400	800	800	1600	1600	2000			
	Max. torque Cmax Nm		150	300	600	150	300	600	300	600	1200	2400	1200	2400	1200	2400	2400	4800	4800	6000			
	combined caliper		660		650	660		650	660	650	645	650	645	650	645	645	645		645				
	Maximum speed tr/mn		5000	5000	4000	4300	4300	4000	3600	3600	3000	3000	2400	2400	2100	2100	1900	1800	1500	1500			
Disc	J kgm ² Fl. coupling and disc		0.011	0.013	0.023	0.030	0.042	0.045	0.066	0.076	0.146	0.168	0.338	0.408	0.520	0.595	0.89	1.42	2.19	2.58			
	Weight kg		6	7.4	11	9.4	11.6	15.3	18	21.4	26	31.5	38.5	46	42	51	69	89	100	120			
	<i>l</i> mm		185	215	250	195	225	250	245	265	295	340	340	370	340	370	410	460	460	435			
	D mm																						
	D ₁ mm																						
Flexible coupling	L mm		175			220			260		315		395		445		495		550		625		
	L ₁ mm		75			95			120		120		120		120		150		150		150		
	Bore d mm		55			65			85		102		102		102		135		135		135		
	max. keyed		58.5			68.5			88.5		112		112		112		145		145		145		
	shrink fit *		40			55			75		75		75		75		100		100		100		
Tightening	D ₃ mm		104	136	178	104	136	178	136	178	178	210	210	263	210	263	263	310	310	370			
	D ₄ mm		40	55	70	40	55	70	55	70	70	92	92	107	92	107	107	140	140	150			
	K mm		30	45	50	30	45	50	45	50	50	65	65	75	65	75	75	100	100	85			
	O mm		16	18	35	16	18	35	18	35	35	38	38	44	38	44	44	42	42	46			
	P mm		95	105	130	95	105	120	105	115	128	158	158	173	158	173	173	205	205	192.5			
Max. transmissible torque (Ct) and working conditions (ambient temperature ≤ 40°C)	Bore d ₁ mm	keyed	28	38	48	28	38	48	38	48	48	65	65	75	75	75	100	100	100	90			
	d ₁ shrink fit *	mm	28	38	42	28	38	42	38	42	42	60	60	70	70	70	90	90	90	90			
	Screw 1 mm		4	6	15	4	6	15	6	15	15	20	20	25	20	25	25	45	45	55			
	Screw 2 mm		25	25	25	25	25	25	25	25	49	69	86	120	86	120	210	210	295				
	> 300 starts/ hour: Ct = Cn / 2.5			* For shrink fit, dimensions k and <i>l</i> are altered (consult us)												In each case, motor starting torque Cd < Cmax							
≤ 300 starts/ hour to 120 starts/ hour: Ct = Cn / 2			≤ 120 starts/ hour: Ct = Cn / 1.5																				

DISC BRAKE - FLEXIBLE DISC COUPLING PNM


Revision number: T02661-01-B

Revision date: 25.11.2010

Coupling PNM series
 Monobloc disc with thickness: 30mm
 Rubber element and disc can both be removed
 without moving motor or gearbox back
 Without lug

Use:
 For horizontal motions.
 For hoist motions, consult us.

Screws 1 and 2 not
 tightened to the torque
 at the delivery



Designation		Disc Coupling PNM	220M30			260M30			315M30		
			2	6	16	6	16	40	16	40	63
Assembly	Nominal coupling torque Cn Maximum coupling torque Cmax	Nm Nm	50 150	100 300	200 600	100 300	200 600	400 1200	200 600	400 1200	800 2400
	For use with calipers Maximum speed	tr/mn	4300	650 - 5D 4300	4000	650 - 5D 3600	3600	3600	650 - 5D - 5K 3000	3000	3000
	J	kgm ²	0.056	0.06	0.07	0.072	0.085	0.107	0.155	0.178	0.248
	Weight	kg	13	15.2	19	15	18.4	22.5	20	25.5	33.5
	l	mm	244.5	277	309.5	275.5	295.5	332	295	340	358
Disc	D	mm	220			260			315		
	D ₁	mm	85			85			90		
	L	mm	102			102			102		
	L ₁	mm	112			112			112		
	d min. d max. keyed	mm mm	20 55			30 55			35 60		
Coupling	d ₃ d ₄ k O p d ₁ max. keyed Tightening torque of screws 1 Tightening torque of screws 2	mm mm mm mm mm mm Nm Nm	104 40 30 16 107.5 28 4 25	136 55 45 18 120 38 6 25	178 70 50 35 142.5 48 15 25	136 55 45 18 118.5 38 15 25	178 92 65 35 128.5 48 20 25	210 70 50 35 150 65 20 69	178 70 45 35 128 48 20 49	210 92 65 38 158 65 20 69	263 107 75 44 161 75 20 69
	Maximum permissible torque Ct and working conditions (ambient temperature ≤ 40°C)		>300 start/h : Ct=Cn/2.5 ≤300 start/h at 120 start/h : Ct=Cn/2 ≤120 start/h : Ct=Cn/1.5						In each case, motor starting torque Cd < Cmax Other versions, consult us.		

SIME Brakes Industrial Braking Systems

Disc couplings

DISC BRAKE - GEAR DISC COUPLING SDF

Revision number: T10004-01-C

Revision date: 03.02.2010

Gear coupling type **SDF**

Solid discs (**P**) and ventilated discs (**V**)

thickness 30mm

Disc mounting and dismounting without moving the machines back.

Stromag provides also the couplings:

SDF-ML with long hub on gear box side


SMLDF with long hub on motor side

SMLDF-ML with long hub on each side, consult us.

Hub and coupling : oiling protection.

Material and balancing of the discs : see the discs "technical data" leaflet

In standard, only the disc is balanced. The assembly is balanced on demand. (parts angularly matched).



Designation				Disc SDF	315 P30/V30		355 P30/V30		395 P30/V30						
J	P30	V30	kg.m ²		68	68	68	80	0.246	0.16	0.391	0.255	0.604	0.368	0.622
Weight	P30	V30	kg					32	25	39	30	47.5	36.5	53	42
Ø	mm							274	274	274	274	274	274	286	286
Maximum speed	rpm							3000	2700	2700	2700	2700	2700	2400	2400
Maximum braking torque	N.m							Tb ≤ Tp (Tb = maximum braking torque. Tp = maximum peak torque)							
For use with calipers					Check that D – D2 > width of the caliper braking surface (ex.: 4CA2 and 3CA2 not associated to discs D < 445) Check that the caliper nominal braking torque is ≤ Tp										
Disc	D	mm			315	355	395								
	D2	mm			124	145	165								
	D5	mm			82	100	112								
	L	mm			102	102	102								
	L1	mm			107	107	107								
	dp	mm			--	--	--								
	d maximum keyed	mm			55	70	75								
Coupling	d max. shrink fit	mm			50	60	70								
	Tightening torque screw 2 *	N.m			49	86	135								
	d3	mm			140	140	140								
	e	mm			3	3	3								
	k	mm			50	50	50								
	p	mm			120.5	120.5	120.5								
	d1 maximum keyed	mm			68	68	68								
Maximum peak torque (Tp)				N.m	1500	2200	2200								
Transmissible torque (Tt)				N.m	750	1100	1100								
In every case : Ts < Tp (Ts : motor starting torque)															

*: greased under head and on thread

DISC BRAKE - GEAR DISC COUPLING SDF

Revision number: T10004-01-C

Revision date: 03.02.2010

Gear coupling type **SDF**

Solid discs (**P**) and ventilated discs (**V**)

thickness 30mm

Disc mounting and dismounting without moving the machines back.

Stromag provides also the couplings:

SDF-ML with long hub on gear box side

SMLDF with long hub on motor side

SMLDF-ML with long hub on each side,
consult us.

Hub and coupling : oiling protection.


Material and balancing of the discs : see
the discs "technical data" leaflet

In standard, only the disc is balanced.
The assembly is balanced on demand.
(parts angularly matched).

Screws 1 and 2 not
tightened to the torque
at the delivery

MOTOR SIDE
STANDARD HUB

GEAR BOX SIDE
STANDARD HUB



Degrease faces in contact between disc, hub and coupling

Designation			Disc SDF	445 P30/V30						495 P30/V30										
J	P30	V30		kg.m ²	0.945	0.586	0.964	0.605	1.012	0.653	1.0524	1	1.0574	1.0105	1.01664	1.0114	Weight	P30	V30	kg
Weight	P30	V30		kg	58	43	64	49	74	59	86	68	97	79	112	94				
Ø			mm		307		332		361		347		380		410					
Maximum speed			rpm				2100							1900						
Maximum braking torque			N.m																	
For use with calipers				Check that D - D2 > width of the caliper braking surface (ex.: 4CA2 and 3CA2 not associated to discs D < 445) Check that the caliper nominal braking torque is ≤ Tp																
Disc	D		mm			445								495						
	D2		mm			175								218						
	D5		mm			112								155						
	L		mm			135								135						
	L1		mm			140								140						
	d _p		mm			--								30						
	d maximum keyed		mm			80								110						
	d max. shrink fit		mm			70								100						
Coupling	Tightening torque screw 2 *		N.m			210								290						
	d ₃		mm			140		169		200		169		200		228				
	e		mm			3		3		5		3		5		5				
	k		mm			50		62		76		62		76		90				
	p		mm			120.5		133.5		147.5		148.5		166.5		182.5				
	d ₁ maximum keyed		mm			68		80		100		80		100		115				
	d ₁ max. shrink fit		mm			63		75		92		75		92		106				
	Tightening torque screws 1 *		N.m			33		60		60		60		60		95				
Maximum peak torque (Tp)			N.m		2200		3800		6000		3800		6000		9400					
Transmissible torque (Tt)			N.m		1100		1900		3000		1900		3000		4700					
In every case : Ts < Tp (Ts : motor starting torque)																				

*: greased under head and on thread

SIME Brakes Industrial Braking Systems

Disc couplings

DISC BRAKE - GEAR DISC COUPLING SDF

Revision number: T10004-01-C

Revision date: 03.02.2010

Gear coupling type SDF

Solid discs (P) and ventilated discs (V)
thickness 30mm
Disc mounting and dismounting without
moving the machines back.


Stromag provides also the couplings:

SDF-ML with long hub on gear box side
SMLDF with long hub on motor side
SMLDF-ML with long hub on each side,
consult us.

Hub and coupling : oiling protection.

Material and balancing of the discs : see
the discs "technical data" leaflet

In standard, only the disc is balanced.
The assembly is balanced on demand.
(parts angularly matched).



Degrease faces in contact between disc, hub and coupling

Designation				Disc SDF	550 P30/V30						625 P30/V30													
					80	100	115	100		115		135		150										
	J	P30	V30	kg.m ²	2.247	1.307	2.297	1.357	2.387	1.447	3.775	2.329	3.863	2.417	4.065	2.619								
	Weight	P30	V30	kg	97	74	108	85	123	100	131	104	145	118	167	140								
Assembly	\varnothing		mm		347		380		410		380		410		441		483							
	Maximum speed		rpm		1800				1500															
	Maximum braking torque		N.m		Tb ≤ Tp (Tb = maximum braking torque. Tp = maximum peak torque)																			
	For use with calipers				Check that D – D2 > width of the caliper braking surface (ex.: 4CA2 and 3CA2 not associated to discs D < 445) Check that the caliper nominal braking torque is ≤ Tp																			
Disc	D		mm		550				625															
	D2		mm		218				238															
	D5		mm		155				168															
	L		mm		135				135															
	L1		mm		140				140															
	dp		mm		30				30															
	d maximum keyed		mm		110				120															
	d max. shrink fit		mm		100				105															
	Tightening torque screw 2 *		N.m		290				410															
Coupling	d3		mm		169				200															
	e		mm		3				5															
	k		mm		62				76															
	p		mm		148.5				166.5															
	d1 maximum keyed		mm		80				115															
	d1 max. shrink fit		mm		75				106															
	Tightening torque screws 1 *		N.m		60				95															
	Maximum peak torque (Tp)		N.m		3800				6000															
	Transmissible torque (Tt)		N.m		1900				3000															
	In every case : Ts < Tp (Ts : motor starting torque)																							

*: greased under head and on thread

DISC BRAKE - GEAR DISC COUPLING SDF

Revision number: T10004-01-C

Revision date: 03.02.2010

Gear coupling type **SDF**

Solid discs (**P**) and ventilated discs (**V**)

thickness 30mm

Disc mounting and dismounting without moving the machines back.

Stromag provides also the couplings:

SDF-ML with long hub on gear box side

SMLDF with long hub on motor side

SMLDF-ML with long hub on each side, consult us.

Hub and coupling : oiling protection.


Material and balancing of the discs : see the discs "technical data" leaflet

In standard, only the disc is balanced. The assembly is balanced on demand. (parts angularly matched).

Screws 1 and 2 not tightened to the torque at the delivery

MOTOR SIDE
STANDARD HUB

GEAR BOX SIDE
STANDARD HUB



Degrease faces in contact between disc, hub and coupling

Designation			Disc SDF	705 P30/V30						795 P30/V30						
				115	135	150	170			135	150	170				
Assembly	J	P30	V30	kg.m ²	6.165	3.935	6.37	4.14	6.655	4.425	7.153	4.923	10.092	6.512	10.378	6.798
	Weight	P30	V30	kg	173	140	196	163	223	190	259	226	233	193	260	220
	\varnothing			mm	410		441		483		513		441		483	
	Maximum speed			rpm					1300						1200	
Maximum braking torque				N.m					Tb ≤ Tp (Tb = maximum braking torque. Tp = maximum peak torque)							
For use with calipers					Check that D – D2 > width of the caliper braking surface (ex.: 4CA2 and 3CA2 not associated to discs D < 445) Check that the caliper nominal braking torque is ≤ Tp											
Disc	D			mm			705						795			
	D2			mm			268						300			
	D5			mm			190						216			
	L			mm			135						135			
	L1			mm			140						140			
	d _p			mm			30						30			
	d maximum keyed			mm			135						150			
	d max. shrink fit			mm			120						135			
Coupling	Tightening torque screw 2 *			N.m			550						710			
	d ₃			mm	228		266		298		330		266		298	
	e			mm	5		6		6		8		6		8	
	k			mm	90		105		120		135		105		120	
	p			mm	182.5		198		225		239		198		225	
	d ₁ maximum keyed			mm	115		135		150		170		135		150	
	d ₁ max. shrink fit			mm	106		125		140		160		125		140	
	Tightening torque screws 1 *			N.m	95		171		235		235		171		235	
Maximum peak torque (Tp)				N.m	9400		13800		25300		29200		13800		25300	
Transmissible torque (Tt)				N.m	4700		6900		12650		14600		6900		12650	
In every case : Ts < Tp (Ts : motor starting torque)																

*: greased under head and on thread

SIME Brakes Industrial Braking Systems

Disc couplings

DISC BRAKE - FLEXIBLE DISC COUPLING E

Revision number: T02580-01-B

Revision date: 25.11.2010


Flexible coupling "NORMEX" E series

Solid discs Ø 175 to 395


Disc thickness: 15 mm

Screws 1 and 2 not tightened to the torque at the delivery

175 P 15 - 220 P 15



260 P 15 - 315 P 15 - 395 P 15



Degrease faces in contact between disc and coupling.

Designation	Disc type Coupling	175 P 15		220 P 15		260 P 15		315 P 15			395 P 15		
		97	112	112	128	112	128	112	128	148	128	148	168
Assembly	J kgm ²	0.017	0.019	0.038	0.042	0.065	0.070	0.13	0.135	0.14	0.31	0.315	0.335
	Weight kg	8	9.5	12.5	15.5	18	21	22	24	28	30	34	39
	For use with caliper Type	660-650		660-650		660-650		660-650			660-650		
	Maximum speed t/mn	5000		4 300		3 600		3 000			2 400		
	Ø mm	183	244	211	244	190	201	214.5	225.5	230	225.5	230	245
	D mm	175	175	220	220	260	260	315	315	315	395	395	395
Disc	D ₁ mm	75	75	95	95	120	120	120	120	120	120	120	120
	L mm	55	55	65	65	85	85	102	102	102	102	102	102
	L ₁ mm	58.5	58.5	68.5	68.5	88.5	88.5	113	113	113	112	112	112
	d max. keyed mm	44		55		55		60		65		65	
	d max. for shrink fit mm	40		55		55		60		65		65	
	d ₃ mm	97	112	112	128	112	128	112	128	148	128	148	168
Coupling	d ₄ mm	69	79	79	90	79	90	79	90	107	90	107	124
	k mm	50	60	60	70	60	70	60	70	80	70	80	90
	p mm	76.5	127.25	84.25	107.25	43.25	44.25	50.75	51.75	46.25	51.75	46.25	51.25
	d ₁ max. keyed mm	42	48	48	55	48	55	48	55	65	55	65	75
	Peak max. torque (Cp) Nm	200	310	310	500	310	500	310	500	800	500	800	1300
	Max. permissible torque (Ct) and working conditions (Ambient temperature ≤ 40 °C)	150 starts/h - Ct ≤ Cp/2.5 300 starts/h - Ct ≤ Cp/3.2 600 starts/h - Ct ≤ Cp/4 In every case: Cd < Cp (Cd motor starting torque) (Ct: motor nominal torque)											
	Tightening torque on screws (1) and (2) *	Nm	10	25	25	25	25	25	25	49	25	49	86

*: stopped with normal glue

DISC BRAKE - FLEXIBLE DISC COUPLING E

Revision number: T02580-01-B


Revision date: 25.11.2010

Flexible coupling "NORMEX" E series

Solid discs Ø 445 to 625

Disc thickness: 15 mm

Screws 1 not tightened to the torque at the delivery



Degrease faces in contact between disc and coupling.

Designation		Disc type Coupling	445 P 15				495 P 15			550 P 15				625 P 15		
	Assembly		128	148	168	194	148	168	194	148	168	194	214	168	194	214
J		kgm ²	0.49	0.495	0.515	0.55	0.785	0.815	0.84	1.175	1.205	1.23	1.30	1.975	2	2.07
Weight		kg	33	37	43	51	52	58	66	58	64	72	80	74	82	90
For use with caliper	Type		660-650-645				660-650-645			660-650-645				660-650-645		
ℓ	Disc	mm	225.5	230	245	260	263	278	293	263	278	293	308	278	293	308
D	Disc	mm	445	445	445	445	495	495	495	550	550	550	550	625	625	625
D ₁		mm	120	120	120	120	150	150	150	150	150	150	150	150	150	150
L		mm	102	102	102	102	135	135	135	135	135	135	135	135	135	135
L ₁		mm	112	112	112	112	145	145	145	145	145	145	145	145	145	145
d max. keyed	Disc	mm	60	65	65	65	65	70	70	65	70	70	90	70	70	90
d max. for shrink fit		mm	60	65	65	65	65	70	70	65	70	70	90	70	70	90
d ₃	Coupling	mm	128	148	168	194	148	168	194	148	168	194	214	168	194	214
d ₄		mm	90	107	124	140	107	124	140	107	124	140	157	124	140	157
k		mm	70	80	90	100	80	90	100	80	90	100	110	90	100	110
p		mm	51.75	46.25	51.25	56.25	46.25	51.25	56.25	46.25	51.25	56.25	61	51.25	56.25	61
d _{max} keyed	Coupling	mm	55	65	75	85	65	75	85	65	75	85	95	75	85	95
Peak max. torque (Cp)		Nm	500	800	1300	2000	800	800	2000	2000	1300	2000	3100	1300	2000	3100
Max. permissible torque (Ct) and working conditions (Ambient temperature ≤ 40 °C)		150 starts / hour 8 h/24 h - Ct ≤ Cp/2.5 300 starts / hour 8 h/24 h - Ct ≤ Cp/3.2 600 starts / hour 8 h/24 h - Ct ≤ Cp/4										In every case: Cd < Cp (Cd motor starting torque) (Ct: motor nominal torque)				
Tightening torque on screw (1) *		Nm	25	49	86	86	49	86	86	49	86	86	135	86	86	135

*: stopped with normal glue

SIME Brakes Industrial Braking Systems

Disc couplings

DISC BRAKE - FLEXIBLE DISC COUPLING E

Revision number: T02580-01-B

Revision date: 25.11.2010


Flexible coupling E series

Monobloc discs Ø 220 - 260 - 315


Disc thickness: 30 mm

Screws 1 and 2 not tightened to the torque at the delivery

220 M30



260 M30 - 315 M30



Motor side

Degrease faces in contact between disc and coupling.

Designation	Disc Flexible coupling	220 M 30		260 M 30		315 M 30		
		112	128	112	128	112	128	148
Assembly	J kgm ²	0.063	0.067	0.078	0.09	0.145	0.155	0.160
	Weight kg	16.2	19.2	15	18	17	20	24.5
	For use with calipers Type	650-5D		650-5D		650-5D-5K		650-5D
	Maximum speed r.p.m.	4 300		3 600		3 000		
Disc	\varnothing mm	313.5	323.5	220.5	231.5	231.5	225.5	230
	D mm	220		260		315		
	D_1 mm	85		85		90		
	L mm	102		102		102		
	L_1 mm	113		120		113		
	d (pilot bore) mm	20		30		35		
	d maxi keyed mm	55		55		60		
	d maxi shrink fitted mm	55		55		60		
Coupling Pb75	k mm	60	70	60	70	60	70	80
	p mm	149.75	149.75	56.75	57.75	50.75	51.75	46.25
	d_3 mm	112	128	112	128	112	128	148
	d _{maxi} keyed mm	48	55	48	55	48	55	65
	d _{maxi} shrink fitted mm	-	-	-	-	-	-	-
	Peak maxi. torque (Cp) N.m	310	500	310	500	310	500	800
	Transmissible torque (Ct) and working conditions (ambient temperature $\leq 40^\circ\text{C}$) (Ct: motor nominal torque)	150 starts/hour		8 h/24 h - Ct $\leq \text{Cp}/2.5$				
		300 starts/hour		8 h/24 h - Ct $\leq \text{Cp}/3.2$				
		600 starts/hour		8 h/24 h - Ct $\leq \text{Cp}/4$				
		(in every case: Cd < Cp)		(Cd: motor starting torque)				
	Tightening torque of screws (1) and (2) *Nm	20	20	20	20	20	20	44

*: stopped with normal glue

NOTES

SIME Brakes Industrial Braking Systems

Disc couplings

DISC BRAKE - FLEXIBLE DISC COUPLING SVKL AND SDKL

Revision number: T10152-01-G

Revision date: 13.09.2019

Flexible couplings series **SVKL** and **SDKL**

Long hub on motor side

Ventilated Discs thickness : **30 mm**

Disc mounting and dismounting without moving
the machines back


- Rubber element **V**

- Rubber element **D**

(specify type of rubber element with order)

Option:

- Solid disc



Degrease faces in contact between disc and coupling.

Flexible couplings SVKL / SDKL		125	145		170		200	230		
Disc diameter (th. 30)		315	315	355	395	445	445	495	550	
ASSEMBLY	J with ventilated disc	kg.m ²	0.17	0.18	0.27	0.42	0.68	0.73	1.2	1.74
	J with solid disc	kg.m ²	0.26	0.27	0.41	0.66	1.04	1.09	1.22	2.68
	Max. weight bored	kg	27	31	37	48	57	63	96	107
	Maximum speed	r.p.m.	3000	3000	2700	2400	2100	2100	1800	1800
	L2	mm	286.5	298	298	331.5	364.5	364.5	412.5	412.5
DISC	ØD	mm	315	315	355	395	445	445	495	550
	ØD2	mm	125	125	145	165	175	175	220	220
	ØD5	mm	80	80	95	105	110	110	150	150
	Ød max keyed or shrink fit	mm	50	50	60	70	70	70	100	100
COUPLING	L	mm	102	102	102	102	135	135	135	135
	L1	mm	107	107	107	107	140	140	140	140
	Øa	mm	125	145	145	170	170	200	230	230
	Øb	mm	105	125	125	144	144	165	190	190
	Øc	mm	80	100	100	112	112	130	150	150
	Ød1 max keyed	mm	55	70	70	80	80	95	110	110
	m	mm	110.5	110.5		140.5		130.5	169.5	
	n	mm	61	72.5		76		86	95	
	p	mm	76	87.5		91		101	110	
	s	mm	6	6.5		7.5		8.5	9.5	
Max. torque		V	750	1200	1200	1900	1900	2880	5150	5150
Tkmax in Nm		D	1110	1800	1800	2850	2850	4950	7740	7740
Transmissible torque (Tk _n) (Tk _n : motor nominal torque)			Tk _n ≤ Tk _{max} /k		k min.	Temperature Rate	k=3 < 40°C ≤ 120 starts/h	k=4 < 80°C ≤ 240 starts/h	k=6 < 80°C ≤ 600 starts/h	≤ 80°C ≤ 600 starts/h
Tightening torque *		Screws 1	Nm	48	84	84	204	204	204	285
		Screws 2	Nm	48	48	84	133	204	204	285

* Screws class 10.9 greased with molybdenum bisulphide grease under the head and in threads.
Tightening tool dispersion = ±10%

Ts: motor starting torque. In all cases, Ts < Tkmax

DISC BRAKE - FLEXIBLE DISC COUPLING SVKL AND SDKL

Revision number: T10152-01-G

Revision date: 13.09.2019

Flexible couplings series **SVKL** and **SDKL**

Long hub on motor side


Ventilated Discs thickness : **30 mm**

Disc mounting and dismounting without moving the machines back

- Rubber element **V**
 - Rubber element **D**
- (specify type of rubber element with order)

Option:

- Solid disc



Degrease faces in contact between disc and coupling.


Flexible couplings SVKL / SDKL		260			300			400				
Disc diameter (th. 30)		550	625	705	625-2	705	705-2	795	705	795		
ASSEMBLY	J with ventilated disc	kg.m ²	1.97	2.77	4.66	4.52	5.09	5.23	7.86	7.44	10.21	
	J with solid disc	kg.m ²	2.91	4.22	6.89	5.23	7.32	7.81	11.44	9.67	13.79	
	Max. weight bored	kg	120	140	170	185	215	229.5	250	300	356	
	Maximum speed	r.p.m.	1800	1500	1300	1500	1300	1300	1200	1300	1200	
	L2	mm	469	469	469	480	480	480	480	576.5	576.5	
	ØD	mm	550	625	705	625	705	705	795	705	795	
	ØD2	mm	220	235	265	300	265	300	300	265	300	
	ØD5	mm	150	150	180	210	180	210	210	180	210	
	Ød max keyed or shrink fit	mm	100	100	120	130	120	130	130	120	130	
DISC	L	mm	135	135	135	135	135	135	135	135	135	
	L1	mm	140	140	140	140	140	140	140	140	140	
	Øa	mm	260	260	260	300	300	300	300	400	400	
	Øb	mm	220	220	220	260	260	260	260	335	335	
	Øc	mm	175	175	175	210	210	210	210	250	250	
	Ød1 max keyed	mm	125	125	125	140	140	140	140	160	160	
	m	mm	209.5			209.5			289.5			
	n	mm	111.5			122.5			139			
	p	mm	126.5			137.5			154			
COUPLING	s	mm	9.5			10.5			10.5			
	Max. torque	Rubber element	V	7950	7950	7950	11700	11700	11700	11700	26700	26700
	Tkmax in Nm		D	11940	11940	11940	17550	17550	17550	17550	30360	39700
	Transmissible torque (Tk _n) (Tk _n : motor nominal torque)	Tk _n ≤ Tkmax/k Tk _n < Tkmax		k min.	Temperature Rate	k=3 ≤ 40°C ≤ 120 starts/h	k=4 ≤ 80°C ≤ 240 starts/h	k=6 ≤ 80°C ≤ 600 starts/h				
	Tightening torque *	Screws 1	Nm	541	541	541	685	685	685	685	1364	1364
		Screws 2	Nm	285	398	541	541	685	685	541	685	

* Screws class 10.9 greased with molybdenum bisulphide grease under the head and in threads.
Tightening tool dispersion = ±10%

Ts: motor starting torque. In all cases, Ts < Tkmax

Elastic couplings

ELASTIC COUPLINGS



DISC BRAKE - SVW & SDW ELASTIC COUPLINGS


Revision number: T10156-01-B

Revision date: 12.12.2019

- Cam ring **V**
- Cam ring **D**
(Specify type of cam ring with order)
- Working temperature : -25°C to +80°C

Option:

Long hub (motor or/and gearbox side)
Short hub (motor or/and gearbox side)
Consult us.





Coupling size SVW- / SDW-		50	70	85	100	125	145	170	200	230	260	300	400	
Cam ring n°	SVW SDW	50V 85D	70V 100D	85V 125D	100V 125D	125V 145D	145V 145D	170V 170D	200V 200D	230V 230D	260V 260D	300V 300D	400V 400D	
Qty of cams		4	6	6	6	6	6	8	8	10	10	10	14	
Nominal torque T_{CN}	SVW Nm	15	55	90	160	300	480	760	1150	2060	3180	4680	10680	
	SDW Nm			140	240	440	720	1140	1980	3090	4780	7020	16020	
Max. torque T_{cmax}	SVW Nm	40	140	225	390	750	1200	1900	2880	5150	7950	11700	26700	
	SDW Nm			350	610	1110	1800	2850	4950	7740	11940	17550	40050	
Max. r.p.m.	tr/mn	9000	7500	7000	5600	5000	5000	4000	3600	3200	2500	2000	1750	
Mass moment of inertia	kgm ²	0,0002	0,001	0,002	0,005	0,010	0,021	0,047	0,108	0,195	0,385	0,735	1,852	
Weight	kg	0,68	1,64	2,5	4,5	7	9,5	16	27,5	40	57	84	133	
Diameters	a	mm	50	70	85	105	126	145	170	200	230	260	300	400
	c	mm	42	55	62	72	88	90	112	125	140	150	200	225
	d pilot bored.	mm	-	-	-	15	20	20	25	25	35	35	40	40
	d max.	mm	24	32	42	48	60	65	75	90	100	105	140	160
	i	mm	19	29	38	46	56	63	90	102	117	140	162	250
Lengths	L	mm	75	100	110	125	145	160	190	245	270	285	330	400
	m	mm	29,5	38,5	43	49	56	60,5	74,5	98,5	110	112,5	131,5	163,5
	o	mm	23,5	31,5	35	37,5	44	46,5	56,5	77,5	87	87,5	106,5	127,5
	s	mm	12	18	18	20	25	30	30	35	35	45	50	55
	r	mm	2	2,5	3	3,5	4	4,5	5,5	6,5	7,5	7,5	8,5	9

Cardan Shafts

CARDAN SHAFTS



MAIN CHARACTERISTICS	ADVANTAGES
<ul style="list-style-type: none"> TRANSMISSION OF AN ANGULAR ROTATION COUPLING OF 2 ROTATING NON-ALIGNED SHAFTS 	<ul style="list-style-type: none"> MAINTENANCE FREE - do not need lubrication FEWER FAILURES - closed system without loss of grease and without penetration of water and dirt LONG SERVICE LIFE - SAE or involute splines: optimization in accordance with size and utilization of the cardan shaft


Type	Design	Description
ACS-100		With length compensation
ACS-105		With length compensation in double-flange design
ACS-110		Short couple shaft
ACS-130		Tube shaft without length compensation
ACS-135		Tube shaft without length compensation in double-flange design
ACS-160		Intermediate shaft
ACS-220		Intermediate tube shaft

L1 = compressed length

L2 = maximum possible length compensation

Lw max. = maximum possible working length

Optimal working length = **Lw opt.** = **L1** + $\frac{1}{2}$ **L2**



Cardan Shafts

ACCESSORIES - CARDAN SHAFTS TYPE ACS

Revision number: T10155-01-B

Revision date: 05.11.2018

Cardan Shaft Sizes


Size	Swing diameter mm	Bearing torque Nm	Feature
1	up to 76	up to 600	One-piece bearing yokes Length compensation with involute spline Flange yoke with DIN or SAE connection
2	100 - 144	1.400 - 6.000	One-piece bearing yokes Length compensation with involute spline Flange yoke with DIN, SAE or cross-serrated connection Maintenance-free U-joints
3	158 - 204	8.800 - 20.000	One-piece bearing yokes Length compensation with involute spline or straight flank spline (SAE) Application-related spline coating Flange yoke with DIN, SAE or cross-serrated connection, as well as with face key Maintenance-free U-joints
4	220 - 315	26.000 – 143.000	One-piece bearing yokes Length compensation with involute spline or straight flank spline (SAE) Application-related spline coating Flange yoke with DIN, face key or Hirth-serration Maintenance-free U-joints
5	350 - 620	210.000 – 1.250.000	One-piece bearing yokes Length compensation with involute spline or straight flank spline (SAE) Application-related spline coating Flange yoke with DIN, face key or Hirth-serration Double flange design
6	from 680	from 1.950.000	One-piece bearing yokes Length compensation with straight flank spline (SAE) Application-related spline coating Flange yoke with face key or Hirth-serration Double flange design

ACCESSORIES - CARDAN SHAFTS TYPE ACS


Revision number: T10155-01-B

Revision date: 05.11.2018

Series 1, 2 and 3

Series		1	2				3				
Size		07600	10000	11600	12600	14400	15800	17200	17800	20400	
DESIGN	Bearing Torque Nm	600	1.400	3.000	5.300	6.000	8.800	12.500	17.000	20.000	
	Reversing Fatigue Torque Nm	300	700	1.500	2.300	2.900	4.400	5.100	8.500	11.000	
	Joint Performance Factor Nm	220	660	990	1.780	2.070	2.400	3.500	4.600	6.800	
	Swing Diameter mm	76	100	116	126	144	158	172	178	204	
		L1 min	250	421	451	536	572	630	566	661	746
		L2 min	40	110	110	110	110	180	110	110	110
		tube size	50	50 / 76,2	70 / 90	90	100	100	120	120	140
		L1 min	214	240	290	340	409	400	430	450	480
		L2 min	15	15	30	40	45	35	40	40	40
		L1 max	249	420	450	535	571	559	565	660	745
		L2 max	40	110	110	110	110	110	110	110	110
		L1 min	190	218	278	309	369	355	400	353	440
		tube size	50	50 / 76,2	70 / 90	90	100	120	120	120	140
CONNECTIONS ($\varnothing D-N \cdot \varnothing d$)			75-6-6	90-4-8	100-6-8	120-8-10	150-8-12	150-8-12	180-8-14	180-8-14	180-8-14
			90-4-8	100-6-8	120-8-8	150-8-12	180-8-14	180-8-14	180-8-16	180-8-16	180-8-16
				100-8-8	120-8-10	180-8-10		180-8-16	180-10-16	180-10-16	180-10-16
				120-8-8	150-8-10	180-8-14		180-10-16	225-8-16	225-8-16	225-8-16
				120-8-10	150-8-12				250-8-18	250-8-18	
			87-4-8	87-4-8	119-4-11,1	146-4-12,7	174,8-8-9,6	174,8-8-9,6	203,2-8-9,6	203,2-8-9,6	203,2-12-11,1
				96,8-4-9,6	149-4-12,7			203,2-8-9,6	203,2-12-11,1	203,2-12-11,1	244,5-8-16,1
				119-4-11,1				203,2-12-11,1			
				100-4-8,5	122-4-11	122-4-11	122-4-11	150-4-13	150-4-13	150-4-13	180-4-15
				122-4-11			150-4-13	180-4-15	180-4-15	180-4-15	

CONNECTIONS



SIME Brakes Industrial Braking Systems

Cardan Shafts

ACCESSORIES - CARDAN SHAFTS TYPE ACS


Revision number: T10155-01-B

Revision date: 05.11.2018

Series 4 and 5

Series		4					5				
Size		21500	21510	22580	25080	28580	31510	35000	39000	44000	
DESIGN	Bearing Torque Nm	26.000	29.000	45.000	70.000	100.000	143.000	210.000	300.000	500.000	
	Reversing Fatigue Torque Nm	13.000	14.500	23.000	35.000	50.000	70.000	100.000	150.000	250.000	
	Joint Performance Factor Nm	8.050	8.350	12.050	18.650	26.200	28.140	40.300	56.800	81.500	
	Swing Diameter mm	220	220	225	250	285	315	350	390	440	
		L1 min	797	775	900	995	1.115	1.205	1.295	1.450	1.660
		L2 min	150	140	110	140	140	140	150	170	190
		tube size	144	150	160 / 170	180	200	219	245	273	325
		L1 min	551	580	585	645	990	980	1.175	1.140	1.300
		L2 min	50	40	40	40	50	100	50	80	70
		L1 max	796	650	899	994	1.114	1.204	1.294	1.449	1.659
		L2 max	150	110	140	140	140	140	150	170	190
		L1 min	506	538	615	680	760	890	950	1.040	1.250
		tube size	144	150	160 / 170	180	200	215	245	273	324
CONNECTIONS ($\varnothing D-N \cdot \varnothing d$)		225-8-16	225-8-16	225-8-16	250-8-18	285-8-20	315-8-22	350-10-22	390-10-24	435-10-27	
		250-8-18	250-8-18	250-8-18	285-8-20	315-8-22	350-10-22	390-10-24	435-10-27		
		285-8-20	285-8-20	285-8-20	315-8-22						
		225-8-17 (32x9)	225-8-17 (32x9)	225-8-17 (32x9)	250-8-19 (40x12)	285-8-21 (40x15)	315-10-23 (40x15)	350-10-23 (50x16)	390-10-25 (70x18)	435-16-28 (80x20)	
			250-8-19 (40x12,5)	250-8-19 (40x12,5)	285-8-21 (40x15)	315-10-23 (40x15)	350-10-23 (50x16)	390-10-25 (70x18)	435-16-28 (80x20)	480-16-31 (90x22,5)	
				285-8-21 (40x15)							
								350-12-1116	390-12-1118	435-16-1118	
								390-12-1118	435-16-1118	480-16-1120	

CONNECTIONS - with face KEY




ACCESSORIES - CARDAN SHAFTS TYPE ACS

Revision number: T10155-01-B


Revision date: 05.11.2018

Series 5 and 6

Series		5		6			
Size		49000	55000	62000	68000	75000	84000
DESIGN	Bearing Torque Nm	700.000	1.000.000	1.250.000	1.950.000	2.650.000	3.900.000
	Reversing Fatigue Torque Nm	345.000	500.000	625.000	950.000	1.350.000	1.850.000
	Joint Performance Factor Nm	112.000	154.000	210.000	320.000	750.000	2.230.000
	Swing Diameter mm	490	550	620	680	750	840
	100	L1 min	1.810	1.965	2.240		
		L2 min	190	240	250		
		tube size	351	402	445		
	110	L1 min	1.300	1.770	2.050		
		L2 min	50	55	55		
		L1 max	1.809	1.964	2.239		
		L2 max	190	240	250		
CONNECTION (ØD-N-Ød)	130	L1 min	1.360	1.480	1.690		
		tube size	355	406	445		
	105	L1 min				3.250	4.000
		L2 min				250	250
		tube size				559	609
	135	L1 min				1.950	2.400
		tube size				559	609
							660
	DIN with face key (w x k)		480-16-31 (90x22,5)	550-16-31 (100x22,5)	620-16-38 (100x25)		
			550-16-31 (100x22,5)	620-16-38 (100x25)			
CONNECTION (ØD-N-Ød)	High-serration		480-16-1120	550-11-1122	620-6	680-24-33	750-24-33
			550-16-24	620-24-26	680-24-33		840-24-38

Hydraulic Buffers

HYDRAULIC BUFFERS




MAIN CHARACTERISTICS	APPLICATIONS
<ul style="list-style-type: none"> DAMPING DEVICES REQUIRING NO EXTERNAL ENERGY DECCELERATE MOVING MACHINES ALONG THE SHORTEST POSSIBLE PATH SELF-ADJUSTMENT 2 TYPES: REAR MOUNTING OR FRONT MOUNTING FILLING: OIL / NITROGEN 	<ul style="list-style-type: none"> STEEL INDUSTRY NUCLEAR CRANES PORT APPLICATIONS OVERHEAD CRANES - CONTAINER CRANES STACKER CRANES TRANSFER CARS - RAILWAY APPLICATIONS

Coating & Options	
Temperature	-10 °C à +80 °C (standard) -40 °C à +120 °C (special)
Piston rod	Plasma coating (20 µm)
Body coating	Synthetic resin Color 80µm - standard: RAL5009 (Azure blue)
Options	Body coating: RAL1003 (signal yellow) RAL3020 (traffic red) RAL7021 (black grey) RAL9011 (graphite black) Safety chain Protection cover



With the options: safety chain and protection cover



SIME Brakes Industrial Braking Systems

Hydraulic Buffers


ACCESSORIES - HYDRAULIC BUFFERS

Revision number: T10125-01-D



Revision date: 20.09.2019

PHS 063

Type FM



Type RM



PHS 063 100-RM

Size Stroke Type

Dimensions in mm	S	L	L1	L2	B	D1	D2	D3	d	W (kJ) Capacity/Stroke	F (kN) Buffering Force
PHS 063 100	100	455,5	202	233,5	20	91	168	135	17	15	170
PHS 063 150	150	568	252	296	20	91	168	135	17	23	170
PHS 063 200	200	680,5	302	358,5	20	91	168	135	17	30	170
PHS 063 250	250	793	352	421	20	91	168	135	17	38	170
PHS 063 300	300	905,5	402	483,5	20	91	168	135	17	46	170
PHS 063 350	350	1018	452	546	20	91	168	135	17	51	160
PHS 063 400	400	1130,5	502	608,5	20	91	168	135	17	54	150
PHS 063 450	450	1243	552	671	20	91	168	135	17	57	140
PHS 063 500	500	1355,5	602	733,5	20	91	168	135	17	59	130
PHS 063 550	550	1468	652	796	20	91	168	135	17	60	120
PHS 063 600	600	1580,5	702	858,5	20	91	168	135	17	60	110
PHS 063 650	650	1693	752	921	20	91	168	135	17	59	100
PHS 063 700	700	1805,5	802	983,5	20	91	168	135	17	57	90
PHS 063 750	750	1918	852	1046	20	91	168	135	17	54	80
PHS 063 800	800	2030,5	902	1108,5	20	91	168	135	17	51	70


ACCESSORIES - HYDRAULIC BUFFERS

Revision number: T10125-01-D



Revision date: 20.09.2019

PHS 080

Type FM



Type RM



PHS 080 100-RM

Size	Stroke	Type
------	--------	------

Dimensions in mm	S	L	L1	L2	B	D1	D2	D3	d	W (kJ) Capacity/Stroke	F (kN) Buffering Force
PHS 080 100	100	522,5	209,5	288	25	110	198	165	17	23	260
PHS 080 150	150	635	259,5	350,5	25	110	198	165	17	35	260
PHS 080 200	200	747,5	309,5	413	25	110	198	165	17	48	260
PHS 080 250	250	860	359,5	475,5	25	110	198	165	17	59	260
PHS 080 300	300	972,5	409,5	538	25	110	198	165	17	68	250
PHS 080 350	350	1085	459,5	600,5	25	110	198	165	17	76	240
PHS 080 400	400	1197,5	509,5	663	25	110	198	165	17	84	230
PHS 080 450	450	1310	559,5	725,5	25	110	198	165	17	90	220
PHS 080 500	500	1422,5	609,5	788	25	110	198	165	17	95	210
PHS 080 550	550	1535	659,5	850,5	25	110	198	165	17	100	200
PHS 080 600	600	1647,5	709,5	913	25	110	198	165	17	104	190
PHS 080 650	650	1760	759,5	975,5	25	110	198	165	17	106	180
PHS 080 700	700	1872,5	809,5	1038	25	110	198	165	17	108	170
PHS 080 750	750	1985	859,5	1100,5	25	110	198	165	17	109	160
PHS 080 800	800	2097,5	909,5	1163	25	110	198	165	17	109	150

SIME Brakes Industrial Braking Systems

Hydraulic Buffers


ACCESSORIES - HYDRAULIC BUFFERS

Revision number: T10125-01-D



Revision date: 20.09.2019

PHS 100

Type FM



Type RM



PHS 100 100-RM
Size Stroke Type

Dimensions in mm	S	L	L1	L2	B	D1	D2	D3	d	W (kJ) Capacity/Stroke	F (kN) Buffering Force
PHS 100 100	100	538,5	207	301,5	30	132	258	210	23	38	420
PHS 100 150	150	651	257	364	30	132	258	210	23	58	420
PHS 100 200	200	763,5	307	426,5	30	132	258	210	23	78	420
PHS 100 250	250	876	357	489	30	132	258	210	23	98	420
PHS 100 300	300	988,5	407	551,5	30	132	258	210	23	115	420
PHS 100 350	350	1101	457	614	30	132	258	210	23	132	420
PHS 100 400	400	1213,5	507	676,5	30	132	258	210	23	148	410
PHS 100 450	450	1326	557	739	30	132	258	210	23	161	400
PHS 100 500	500	1438,5	607	801,5	30	132	258	210	23	175	390
PHS 100 550	550	1551	657	864	30	132	258	210	23	190	380
PHS 100 600	600	1663,5	707	926,5	30	132	258	210	23	200	370
PHS 100 650	650	1776	757	989	30	132	258	210	23	210	360
PHS 100 700	700	1888,5	807	1051,5	30	132	258	210	23	220	350
PHS 100 750	750	2001	857	1114	30	132	258	210	23	230	340
PHS 100 800	800	2113,5	907	1176,5	30	132	258	210	23	240	330


ACCESSORIES - HYDRAULIC BUFFERS

Revision number: T10125-01-D



Revision date: 20.09.2019

PHS 125

Type FM



Type RM



PHS 125 100-RM

Size Stroke Type

Dimensions in mm	S	L	L1	L2	B	D1	D2	D3	d	W (kJ) Capacity/Stroke	F (kN) Buffering Force
PHS 125 100	100	528,5	204,5	289	35	167	300	245	27	60	670
PHS 125 150	150	641	254,5	351,5	35	167	300	245	27	91	670
PHS 125 200	200	753,5	304,5	414	35	167	300	245	27	121	670
PHS 125 250	250	866	354,5	476,5	35	167	300	245	27	154	670
PHS 125 300	300	978,5	404,5	539	35	167	300	245	27	185	670
PHS 125 350	350	1091	454,5	601,5	35	167	300	245	27	215	670
PHS 125 400	400	1203,5	504,5	664	35	167	300	245	27	248	670
PHS 125 450	450	1316	554,5	726,5	35	167	300	245	27	275	650
PHS 125 500	500	1428,5	604,5	789	35	167	300	245	27	301	650
PHS 125 550	550	1541	654,5	851,5	35	167	300	245	27	325	630
PHS 125 600	600	1653,5	704,5	914	35	167	300	245	27	351	630
PHS 125 650	650	1766	754,5	976,5	35	167	300	245	27	377	630
PHS 125 700	700	1878,5	804,5	1039	35	167	300	245	27	393	610
PHS 125 750	750	1991	854,5	1101,5	35	167	300	245	27	414	610
PHS 125 800	800	2103,5	904,5	1164	35	167	300	245	27	435	590

Barrel-roller couplings

BARREL-ROLLER COUPLINGS





APPLICATIONS

- HOISTING DEVICE OF CRANES AND CONVEYORS INSTALLATIONS
- STEEL INDUSTRY
- HOISTING, GANTRY, STACKER AND CONTAINERS CRANES

MAIN CHARACTERISTICS



- CONNECT THE SLOW ROTATING SHAFT OF A GEARBOX TO THE ROPE DRUM OF HOISTING INSTALLATIONS
- CANCEL ALL THE CONSEQUENTIAL DISADVANTAGE OF A RIGID CONNECTION
- COMPENSATION OF ANGULAR AND AXIAL MISALIGNEMENT

BCS COUPLINGS

- All-steel design
- Connection between hub and sleeve performed by barrel rollers
- Possibility to disassemble the hub from the sleeve
- Roller seats, inside the sleeve, are precisely machined and hardened

Benefits include

- Consent elevated radial loads proper to the rope drum of a hoisting crane
- Easy mounting :
 - hub fitted on the shaft of the gearbox
 - sleeve bolted directly on the rope drum
 - the 2 parts of the coupling are separately assembled in their axial working position
- Wear minimized



SIME Brakes Industrial Braking Systems


Barrel-roller couplings

DRUMS - BARREL-ROLLER COUPLINGS TYPE BCS

Revision number: T10144-01-C

Revision date: 30.05.2018

Steel coupling designed to connect the slow rotating shaft of a gearbox to the rope drum of hoisting equipment.



COUPLING type BCS...		140	160	180	200	220	240	260	280	310	340	400	420	450	530	560	600	670	730
Bore d (mm)	pilot	30	30	30	50	50	60	60	60	70	70	90	90	100	100	120	120	140	140
	max	65	80	85	95	105	115	130	140	160	175	210	220	235	290	310	330	375	410
Dimensions (mm)	D	230	250	280	320	340	360	380	400	420	450	510	550	580	650	680	710	780	850
	M	90	110	120	135	145	163	183	195	225	255	310	325	350	425	455	490	555	615
	F h6	140	160	180	200	220	240	260	280	310	340	400	420	450	530	560	600	670	730
	T	42	42	42	45	45	45	45	45	45	60	60	60	60	65	65	81	81	81
	L	90	95	100	110	125	130	145	170	175	185	220	240	260	315	350	380	410	450
	H	12	12	12	15	15	15	15	15	15	20	20	20	20	25	25	25	25	25
	N	200	220	250	280	300	320	340	360	380	400	460	500	530	600	630	660	730	800
	G	110	130	142	157	175	195	215	231	261	286	346	361	386	461	491	526	591	651
Ø E H8		14	14	14	18	18	18	18	18	18	24	24	24	24	24	24	28	28	28
Nº holes		6	6	6	6	6	6	6	6	6	6	6	6	8	8	24	24	24	24
K h9		200	220	250	280	300	320	340	360	380	400	460	500	530	580	600	640	700	760
Weight (kg)		13	16	24	29	35	42	54	67	90	108	150	190	230	395	460	520	740	890
Nominal torque max. (daNm)		50	400	780	1350	1600	1850	2200	3200	4000	5100	7700	11250	13000	19000	31000	42000	54000	75000
Radial force (daN)		1200	1400	1800	2500	3100	3700	4200	5200	6300	7950	11250	12300	14500	20200	25000	30000	34000	39000

Premier Industrial Company Leading Brands

OTHER PRODUCT SOLUTIONS FROM **ALTRA MOTION**

Our comprehensive product offerings include various types of clutches and brakes, overrunning clutches, engineered bearing assemblies, gearing and gear motors along with linear motion products, belted drives, couplings, limit switches, precision motors, drives & controls, miniature motors and engine braking systems. With thousands of product solutions available, Altra provides true single source convenience while meeting specific customer requirements. Many major OEMs and end users prefer Altra products as their No. 1 choice for performance and reliability.

WWW.ALTRAMOTION.COM



Electric Clutches & Brakes

Inertia Dynamics
Matrix
Stromag
Warner Electric



Precision Motors & Automation

Kollmorgen



Heavy Duty Clutches & Brakes

Industrial Clutch
Stromag
Svendborg Brakes
Twiflex
Wichita Clutch



Miniature Motors

Portescap



Overrunning Clutches

Formsprag Clutch
Marland Clutch
Stieber



Linear Systems

Thomson



Engineered Couplings & Universal Joints

Ameridrives
Bibby Turboflex
Guardian Couplings
Huco
Lamiflex Couplings
Stromag
TB Wood's



Engine Braking Systems

Jacobs Vehicle Systems



Gear Drives & Gear Motors

Bauer Gear Motor
Boston Gear
Delroyd Worm Gear
Nuttall Gear



Specialty Components

Kilian
Stromag
TB Wood's

Stromag Facilities

Europe

Germany

Hansastraße 120
59425 Unna - Germany
+49 (0) 23 03 102 0
Clutches & Brakes, Couplings, Geared Cam Limit Switches, Discs, Wind Brakes

Dessauer Str. 10
06844 Dessau-Roßlau - Germany
+49 (0) 340 2190 0

Electromagnetic Clutches & Brakes

France

Avenue de l'Europe
18150 La Guerche sur L'Aubois - France
+33 (0)2 48 80 72 72
Disc Brakes & Drum Brakes

Great Britain

Amphill Road
Bedford, MK42 9RD - UK
+44 (0)1234 324347
Electromagnetic Clutches & Brakes, Industrial Caliper Brakes

North America

USA

31 Industrial Park Road
New Hartford, CT 06057 - USA
860-238-4783

Electromagnetic Clutches & Brakes

300 Indiana Highway 212
Michigan City, IN 46360 - USA
219-874-5248

Couplings

2800 Fisher Rd.
Wichita Falls, TX 76302 - USA
940-723-3400

Geared Cam Limit Switches, Industrial Caliper & Drum Brakes

South America

Brasil

Avenida João Paulo Ablas, 2970
Jardim da Glória, Cotia - SP,
06711-250 - Brasil
+55 (11) 4615-6300

Flexible Couplings, Bearing Isolators, and Coupling Guards

Asia Pacific

China

T40B -5, No. 1765 Chuan Qiao Road
Pudong 201206, Shanghai - China
Tel +86 21-60580600

Clutches & Brakes, Electromagnetic Clutches & Brakes, Couplings, Industrial Caliper & Drum Brakes, Discs, Geared Cam Limit Switches, Wind Brakes

India

Gat No.: 448/14, Shinde Vasti, Nighoje
Tal Khed, Pune- 410 501
+91 2135 622100

Clutches & Brakes, Electromagnetic Clutches & Brakes, Couplings, Industrial Caliper & Drum Brakes, Discs, Geared Cam Limit Switches, Wind Brakes

The Brands of Altra Motion

Couplings

Ameridrives
www.ameridrives.com

Bibby Turboflex
www.bibbyturboflex.com

Guardian Couplings
www.guardiancouplings.com

Huco
www.huco.com

Lamiflex Couplings
www.lamiflexcouplings.com

Stromag
www.stromag.com

TB Wood's
www.tbwoods.com

Linear Systems

Thomson
www.thomsonlinear.com

Warner Linear
www.warnerlinear.com

Geared Cam Limit Switches

Stromag
www.stromag.com

Engineered Bearing Assemblies

Kilian
www.kilianbearings.com

Electric Clutches & Brakes

Matrix
www.matrix-international.com

Stromag
www.stromag.com

Warner Electric
www.warnerelectric.com

Deltran
www.thomsonlinear.com

Belted Drives

TB Wood's
www.tbwoods.com

Heavy Duty Clutches & Brakes

Twiflex
www.twiflex.com

Stromag
www.stromag.com

Svendborg Brakes
www.svendborg-brakes.com

Wichita Clutch
www.wichitaclutch.com

Gearing & Specialty Components

Bauer Gear Motor
www.bauergears.com

Boston Gear
www.bostongear.com

Delevan
www.delevan.com

Delroyd Worm Gear
www.delroyd.com

Nuttall Gear
www.nuttallgear.com

Engine Braking Systems

Jacobs Vehicle Systems
[www.jacbsvehiclesystems.com](http://www.jacobsvehiclesystems.com)

Precision Motors & Automation

Kollmorgen
www.kollmorgen.com

Miniature Motors

Portescap
www.portescap.com

OVERRUNNING CLUTCHES

Formsprag Clutch
www.formsprag.com

Marland Clutch
www.marland.com

Stieber
www.stieberclutch.com

Neither the accuracy nor completeness of the information contained in this publication is guaranteed by the company and may be subject to change in its sole discretion. The operating and performance characteristics of these products may vary depending on the application, installation, operating conditions and environmental factors. The company's terms and conditions of sale can be viewed at <http://www.altramotion.com/terms-and-conditions/sales-terms-and-conditions>. These terms and conditions apply to any person who may buy, acquire or use a product referred to herein, including any person who buys from a licensed distributor of these branded products.

©2019 by Stromag LLC. All rights reserved. All trademarks in this publication are the sole and exclusive property of Stromag LLC or one of its affiliated companies.