



WQuattro

Super Premium Efficiency Motor

- Meet IE4 efficiency levels
- Low CO_{2eq} emissions

**European
Market**



WQuattro

The WQuattro line was developed for users who consider energy saving a priority. The WQuattro is an environmentally friendly motor which, due to its exceptional efficiency performance, demands less energy from the grid. This in turn translates into a low total cost of ownership and the reduction of CO_{2eq} emissions.

As a hybrid motor having a squirrel cage rotor fitted with high energy permanent magnets, the WQuattro is suitable for starting either direct on line or with a variable frequency drive.

When used with a variable frequency drive, the WQuattro may be operated with scalar control, making it ideal for variable torque applications such as pumps and fans.

Features

- Output: 0,37 up to 7,5 kW
- Frame: 80 up to 132M/L
- Insulation class: F (DT 80K)
- Voltage: 230/400, 400/690 or 525 V
- Polarity: 4 and 6 poles
- Colour: RAL 6021 (green)
- Squirrel cage rotor and high energy permanent magnets (NdFeB)
- Synchronous speed (operation)
- D.O.L. starting, as an induction motor
- Suitable for variable speed applications with scalar control
- W22 mechanical platform
- Meet IE4 efficiency levels

Benefits

- Interchangeable with induction motors (same output x frame ratio)
- No need for sensors/encoder in applications with frequency inverters
- No need for special protection overload relays
- Low bearing temperature – extended life and less maintenance
- Easy speed synchronization - multiple motors may be fed by the same inverter


Higher efficiency in the same frame size



NEMA, IEC 60034-30-1:2014 and WEG Comparison

	NEMA	IEC 60034-30-1	WEG
Super Premium Efficiency	-	IE4	WQuattro (exceeds IE4)
Premium Efficiency	NEMA Premium	IE3	W22 Premium Efficiency
High Efficiency	EPAct	IE2	W22 High Efficiency

Efficiency - 4 poles - 50 Hz - IEC




Efficiency values shown are according to IEC 60034-30-1.

Electrical features


Output		Frame	Full Load Torque (Nm)	Locked Rotor Current I/In	Locked Rotor Torque TI/Tn	Breakdown Torque Tb/Tn	Inertia J (kgm²)	Maximum load inertia Jc (kgm²)	Weight (kg)	Rated speed (rpm)	Efficiency			Power Factor			Full load current In at 400 V (A)
											% of full load						
kW	HP										50	75	100	50	75	100	
IV poles - 1500 rpm - 50 Hz																	
0,55	0,75	80	3,50	6,0	2,2	1,8	0,0022	0,0660	15,1	1500	80,4	83,6	84,2	0,61	0,77	0,85	1,11
0,75	1	80	4,78	6,1	2,4	2,3	0,0025	0,0750	15,5	1500	79,0	84,0	85,7	0,58	0,74	0,82	1,54
1,1	1,5	90L	7,01	7,0	3	2	0,0050	0,1500	23,0	1500	82,0	86,0	87,4	0,55	0,68	0,76	2,10
1,5	2	L90L	9,55	6,7	3,2	1,8	0,0058	0,1740	23,2	1500	83,5	86,8	88,2	0,53	0,66	0,74	3,32
2,2	3	100L	14,0	7,3	3,6	2,2	0,0080	0,2400	33,2	1500	86,0	89,0	90,2	0,67	0,80	0,87	4,05
3	4	L100L	19,1	6,6	3,5	1,9	0,0095	0,2850	33,8	1500	86,5	89,5	90,4	0,60	0,75	0,82	5,84
4	5,5	112M	25,5	6,3	3,1	2	0,0153	0,3510	41,8	1500	89,0	91,0	91,7	0,68	0,81	0,88	7,15
5,5	7,5	132S	35,0	8,2	3,8	2,5	0,0497	1,49	72,7	1500	89,0	92,0	92,5	0,76	0,88	0,93	9,23
7,5	10	132M/L	47,8	7,8	3,8	2,2	0,0606	1,82	87,6	1500	90,5	92,2	93,0	0,77	0,88	0,93	12,5
VI poles - 1000 rpm - 50 Hz																	
0,37	0,5	80	3,54	4,6	2,8	2,7	0,0024	0,0720	15,0	1000	66,6	75,5	79,6	0,37	0,53	0,66	1,02
0,55	0,75	80	5,26	4,3	2,7	2,2	0,0026	0,0780	16,0	1000	68,1	76,3	80,9	0,38	0,54	0,67	1,46
0,75	1	90S	7,17	5,2	2,5	1,6	0,0045	0,1350	22,0	1000	80,3	84,5	85,5	0,58	0,73	0,85	1,49
1,1	1,5	90L	10,5	5,2	2,8	1,7	0,0052	0,1560	24,0	1000	82,8	85,3	85,5	0,56	0,70	0,79	2,36
1,5	2	100L	14,3	5,1	3,2	2,4	0,0073	0,2430	30,0	1000	81,3	85,7	87,6	0,49	0,63	0,74	3,34
2,2	3	112M	21,0	5,0	2,3	1,7	0,0105	0,3150	39,0	1000	83,7	86,5	87,4	0,58	0,72	0,80	4,54
3	4	132S	28,7	5,7	3,5	2,2	0,0329	0,9870	55,0	1000	86,6	89,6	90,7	0,55	0,69	0,77	6,20
4	5,5	132M	38,2	5,5	3,5	2,1	0,0390	1,17	59,0	1000	87,4	90,1	91,0	0,53	0,67	0,76	7,83
5,5	7,5	132M/L	52,6	4,9	3,4	1,7	0,0436	1,31	63,0	1000	87,6	90,1	90,9	0,50	0,65	0,73	12,0
Optional Frames																	
4	5,5	132S	38,2	5,5	3,5	2,1	0,0390	1,17	59,0	1000	87,4	90,1	91,0	0,53	0,67	0,76	7,83
5,5	7,5	132S	52,6	4,9	3,4	1,7	0,0436	1,31	63,0	1000	87,6	90,1	90,9	0,50	0,65	0,73	12,0

Mechanical features

Frames 80 to 112



Frame 132



Frame	A	AA	AB	AC	AD	B	BA	BB	C	CA	DE Shaft						NDE Shaft					
											D	E	ES	F	G	GD	DA	EA	TS	FA	GB	GF
80	125	30,5	149	159	140	100	-	125,5	50	93	19j6	40	28	6	15,5	6	14j6	30	18	5	11	5
90S	140	36,5	164	179	157	100	-	131	56	104	24j6	50	36	8	20	7	16j6	40	28	5	13	5
90L	140	36,5	164	179	157	125	-	156	56	104	24j6	50	36	8	20	7	16j6	40	28	5	13	5
L90L	140	36,5	164	179	157	125	-	156	56	104	24j6	50	36	8	20	7	16j6	40	28	5	13	5
100L	160	40	188	199	167	140	-	173	63	118	28j6	60	45	8	24	7	22j6	50	36	6	18,5	6
L100L	160	40	188	199	167	140	-	173	63	118	28j6	60	45	8	24	7	22j6	50	36	6	18,5	6
112M	190	40,5	220	222	192	140	-	177	70	128	28j6	60	45	8	24	7	24j6	50	36	8	20	7
132S	216	35	248	272	220	140	55	187	89	150	38k6	80	63	10	33	8	28j6	60	45	8	24	7
132M	216	35	248	272	220	178	55	225	89	150	38k6	80	63	10	33	8	28j6	60	45	8	24	7
132M/L	216	35	248	272	220	178/203	55	250	89	150	38k6	80	63	10	33	8	28j6	60	45	8	24	7

Frame	H	HA	HC	HD	HH	HK	K	L	LC	LL	LM	S1	d1	d2	Bearings	
															DE	NDE
80	80	8	163	222	100	59	10	277	313	108,5	99	2xM20x1,5	DM6	DM4	6204 ZZ	6203 ZZ
90S	90	9	182	249	106	67	10	304	350	115	104	2xM25x1,5	DM8	DM6	6205 ZZ	6204 ZZ
90L	90	9	182		118,5	67	10	329	375	115	104	2xM25x1,5	DM8	DM6	6205 ZZ	6204 ZZ
L90L	90	9	182		118,5	67	10	360	406	115	104	2xM25x1,5	DM8	DM6	6205 ZZ	6204 ZZ
100L	100	10	205		133	67	12	376	431	115	104	2xM25x1,5	DM10	DM8	6206 ZZ	6205 ZZ
L100L	100	10	205	272	133	67	12	420	475	115	104	2xM25x1,5	DM10	DM8	6206 ZZ	6205 ZZ
112M	112	10	235		140	80	12	394	448	140	133	2xM32x1,5	DM10	DM8	6207 ZZ	6206 ZZ
132S	132	16	266		159	80	12	452	519	140	133	2xM32x1,5	DM12	DM10	6308 ZZ	6207 ZZ
132M	132	16	266		178	80	12	489	557	140	133	2xM32x1,5	DM12	DM10	6308 ZZ	6207 ZZ
132M/L	132	16	266	354	190,5	80	12	515	582	140	133	2xM32x1,5	DM12	DM10	6308 ZZ	6207 ZZ

WEG Worldwide Operations

ARGENTINA

San Francisco - Cordoba
Phone: +54 3564 421484
info-ar@weg.net

Cordoba - Cordoba
Phone: +54 351 4641366
weg-morbe@weg.com.ar

Buenos Aires
Phone: +54 11 42998000
ventas@pulverlux.com.ar

AUSTRALIA

Scoresby - Victoria
Phone: +61 3 97654600
info-au@weg.net

AUSTRIA

Markt Piesting - Wiener
Neustadt-Land
Phone: +43 2633 4040
watt@wattdrive.com

BELGIUM

Nivelles - Belgium
Phone: +32 67 888420
info-be@weg.net

BRAZIL

Jaraguá do Sul - Santa Catarina
Phone: +55 47 32764000
info-br@weg.net

CHILE

Santiago
Phone: +56 2 27848900
info-cl@weg.net

CHINA

Nantong - Jiangsu
Phone: +86 513 85989333
info-cn@weg.net

Changzhou - Jiangsu
Phone: +86 519 88067692
info-cn@weg.net

COLOMBIA

San Cayetano - Bogota
Phone: +57 1 4160166
info-co@weg.net

ECUADOR

El Batan - Quito
Phone: +593 2 5144339
ceccato@weg.net

FRANCE

Saint-Quentin-Fallavier - Isère
Phone: +33 4 74991135
info-fr@weg.net

GERMANY

Türnich - Kerpen
Phone: +49 2237 92910
info-de@weg.net

Balingen - Baden-Württemberg
Phone: +49 7433 90410
info@weg-antriebe.de

Homburg (Efze) - Hesse
Phone: +49 5681 99520
info@akh-antriebstechnik.de

GHANA

Accra
Phone: +233 30 2766490
info@zestghana.com.gh

INDIA

Bangalore - Karnataka
Phone: +91 80 41282007
info-in@weg.net

Hosur - Tamil Nadu
Phone: +91 4344 301577
info-in@weg.net

ITALY

Cinisello Balsamo - Milano
Phone: +39 2 61293535
info-it@weg.net

JAPAN

Yokohama - Kanagawa
Phone: +81 45 5503030
info-jp@weg.net

MALAYSIA

Shah Alam - Selangor
Phone: +60 3 78591626
info@wattdrive.com.my

MEXICO

Huehuetoca - Mexico
Phone: +52 55 53214275
info-mx@weg.net

Tizayuca - Hidalgo
Phone: +52 77 97963790

NETHERLANDS

Oldenzaal - Overijssel
Phone: +31 541 571080
info-nl@weg.net

PERU

La Victoria - Lima
Phone: +51 1 2097600
info-pe@weg.net

PORTUGAL

Maia - Porto
Phone: +351 22 9477700
info-pt@weg.net

RUSSIA and CIS

Saint Petersburg
Phone: +7 812 363 2172
sales-wes@weg.net

SOUTH AFRICA

Johannesburg
Phone: +27 11 7236000
info@zest.co.za

SPAIN

Coslada - Madrid
Phone: +34 91 6553008
wegiberia@wegiberia.es

SINGAPORE

Singapore
Phone: +65 68589081
info-sg@weg.net

Singapore
Phone: +65 68622220
watteuro@watteuro.com.sg

SCANDINAVIA

Mölnlycke - Sweden
Phone: +46 31 888000
info-se@weg.net

UK

Redditch - Worcestershire
Phone: +44 1527 513800
info-uk@weg.net

UNITED ARAB EMIRATES

Jebel Ali - Dubai
Phone: +971 4 8130800
info-ae@weg.net

USA

Duluth - Georgia
Phone: +1 678 2492000
info-us@weg.net

Minneapolis - Minnesota
Phone: +1 612 3788000


VENEZUELA

Valencia - Carabobo
Phone: +58 241 8210582
info-ve@weg.net

For those countries where there is not a WEG own operation, find our local distributor at www.weg.net.



WEG Group - Motors Business Unit
Jaraguá do Sul - SC - Brazil
Phone: +55 47 3276 4000
motores@weg.net
www.weg.net



Cod: 50025713 | Rev: 03 | Date (m/y): 07/2017
The values shown are subject to change without prior notice.