

Data Sheet

Remote Control R06 Receiver

The R06 receiver is highly customizable with many features and mounting kits to ensure reliable and safe operation in potentially dangerous applications.

Features

- Multiband Radio with Full-Duplex communication
- External LEDs for troubleshooting
- Highly field-customizable
- Removable EEPROM SIM module
- STOP: PLd, Category 3 according to EN ISO 13849-1:2008
- 6 digital outputs

Benefits

- Easy and fast maintenance
- Multi-feedback capability
- Frequency management against interferences

Applications

Industrial lifting and automation

Comprehensive technical literature is online at www.danfoss.com





Technical data

Description	Value
Stop function (400-900MHz)	Cat. 3-PLd
Ingress Protection rating	IP65/NEMA4
Frequency band - ERP	433.050 to 434.040 MHz; ERP<1mW
	434.040 to 434.790 MHz; ERP<10mW
	869.700 to 870.000 MHz; ERP<5mW
	902.000 to 928.000 MHz; ERP<1mW
Range Line of sight (guaranteed)	100m
AC power supply	48 - 230 Vac \pm 25% (Multivoltage) / 18-30 Vac (700mA)
DC power supply	8 - 36 Vdc (2A)
Antenna	Internal
Removable EEPROM	Internal
Signaling	External
STOP Outputs (400-900MHz)	1 (6A)
Start Relay	1 (6A)
Safety Relay	1 (6A)
ON/OFF outputs	6 (6A)
Proportional Outputs	N/A
CAN Bus Protocols	CANopen
ON/OFF inputs	Option
Analog inputs	Option
Response Time	100ms
Maximum Total output current	8A
Operating Temperature Range	-20 °C to 70 °C (-4 °F to 158 °F)
Storage Temperature Range (24h)	-25°C to 75°C (-13°F to 167°F)
Storage Temperature Range (long periods)	-25°C to 55°C (-13°F to 131°F)
Relative Humidity	max. 95% without condensation
Weight	640 grams
Dimensions (LxWxH mm)	151x129x61
Tether connection	N/A
Associated transmitters (400-900MHz)	Ikargo1, T70/1, T70/2, IK2
Options	
Inputs	4 Digital or 1 Proportional input board

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.