

VAF 111 series vacuum gauges are recommended for visually checking the vacuum level for maintenance, monitoring and adjustment purposes. They are mounted as options on modular vacuum pumps GVP series, reference GVO VAF11140.



## Industry-specific applications



See page 7/6.

| Characteristics |                  |    |      |    |    |    |         |  |
|-----------------|------------------|----|------|----|----|----|---------|--|
| Models          | D <sup>(1)</sup> | D1 | b1   | b2 | b3 | b4 | d       |  |
| VAF 111 40      | 40               | 43 | 32.5 | 12 | 52 | 4  | G1/8"-M |  |
| VAF 111 50      | 50               | 54 | 32.5 | 12 | 52 | 4  | G1/4"-M |  |
| VAF 111 63      | 63               | 68 | 32.5 | 12 | 52 | 4  | G1/4"-M |  |

(1) Flush-mounting diameter. All dimensions shown in (mm)

| Specifications |  |  |  |
|----------------|--|--|--|
| Damping        | By silicone movement - Patented                  |  |  |
| Ring           | Chrome   |  |  |
| Measuring      | Bourdon tube in CuSn                             |  |  |
| Precision      | cl.2.5 (± 2.5% of max. scale value)              |  |  |
| Housing        | Black ABS  |  |  |
| Temperature    | 0 to 60°C / 32 to 140°F                          |  |  |
| Flush-mounting | Ring included in the delivery                    |  |  |
| Option         | as per quantity, possibility of customized dial. |  |  |

## Dimensions





| For all orders, please specify:<br>Model + Version.<br>Example: VAF11150 |            |         |  |  |  |  |
|--|------------|---------|--|--|--|--|
| 1: Model   | 2: Version |         |  |  |  |  |
| VAF 111  | 40         | Ø 40 mm |  |  |  |  |
|  | 50         | Ø 50 mm |  |  |  |  |
|  | 63         | Ø 63 mm |  |  |  |  |