

Data Sheet

Remote Control MPCAN Receiver

The MPCAN receiver is highly customizable with many features and accessories, including a tether connection to the transmitter as an alternative to Wireless Radio Communication. The MPCAN is adapted to vehicles with CAN bus communications.

Features

- Available for 400-900 MHz and 2.4 GHz Frequency Bands
- External LEDs for troubleshooting
- Removable EEPROM SIM module
- 4 digital outputs/inputs

Benefits

- Highly field customizable
- Frequency management against interferences
- Easy and fast maintenance
- Full Duplex communication capability
- CANopen & J1939 in 2.4GHz model

Applications

- Construction and mining vehicles and cranes
- Industrial vehicles
- Agriculture and forestry

Comprehensive technical literature is online at www.danfoss.com





Technical data

Specification	Value
Stop function (400 - 900 MHz)	Cat. 3-PLd
Stop Function (2.4 GHz)	Cat. 4-PLe
Ingress protection	IP65/NEMA4
Frequency band - ERP	433.050 to 434.040 MHz; ERP<1 mW
	434.040 to 434.790 MHz; ERP<10mW
	869.700 to 870.000 MHz; ERP<5 mW
	902.000 to 928.000 MHz; ERP<1mW
	2405MHz to 2475MHz 20dBm/100mW
Range Line of sight (guaranteed)	100m
AC power supply	N/A
DC power supply	8 - 35 Vdc
Receiver Current Consumption	200mA
Antenna	External/Internal
Removable EEPROM	Internal
Signaling	External
STOP Outputs (400 - 900MHz)	2
STOP Outputs (2.4GHz)	2
Start Output	N/A
Safety Relay Output	N/A
ON/OFF outputs	4 (2A per output)
Proportional outputs	N/A
CAN Bus Protocols (400-900MHz)	CANopen
CAN Bus Protocols (2.4GHz)	CANopen, J1939
ON/OFF inputs	4
Proportional inputs	N/A
Reponse time	100ms
Maximum Total output current	7.5A
Operating temperature range	-20° C to +70° C (-4° F to +158° F)
Storage Temperature Range (24h)	-25°C to 75°C (-13°F to 167°F)
Storage Temperature Range (long periods)	-25°C to 55°C (-13°F to 131°F)
Relative Humidity	max. 95% without condensation
Weight	300 grams
Dimensions	117 x 133 x 36
Tether connection	Yes (M12 Connector)
Associated transmitters (400 - 900MHz)	Ikargo1, Ikargo2, T70 1, T70 2, T70 1 HALL, T70 2 HALL, T70 1 ATEX, T70 2 ATEX, IK2, IK3, IK4
Associated transmitters (2.4 GHz)	Ikompact, Ikore, IkoreB, IK2, IK3, IK4

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.